



API Reference

Amazon Elastic Container Registry



API Version 2015-09-21

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Elastic Container Registry: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchCheckLayerAvailability	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	7
Errors	7
Examples	8
See Also	9
BatchDeleteImage	11
Request Syntax	11
Request Parameters	11
Response Syntax	12
Response Elements	13
Errors	13
Examples	14
See Also	16
BatchGetImage	18
Request Syntax	18
Request Parameters	18
Response Syntax	19
Response Elements	20
Errors	20
Examples	22
See Also	23
BatchGetRepositoryScanningConfiguration	25
Request Syntax	25
Request Parameters	25
Response Syntax	25
Response Elements	26
Errors	26
See Also	27
CompleteLayerUpload	29

Request Syntax	29
Request Parameters	29
Response Syntax	30
Response Elements	31
Errors	31
See Also	33
CreatePullThroughCacheRule	35
Request Syntax	35
Request Parameters	35
Response Syntax	37
Response Elements	38
Errors	39
Examples	41
See Also	42
CreateRepository	44
Request Syntax	44
Request Parameters	44
Response Syntax	46
Response Elements	47
Errors	47
Examples	49
See Also	50
CreateRepositoryCreationTemplate	52
Request Syntax	52
Request Parameters	52
Response Syntax	55
Response Elements	56
Errors	57
Examples	58
See Also	60
DeleteLifecyclePolicy	61
Request Syntax	61
Request Parameters	61
Response Syntax	61
Response Elements	62
Errors	63

Examples	64
See Also	65
DeletePullThroughCacheRule	66
Request Syntax	66
Request Parameters	66
Response Syntax	67
Response Elements	67
Errors	68
See Also	69
DeleteRegistryPolicy	71
Response Syntax	71
Response Elements	71
Errors	71
See Also	72
DeleteRepository	74
Request Syntax	74
Request Parameters	74
Response Syntax	75
Response Elements	75
Errors	76
Examples	77
See Also	78
DeleteRepositoryCreationTemplate	79
Request Syntax	79
Request Parameters	79
Response Syntax	79
Response Elements	80
Errors	80
Examples	81
See Also	83
DeleteRepositoryPolicy	84
Request Syntax	84
Request Parameters	84
Response Syntax	84
Response Elements	85
Errors	85

Examples	86
See Also	88
DeleteSigningConfiguration	89
Response Syntax	89
Response Elements	89
Errors	90
See Also	90
DeregisterPullTimeUpdateExclusion	92
Request Syntax	92
Request Parameters	92
Response Syntax	92
Response Elements	92
Errors	93
Examples	94
See Also	95
DescribeImageReplicationStatus	96
Request Syntax	96
Request Parameters	96
Response Syntax	97
Response Elements	97
Errors	98
See Also	99
DescribeImages	100
Request Syntax	100
Request Parameters	101
Response Syntax	102
Response Elements	103
Errors	103
Examples	104
See Also	107
DescribeImageScanFindings	108
Request Syntax	108
Request Parameters	108
Response Syntax	109
Response Elements	112
Errors	113

Examples	115
See Also	120
DescribeImageSigningStatus	122
Request Syntax	122
Request Parameters	122
Response Syntax	123
Response Elements	123
Errors	124
See Also	125
DescribePullThroughCacheRules	127
Request Syntax	127
Request Parameters	127
Response Syntax	128
Response Elements	129
Errors	129
See Also	130
DescribeRegistry	132
Response Syntax	132
Response Elements	132
Errors	133
See Also	133
DescribeRepositories	135
Request Syntax	135
Request Parameters	135
Response Syntax	136
Response Elements	137
Errors	138
Examples	138
See Also	140
DescribeRepositoryCreationTemplates	141
Request Syntax	141
Request Parameters	141
Response Syntax	142
Response Elements	143
Errors	144
Examples	144

See Also	146
GetAccountSetting	147
Request Syntax	147
Request Parameters	147
Response Syntax	147
Response Elements	147
Errors	148
Examples	149
See Also	150
GetAuthorizationToken	151
Request Syntax	151
Request Parameters	151
Response Syntax	151
Response Elements	152
Errors	152
Examples	153
See Also	154
GetDownloadUrlForLayer	155
Request Syntax	155
Request Parameters	155
Response Syntax	156
Response Elements	156
Errors	157
See Also	158
GetLifecyclePolicy	159
Request Syntax	159
Request Parameters	159
Response Syntax	159
Response Elements	160
Errors	161
Examples	162
See Also	163
GetLifecyclePolicyPreview	164
Request Syntax	164
Request Parameters	164
Response Syntax	166

Response Elements	167
Errors	168
Examples	169
See Also	170
GetRegistryPolicy	172
Response Syntax	172
Response Elements	172
Errors	172
See Also	173
GetRegistryScanningConfiguration	175
Response Syntax	175
Response Elements	175
Errors	176
See Also	176
GetRepositoryPolicy	178
Request Syntax	178
Request Parameters	178
Response Syntax	178
Response Elements	179
Errors	179
Examples	180
See Also	182
GetSigningConfiguration	183
Response Syntax	183
Response Elements	183
Errors	184
See Also	185
InitiateLayerUpload	186
Request Syntax	186
Request Parameters	186
Response Syntax	187
Response Elements	187
Errors	187
See Also	188
ListImageReferrers	190
Request Syntax	190

Request Parameters	190
Response Syntax	192
Response Elements	192
Errors	193
Examples	194
See Also	195
ListImages	197
Request Syntax	197
Request Parameters	197
Response Syntax	199
Response Elements	199
Errors	200
Examples	200
See Also	202
ListPullTimeUpdateExclusions	203
Request Syntax	203
Request Parameters	203
Response Syntax	204
Response Elements	204
Errors	205
Examples	206
See Also	207
ListTagsForResource	208
Request Syntax	208
Request Parameters	208
Response Syntax	208
Response Elements	208
Errors	209
Examples	209
See Also	211
PutAccountSetting	212
Request Syntax	212
Request Parameters	212
Response Syntax	212
Response Elements	213
Errors	213

Examples	214
See Also	215
PutImage	217
Request Syntax	217
Request Parameters	217
Response Syntax	219
Response Elements	219
Errors	219
Examples	221
See Also	223
PutImageScanningConfiguration	224
Request Syntax	224
Request Parameters	224
Response Syntax	225
Response Elements	225
Errors	226
See Also	227
PutImageTagMutability	228
Request Syntax	228
Request Parameters	228
Response Syntax	229
Response Elements	230
Errors	230
Examples	231
See Also	232
PutLifecyclePolicy	234
Request Syntax	234
Request Parameters	234
Response Syntax	235
Response Elements	235
Errors	236
Examples	237
See Also	238
PutRegistryPolicy	239
Request Syntax	239
Request Parameters	239

Response Syntax	239
Response Elements	240
Errors	240
See Also	241
PutRegistryScanningConfiguration	242
Request Syntax	242
Request Parameters	242
Response Syntax	243
Response Elements	243
Errors	244
See Also	244
PutReplicationConfiguration	246
Request Syntax	246
Request Parameters	247
Response Syntax	247
Response Elements	247
Errors	248
See Also	248
PutSigningConfiguration	250
Request Syntax	250
Request Parameters	250
Response Syntax	251
Response Elements	251
Errors	251
See Also	252
RegisterPullTimeUpdateExclusion	253
Request Syntax	253
Request Parameters	253
Response Syntax	253
Response Elements	253
Errors	254
Examples	255
See Also	256
SetRepositoryPolicy	258
Request Syntax	258
Request Parameters	258

Response Syntax	259
Response Elements	259
Errors	260
Examples	261
See Also	262
StartImageScan	263
Request Syntax	263
Request Parameters	263
Response Syntax	264
Response Elements	264
Errors	265
Examples	267
See Also	268
StartLifecyclePolicyPreview	269
Request Syntax	269
Request Parameters	269
Response Syntax	270
Response Elements	270
Errors	271
Examples	272
See Also	273
TagResource	275
Request Syntax	275
Request Parameters	275
Response Elements	276
Errors	276
See Also	277
UntagResource	278
Request Syntax	278
Request Parameters	278
Response Elements	278
Errors	278
See Also	280
UpdateImageStorageClass	281
Request Syntax	281
Request Parameters	281

Response Syntax	282
Response Elements	282
Errors	283
Examples	284
See Also	287
UpdatePullThroughCacheRule	288
Request Syntax	288
Request Parameters	288
Response Syntax	289
Response Elements	289
Errors	291
See Also	292
UpdateRepositoryCreationTemplate	293
Request Syntax	293
Request Parameters	293
Response Syntax	296
Response Elements	297
Errors	297
Examples	298
See Also	300
UploadLayerPart	302
Request Syntax	302
Request Parameters	302
Response Syntax	304
Response Elements	304
Errors	305
See Also	307
ValidatePullThroughCacheRule	308
Request Syntax	308
Request Parameters	308
Response Syntax	309
Response Elements	309
Errors	311
See Also	311
Data Types	313
Attribute	316

Contents	316
See Also	316
AuthorizationData	317
Contents	317
See Also	317
AwsEcrContainerImageDetails	319
Contents	319
See Also	321
CvssScore	322
Contents	322
See Also	322
CvssScoreAdjustment	324
Contents	324
See Also	324
CvssScoreDetails	325
Contents	325
See Also	326
DescribeImagesFilter	327
Contents	327
See Also	327
EncryptionConfiguration	328
Contents	328
See Also	329
EncryptionConfigurationForRepositoryCreationTemplate	330
Contents	330
See Also	331
EnhancedImageScanFinding	332
Contents	332
See Also	335
Image	336
Contents	336
See Also	337
ImageDetail	338
Contents	338
See Also	341
ImageFailure	342

Contents	342
See Also	342
ImageIdentifier	344
Contents	344
See Also	344
ImageReferrer	345
Contents	345
See Also	346
ImageReplicationStatus	347
Contents	347
See Also	348
ImageScanFinding	349
Contents	349
See Also	350
ImageScanFindings	351
Contents	351
See Also	352
ImageScanFindingsSummary	353
Contents	353
See Also	353
ImageScanningConfiguration	355
Contents	355
See Also	355
ImageScanStatus	356
Contents	356
See Also	356
ImageSigningStatus	357
Contents	357
See Also	358
ImageTagMutabilityExclusionFilter	359
Contents	359
See Also	359
Layer	360
Contents	360
See Also	361
LayerFailure	362

Contents	362
See Also	362
LifecyclePolicyPreviewFilter	364
Contents	364
See Also	364
LifecyclePolicyPreviewResult	365
Contents	365
See Also	366
LifecyclePolicyPreviewSummary	367
Contents	367
See Also	367
LifecyclePolicyRuleAction	368
Contents	368
See Also	368
ListImageReferrersFilter	369
Contents	369
See Also	369
ListImagesFilter	370
Contents	370
See Also	370
PackageVulnerabilityDetails	371
Contents	371
See Also	372
PullThroughCacheRule	374
Contents	374
See Also	376
Recommendation	377
Contents	377
See Also	377
RegistryScanningConfiguration	378
Contents	378
See Also	378
RegistryScanningRule	379
Contents	379
See Also	379
Remediation	380

Contents	380
See Also	380
ReplicationConfiguration	381
Contents	381
See Also	381
ReplicationDestination	382
Contents	382
See Also	382
ReplicationRule	383
Contents	383
See Also	383
Repository	384
Contents	384
See Also	386
RepositoryCreationTemplate	387
Contents	387
See Also	390
RepositoryFilter	391
Contents	391
See Also	391
RepositoryScanningConfiguration	393
Contents	393
See Also	394
RepositoryScanningConfigurationFailure	395
Contents	395
See Also	395
Resource	397
Contents	397
See Also	397
ResourceDetails	399
Contents	399
See Also	399
ScanningRepositoryFilter	400
Contents	400
See Also	400
ScoreDetails	401

Contents	401
See Also	401
SigningConfiguration	402
Contents	402
See Also	402
SigningRepositoryFilter	403
Contents	403
See Also	403
SigningRule	405
Contents	405
See Also	405
SubjectIdentifier	407
Contents	407
See Also	407
Tag	408
Contents	408
See Also	408
TransitioningImageTotalCount	409
Contents	409
See Also	409
VulnerablePackage	410
Contents	410
See Also	411
Common Parameters	412
Common Errors	415

Welcome

Amazon Elastic Container Registry (Amazon ECR) is a managed container image registry service. Customers can use the familiar Docker CLI, or their preferred client, to push, pull, and manage images. Amazon ECR provides a secure, scalable, and reliable registry for your Docker or Open Container Initiative (OCI) images. Amazon ECR supports private repositories with resource-based permissions using IAM so that specific users or Amazon EC2 instances can access repositories and images.

Amazon ECR has service endpoints in each supported Region. For more information, see [Amazon ECR endpoints](#) in the *AWS General Reference*.

This document was last published on January 15, 2026.

Actions

The following actions are supported:

- [BatchCheckLayerAvailability](#)
- [BatchDeleteImage](#)
- [BatchGetImage](#)
- [BatchGetRepositoryScanningConfiguration](#)
- [CompleteLayerUpload](#)
- [CreatePullThroughCacheRule](#)
- [CreateRepository](#)
- [CreateRepositoryCreationTemplate](#)
- [DeleteLifecyclePolicy](#)
- [DeletePullThroughCacheRule](#)
- [DeleteRegistryPolicy](#)
- [DeleteRepository](#)
- [DeleteRepositoryCreationTemplate](#)
- [DeleteRepositoryPolicy](#)
- [DeleteSigningConfiguration](#)
- [DeregisterPullTimeUpdateExclusion](#)
- [DescribeImageReplicationStatus](#)
- [DescribeImages](#)
- [DescribeImageScanFindings](#)
- [DescribeImageSigningStatus](#)
- [DescribePullThroughCacheRules](#)
- [DescribeRegistry](#)
- [DescribeRepositories](#)
- [DescribeRepositoryCreationTemplates](#)
- [GetAccountSetting](#)
- [GetAuthorizationToken](#)
- [GetDownloadUrlForLayer](#)

- [GetLifecyclePolicy](#)
- [GetLifecyclePolicyPreview](#)
- [GetRegistryPolicy](#)
- [GetRegistryScanningConfiguration](#)
- [GetRepositoryPolicy](#)
- [GetSigningConfiguration](#)
- [InitiateLayerUpload](#)
- [ListImageReferrers](#)
- [ListImages](#)
- [ListPullTimeUpdateExclusions](#)
- [ListTagsForResource](#)
- [PutAccountSetting](#)
- [PutImage](#)
- [PutImageScanningConfiguration](#)
- [PutImageTagMutability](#)
- [PutLifecyclePolicy](#)
- [PutRegistryPolicy](#)
- [PutRegistryScanningConfiguration](#)
- [PutReplicationConfiguration](#)
- [PutSigningConfiguration](#)
- [RegisterPullTimeUpdateExclusion](#)
- [SetRepositoryPolicy](#)
- [StartImageScan](#)
- [StartLifecyclePolicyPreview](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateImageStorageClass](#)
- [UpdatePullThroughCacheRule](#)
- [UpdateRepositoryCreationTemplate](#)
- [UploadLayerPart](#)

- [ValidatePullThroughCacheRule](#)

BatchCheckLayerAvailability

Checks the availability of one or more image layers in a repository.

When an image is pushed to a repository, each image layer is checked to verify if it has been uploaded before. If it has been uploaded, then the image layer is skipped.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerDigests": [ "string" ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

layerDigests

The digests of the image layers to check.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

registryId

The AWS account ID associated with the registry that contains the image layers to check. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository that is associated with the image layers to check.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "layerDigest": "string"
    }
  ],
  "layers": [
    {
      "layerAvailability": "string",
      "layerDigest": "string",
      "layerSize": number,
      "mediaType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures

Any failures associated with the call.

Type: Array of [LayerFailure](#) objects

layers

A list of image layer objects corresponding to the image layer references in the request.

Type: Array of [Layer](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example checks the availability of an image layer in the amazonlinux repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 126
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchCheckLayerAvailability
X-Amz-Date: 20161216T195733Zc
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "layerDigests": [
    "sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8"
  ],
  "repositoryName": "amazonlinux"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:57:33 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 233
Connection: keep-alive
x-amzn-RequestId: e2422faf-c3c9-11e6-a3ee-63b3b5dcf3b9

{
  "failures": [],
  "layers": [
    {
      "layerAvailability": "AVAILABLE",
      "layerDigest":
"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8",
      "layerSize": 91768077,
      "mediaType": "application/vnd.docker.image.rootfs.diff.tar.gzip"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchDeleteImage

Deletes a list of specified images within a repository. Images are specified with either an `imageTag` or `imageDigest`.

You can remove a tag from an image by specifying the image's tag in your request. When you remove the last tag from an image, the image is deleted from your repository.

You can completely delete an image (and all of its tags) by specifying the image's digest in your request.

Request Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageIds

A list of image ID references that correspond to images to delete. The format of the `imageIds` reference is `imageTag=tag` or `imageDigest=digest`.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

registryId

The AWS account ID associated with the registry that contains the image to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The repository that contains the image to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "imageId": {
        "imageDigest": "string",
        "imageTag": "string"
      }
    }
  ],
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures

Any failures associated with the call.

Type: Array of [ImageFailure](#) objects

imageIds

The image IDs of the deleted images.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes an image in the ubuntu repository with the imageTag value of xenial.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 66
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchDeleteImage
X-Amz-Date: 20161216T193711Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu",
  "imageIds": [
    {
```

```
    "imageTag": "xenial"
  }
]
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:37:11 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 138
Connection: keep-alive
x-amzn-RequestId: 09cc7023-c3c7-11e6-8acf-61b7dd8abe56

{
  "failures": [],
  "imageIds": [
    {
      "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",
      "imageTag": "xenial"
    }
  ]
}
```

Example

This example deletes an image (and all of its tags) in the ubuntu repository with the `imageDigest` value of `sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a`.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 134
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchDeleteImage
X-Amz-Date: 20161216T194250Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
```

Authorization: AUTHPARAMS

```
{
  "repositoryName": "ubuntu",
  "imageIds": [
    {
      "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:42:50 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 248
Connection: keep-alive
x-amzn-RequestId: d441a9f6-c3c7-11e6-8acf-61b7dd8abe56

{
  "failures": [],
  "imageIds": [
    {
      "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",
      "imageTag": "xenial"
    },
    {
      "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",
      "imageTag": "latest"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetImage

Gets detailed information for an image. Images are specified with either an `imageTag` or `imageDigest`.

When an image is pulled, the BatchGetImage API is called once to retrieve the image manifest.

Request Syntax

```
{
  "acceptedMediaTypes": [ "string" ],
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[acceptedMediaTypes](#)

The accepted media types for the request.

Valid values: `application/vnd.docker.distribution.manifest.v1+json` | `application/vnd.docker.distribution.manifest.v2+json` | `application/vnd.oci.image.manifest.v1+json`

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

imageIds

A list of image ID references that correspond to images to describe. The format of the imageIds reference is imageTag=tag or imageDigest=digest.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

registryId

The AWS account ID associated with the registry that contains the images to describe. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The repository that contains the images to describe.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "imageId": {
        "imageDigest": "string",
```

```
        "imageTag": "string"
      }
    ],
    "images": [
      {
        "imageId": {
          "imageDigest": "string",
          "imageTag": "string"
        },
        "imageManifest": "string",
        "imageManifestMediaType": "string",
        "registryId": "string",
        "repositoryName": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures

Any failures associated with the call.

Type: Array of [ImageFailure](#) objects

images

A list of image objects corresponding to the image references in the request.

Type: Array of [Image](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UnableToGetUpstreamImageException

The image or images were unable to be pulled using the pull through cache rule. This is usually caused because of an issue with the Secrets Manager secret containing the credentials for the upstream registry.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes an image in the amazonlinux repository with the imageTag value of latest.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 71
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchGetImage
X-Amz-Date: 20161216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "amazonlinux",
  "imageIds": [
    {
      "imageTag": "latest"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
```

```

Date: Fri, 16 Dec 2016 19:53:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 800
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54

{
  "failures": [],
  "images": [
    {
      "imageId": {
        "imageDigest":
"sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
        "imageTag": "latest"
      },
      "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType
\": \"application/vnd.docker.distribution.manifest.v2+json
\", \n  \"config\": {\n    \"mediaType\": \"application/
vnd.docker.container.image.v1+json\", \n    \"size\": 1486, \n    \"digest\":
\"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\" \n
    }, \n    \"layers\": [\n      {\n        \"mediaType\": \"application/
vnd.docker.image.rootfs.diff.tar.gzip\", \n        \"size\": 91768077, \n
        \"digest\":
\"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\" \n
      } \n    ] \n  }",
      "registryId": "012345678910",
      "repositoryName": "amazonlinux"
    }
  ]
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetRepositoryScanningConfiguration

Gets the scanning configuration for one or more repositories.

Request Syntax

```
{  
  "repositoryNames": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

repositoryNames

One or more repository names to get the scanning configuration for.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{  
  "failures": [  
    {  
      "failureCode": "string",  
      "failureReason": "string",  
      "repositoryName": "string"  
    }  
  ],  
  "scanningConfigurations": [  
    {  
      "repositoryName": "string",  
      "scanningConfigurationName": "string",  
      "scanningConfigurationType": "string",  
      "scanningConfigurationData": "string"  
    }  
  ]  
}
```

```
{
  "appliedScanFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "repositoryArn": "string",
  "repositoryName": "string",
  "scanFrequency": "string",
  "scanOnPush": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures

Any failures associated with the call.

Type: Array of [RepositoryScanningConfigurationFailure](#) objects

scanningConfigurations

The scanning configuration for the requested repositories.

Type: Array of [RepositoryScanningConfiguration](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CompleteLayerUpload

Notifies Amazon ECR that the image layer upload has completed for a specified registry, repository name, and upload ID. You can optionally provide a sha256 digest of the image layer for data validation purposes.

When an image is pushed, the CompleteLayerUpload API is called once per each new image layer to verify that the upload has completed.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerDigests": [ "string" ],
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

layerDigests

The sha256 digest of the image layer.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: Yes

registryId

The AWS account ID associated with the registry to which to upload layers. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository to associate with the image layer.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

uploadId

The upload ID from a previous [InitiateLayerUpload](#) operation to associate with the image layer.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

Response Syntax

```
{
  "layerDigest": "string",
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

layerDigest

The sha256 digest of the image layer.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

uploadId

The upload ID associated with the layer.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EmptyUploadException

The specified layer upload does not contain any layer parts.

message

The error message associated with the exception.

HTTP Status Code: 400

InvalidLayerException

The layer digest calculation performed by Amazon ECR upon receipt of the image layer does not match the digest specified.

message

The error message associated with the exception.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

LayerAlreadyExistsException

The image layer already exists in the associated repository.

message

The error message associated with the exception.

HTTP Status Code: 400

LayerPartTooSmallException

Layer parts must be at least 5 MiB in size.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UploadNotFoundException

The upload could not be found, or the specified upload ID is not valid for this repository.

message

The error message associated with the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePullThroughCacheRule

Creates a pull through cache rule. A pull through cache rule provides a way to cache images from an upstream registry source in your Amazon ECR private registry. For more information, see [Using pull through cache rules](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{  
  "credentialArn": "string",  
  "customRoleArn": "string",  
  "ecrRepositoryPrefix": "string",  
  "registryId": "string",  
  "upstreamRegistry": "string",  
  "upstreamRegistryUrl": "string",  
  "upstreamRepositoryPrefix": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[credentialArn](#)

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret that identifies the credentials to authenticate to the upstream registry.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\/[a-zA-Z0-9\_+\.@-]+$`

Required: No

[customRoleArn](#)

Amazon Resource Name (ARN) of the IAM role to be assumed by Amazon ECR to authenticate to the ECR upstream registry. This role must be in the same account as the registry that you are configuring.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

ecrRepositoryPrefix

The repository name prefix to use when caching images from the source registry.

Important

There is always an assumed / applied to the end of the prefix. If you specify `ecr-public` as the prefix, Amazon ECR treats that as `ecr-public/`.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*)/*)[a-z0-9]+(?:?:[._-][a-z0-9]+)*/(?:ROOT)$`

Required: Yes

registryId

The AWS account ID associated with the registry to create the pull through cache rule for. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

upstreamRegistry

The name of the upstream registry.

Type: String

Valid Values: `ecr` | `ecr-public` | `quay` | `k8s` | `docker-hub` | `github-container-registry` | `azure-container-registry` | `gitlab-container-registry`

Required: No

upstreamRegistryUrl

The registry URL of the upstream public registry to use as the source for the pull through cache rule. The following is the syntax to use for each supported upstream registry.

- Amazon ECR (ecr) – `<accountId>.dkr.ecr.<region>.amazonaws.com`
- Amazon ECR Public (ecr-public) – `public.ecr.aws`
- Docker Hub (docker-hub) – `registry-1.docker.io`
- GitHub Container Registry (github-container-registry) – `ghcr.io`
- GitLab Container Registry (gitlab-container-registry) – `registry.gitlab.com`
- Kubernetes (k8s) – `registry.k8s.io`
- Microsoft Azure Container Registry (azure-container-registry) – `<custom>.azurecr.io`
- Quay (quay) – `quay.io`

Type: String

Required: Yes

upstreamRepositoryPrefix

The repository name prefix of the upstream registry to match with the upstream repository name. When this field isn't specified, Amazon ECR will use the `ROOT`.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:?:[._-][a-z0-9]+)*/?|ROOT)$`

Required: No

Response Syntax

```
{  
  "createdAt": number,}
```

```
"credentialArn": "string",  
"customRoleArn": "string",  
"ecrRepositoryPrefix": "string",  
"registryId": "string",  
"upstreamRegistry": "string",  
"upstreamRegistryUrl": "string",  
"upstreamRepositoryPrefix": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time, in JavaScript date format, when the pull through cache rule was created.

Type: Timestamp

credentialArn

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\[a-zA-Z0-9\_/_+=.@-]+\`

customRoleArn

The ARN of the IAM role associated with the pull through cache rule.

Type: String

Length Constraints: Maximum length of 2048.

ecrRepositoryPrefix

The Amazon ECR repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

upstreamRegistry

The name of the upstream registry associated with the pull through cache rule.

Type: String

Valid Values: `ecr` | `ecr-public` | `quay` | `k8s` | `docker-hub` | `github-container-registry` | `azure-container-registry` | `gitlab-container-registry`

upstreamRegistryUrl

The upstream registry URL associated with the pull through cache rule.

Type: String

upstreamRepositoryPrefix

The upstream repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

PullThroughCacheRuleAlreadyExistsException

A pull through cache rule with these settings already exists for the private registry.

HTTP Status Code: 400

SecretNotFoundException

The ARN of the secret specified in the pull through cache rule was not found. Update the pull through cache rule with a valid secret ARN and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UnableToAccessSecretException

The secret is unable to be accessed. Verify the resource permissions for the secret and try again.

HTTP Status Code: 400

UnableToDecryptSecretValueException

The secret is accessible but is unable to be decrypted. Verify the resource permissions and try again.

HTTP Status Code: 400

UnsupportedUpstreamRegistryException

The specified upstream registry isn't supported.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a pull through cache rule for Docker Hub in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.CreatePullThroughCacheRule
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.13.22 Python/3.11.5 Darwin/16.7.0 botocore/1.12.180
X-Amz-Date: 20231003T155747Z
Authorization: AUTHPARAMS
Content-Length: 268

{
  "ecrRepositoryPrefix": "docker_hub",
  "upstreamRegistryUrl": "registry-1.docker.io",
  "credentialArn": "arn:aws:secretsmanager:us-
west-2:012345678910:secret:ECRPTCDockerHub-EXAMPLE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 180
Connection: keep-alive

{
  "ecrRepositoryPrefix": "docker_hub",
  "upstreamRegistryUrl": "registry-1.docker.io",
  "createdAt": "2023-10-03T15:57:48.411000+00:00",
  "registryId": "012345678910",
  "upstreamRegistry": "docker-hub",
  "credentialArn": "arn:aws:secretsmanager:us-
west-2:012345678910:secret:ECRPTCDockerHub-EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRepository

Creates a repository. For more information, see [Amazon ECR repositories](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{
  "encryptionConfiguration": {
    "encryptionType": "string",
    "kmsKey": "string"
  },
  "imageScanningConfiguration": {
    "scanOnPush": boolean
  },
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[encryptionConfiguration](#)

The encryption configuration for the repository. This determines how the contents of your repository are encrypted at rest.

Type: [EncryptionConfiguration](#) object

Required: No

[imageScanningConfiguration](#)

Important

The `imageScanningConfiguration` parameter is being deprecated, in favor of specifying the image scanning configuration at the registry level. For more information, see `PutRegistryScanningConfiguration`.

The image scanning configuration for the repository. This determines whether images are scanned for known vulnerabilities after being pushed to the repository.

Type: [ImageScanningConfiguration](#) object

Required: No

[imageTagMutability](#)

The tag mutability setting for the repository. If this parameter is omitted, the default setting of `MUTABLE` will be used which will allow image tags to be overwritten. If `IMMUTABLE` is specified, all image tags within the repository will be immutable which will prevent them from being overwritten.

Type: String

Valid Values: `MUTABLE` | `IMMUTABLE` | `IMMUTABLE_WITH_EXCLUSION` | `MUTABLE_WITH_EXCLUSION`

Required: No

[imageTagMutabilityExclusionFilters](#)

A list of filters that specify which image tags should be excluded from the repository's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

registryId

The AWS account ID associated with the registry to create the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name to use for the repository. The repository name may be specified on its own (such as `nginx-web-app`) or it can be prepended with a namespace to group the repository into a category (such as `project-a/nginx-web-app`).

The repository name must start with a letter and can only contain lowercase letters, numbers, hyphens, underscores, and forward slashes.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

tags

The metadata that you apply to the repository to help you categorize and organize them. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
```

```
"repository": {
  "createdAt": number,
  "encryptionConfiguration": {
    "encryptionType": "string",
    "kmsKey": "string"
  },
  "imageScanningConfiguration": {
    "scanOnPush": boolean
  },
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "registryId": "string",
  "repositoryArn": "string",
  "repositoryName": "string",
  "repositoryUri": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

repository

The repository that was created.

Type: [Repository](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

InvalidTagParameterException

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryAlreadyExistsException

The specified repository already exists in the specified registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a repository called `sample-repo` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.CreateRepository
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.16.190 Python/3.6.1 Darwin/16.7.0 botocore/1.12.180
X-Amz-Date: 20190715T204735Z
Authorization: AUTHPARAMS
Content-Length: 33

{
```

```
"repositoryName": "sample-repo"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 339
Connection: keep-alive

{
  "repository":{
    "repositoryArn":"arn:aws:ecr:us-west-2:012345678910:repository/sample-repo",
    "registryId":"012345678910",
    "repositoryName":"sample-repo",
    "repositoryUri":"012345678910.dkr.ecr.us-west-2.amazonaws.com/sample-repo",
    "createdAt":1.563223656E9,
    "imageTagMutability":"MUTABLE",
    "imageScanningConfiguration": {
      "scanOnPush": false
    }
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

CreateRepositoryCreationTemplate

Creates a repository creation template. This template is used to define the settings for repositories created by Amazon ECR on your behalf. For example, repositories created through pull through cache actions. For more information, see [Private repository creation templates](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{
  "appliedFor": [ "string" ],
  "customRoleArn": "string",
  "description": "string",
  "encryptionConfiguration": {
    "encryptionType": "string",
    "kmsKey": "string"
  },
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "lifecyclePolicy": "string",
  "prefix": "string",
  "repositoryPolicy": "string",
  "resourceTags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appliedFor

A list of enumerable strings representing the Amazon ECR repository creation scenarios that this template will apply towards. The supported scenarios are `PULL_THROUGH_CACHE`, `REPLICATION`, and `CREATE_ON_PUSH`

Type: Array of strings

Valid Values: `REPLICATION` | `PULL_THROUGH_CACHE` | `CREATE_ON_PUSH`

Required: Yes

customRoleArn

The ARN of the role to be assumed by Amazon ECR. This role must be in the same account as the registry that you are configuring. Amazon ECR will assume your supplied role when the `customRoleArn` is specified. When this field isn't specified, Amazon ECR will use the service-linked role for the repository creation template.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

description

A description for the repository creation template.

Type: String

Length Constraints: Maximum length of 256.

Required: No

encryptionConfiguration

The encryption configuration to use for repositories created using the template.

Type: [EncryptionConfigurationForRepositoryCreationTemplate](#) object

Required: No

imageTagMutability

The tag mutability setting for the repository. If this parameter is omitted, the default setting of `MUTABLE` will be used which will allow image tags to be overwritten. If `IMMUTABLE` is specified,

all image tags within the repository will be immutable which will prevent them from being overwritten.

Type: String

Valid Values: MUTABLE | IMMUTABLE | IMMUTABLE_WITH_EXCLUSION |
MUTABLE_WITH_EXCLUSION

Required: No

imageTagMutabilityExclusionFilters

A list of filters that specify which image tags should be excluded from the repository creation template's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

lifecyclePolicy

The lifecycle policy to use for repositories created using the template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 30720.

Required: No

prefix

The repository namespace prefix to associate with the template. All repositories created using this namespace prefix will have the settings defined in this template applied. For example, a prefix of prod would apply to all repositories beginning with prod/. Similarly, a prefix of prod/team would apply to all repositories beginning with prod/team/.

To apply a template to all repositories in your registry that don't have an associated creation template, you can use ROOT as the prefix.

Important

There is always an assumed / applied to the end of the prefix. If you specify ecr-public as the prefix, Amazon ECR treats that as ecr-public/. When using a pull

through cache rule, the repository prefix you specify during rule creation is what you should specify as your repository creation template prefix as well.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^((?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*/?|ROOT)$`

Required: Yes

[repositoryPolicy](#)

The repository policy to apply to repositories created using the template. A repository policy is a permissions policy associated with a repository to control access permissions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: No

[resourceTags](#)

The metadata to apply to the repository to help you categorize and organize. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "registryId": "string",
  "repositoryCreationTemplate": {
    "appliedFor": [ "string" ],
```

```
"createdAt": number,
"customRoleArn": "string",
"description": "string",
"encryptionConfiguration": {
  "encryptionType": "string",
  "kmsKey": "string"
},
"imageTagMutability": "string",
"imageTagMutabilityExclusionFilters": [
  {
    "filter": "string",
    "filterType": "string"
  }
],
"lifecyclePolicy": "string",
"prefix": "string",
"repositoryPolicy": "string",
"resourceTags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryCreationTemplate

The details of the repository creation template associated with the request.

Type: [RepositoryCreationTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TemplateAlreadyExistsException

The repository creation template already exists. Specify a unique prefix and try again.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a repository creation template in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 1134
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.CreateRepositoryCreationTemplate
X-Amz-Date: 20231216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
```

```
{
  "prefix": "eng/test",
  "description": "Repos for testing images",
  "encryptionConfiguration":
    {"encryptionType": "AES256"},
  "resourceTags":
    [
      {"Key": "environment",
        "Value": "test"}
    ],
  "imageTagMutability": "MUTABLE",
```

```

"repositoryPolicy": "{\r\n  \"Version\": \"2012-10-17\", \r\n  \"Statement\": [\r\n    {\r\n      \"Sid\": \"LambdaECRPullPolicy\", \r\n      \"Effect\": \"Allow\", \r\n      \"Principal\": {\r\n        \"Service\": \"lambda.amazonaws.com\" \r\n      }, \r\n      \"Action\": \"ecr:BatchGetImage\" \r\n    } \r\n  ] \r\n}",
"lifecyclePolicy": "{\r\n  \"rules\": [\r\n    {\r\n      \"rulePriority\": 1, \r\n      \"description\": \"Expire images older than 14 days\", \r\n      \"selection\": {\r\n        \"tagStatus\": \"untagged\", \r\n        \"countType\": \"sinceImagePushed\", \r\n        \"countUnit\": \"days\", \r\n        \"countNumber\": 14 \r\n      }, \r\n      \"action\": {\r\n        \"type\": \"expire\" \r\n      } \r\n    } \r\n  ] \r\n}",
"appliedFor":
["REPLICATION", "PULL_THROUGH_CACHE", "CREATE_ON_PUSH"]
}

```

Sample Response

```

HTTP/1.1 200 OK
Server: Server
Date: Sat, 16 Dec 2023 19:53:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 963
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54

{
  "registryId": "012345678901",
  "repositoryCreationTemplate":
  {
    "appliedFor":
      ["REPLICATION", "PULL_THROUGH_CACHE", "CREATE_ON_PUSH"],
    "description": "Repos for testing images",
    "encryptionConfiguration":
      {
        "encryptionType": "AES256"
      },
    "imageTagMutability": "MUTABLE",
    "lifecyclePolicy": "{\r\n  \"rules\": [\r\n    {\r\n      \"rulePriority\": 1, \r\n      \"description\": \"Expire images older than 14 days\", \r\n      \"selection\": {\r\n        \"tagStatus\": \"untagged\", \r\n        \"countType\": \"sinceImagePushed\", \r\n        \"countUnit\": \"days\", \r\n        \"countNumber\": 14 \r\n      }, \r\n      \"action\": {\r\n        \"type\": \"expire\" \r\n      } \r\n    } \r\n  ] \r\n}",

```

```
"prefix": "eng/test",
"repositoryPolicy": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\" : \"LambdaECRPullPolicy\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : {\n      \"Service\" : \"lambda.amazonaws.com\"\n    },\n    \"Action\" :\n    \"ecr:BatchGetImage\"\n  } ]\n}",
"resourceTags":
[
  {\"Key\": \"environment\",
   \"Value\": \"test\"}
],
"createdAt": "2023-12-16T17:29:02-07:00",
"updatedAt": "2023-12-16T17:29:02-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteLifecyclePolicy

Deletes the lifecycle policy associated with the specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
```

```
"lastEvaluatedAt": number,  
"lifecyclePolicyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastEvaluatedAt

The time stamp of the last time that the lifecycle policy was run.

Type: Timestamp

lifecyclePolicyText

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a lifecycle policy for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T223937Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "repositoryName": "project-a/amazon-ecs-sample",
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
```

```
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lastEvaluatedAt":1.504295007E9,
  "lifecyclePolicyText":{"rules":[{"rulePriority":1,"description":"Expire
images older than 14 days","selection":{"tagStatus":"untagged","countType":
"sinceImagePushed","countUnit":"days","countNumber":14},"action":{"type":
"expire"}}]}},
  "registryId":"012345678910",
  "repositoryName":"project-a/amazon-ecs-sample"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePullThroughCacheRule

Deletes a pull through cache rule.

Request Syntax

```
{  
  "ecrRepositoryPrefix": "string",  
  "registryId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ecrRepositoryPrefix

The Amazon ECR repository prefix associated with the pull through cache rule to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:?:[._-][a-z0-9]+)*/?)|ROOT)$`

Required: Yes

registryId

The AWS account ID associated with the registry that contains the pull through cache rule. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

Response Syntax

```
{
  "createdAt": number,
  "credentialArn": "string",
  "customRoleArn": "string",
  "ecrRepositoryPrefix": "string",
  "registryId": "string",
  "upstreamRegistryUrl": "string",
  "upstreamRepositoryPrefix": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The timestamp associated with the pull through cache rule.

Type: Timestamp

credentialArn

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\/[a-zA-Z0-9\/_+=.@-]+$`

customRoleArn

The ARN of the IAM role associated with the pull through cache rule.

Type: String

Length Constraints: Maximum length of 2048.

ecrRepositoryPrefix

The Amazon ECR repository prefix associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/|ROOT)$`

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

upstreamRegistryUrl

The upstream registry URL associated with the pull through cache rule.

Type: String

upstreamRepositoryPrefix

The upstream repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/|ROOT)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

PullThroughCacheRuleNotFoundException

The pull through cache rule was not found. Specify a valid pull through cache rule and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRegistryPolicy

Deletes the registry permissions policy.

Response Syntax

```
{
  "policyText": "string",
  "registryId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText

The contents of the registry permissions policy that was deleted.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RegistryPolicyNotFoundException

The registry doesn't have an associated registry policy.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRepository

Deletes a repository. If the repository isn't empty, you must either delete the contents of the repository or use the `force` option to delete the repository and have Amazon ECR delete all of its contents on your behalf.

Request Syntax

```
{  
  "force": boolean,  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

force

If true, deleting the repository force deletes the contents of the repository. If false, the repository must be empty before attempting to delete it.

Type: Boolean

Required: No

registryId

The AWS account ID associated with the registry that contains the repository to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "repository": {
    "createdAt": number,
    "encryptionConfiguration": {
      "encryptionType": "string",
      "kmsKey": "string"
    },
    "imageScanningConfiguration": {
      "scanOnPush": boolean
    },
    "imageTagMutability": "string",
    "imageTagMutabilityExclusionFilters": [
      {
        "filter": "string",
        "filterType": "string"
      }
    ],
    "registryId": "string",
    "repositoryArn": "string",
    "repositoryName": "string",
    "repositoryUri": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

repository

The repository that was deleted.

Type: [Repository](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

RepositoryNotEmptyException

The specified repository contains images. To delete a repository that contains images, you must force the deletion with the `force` parameter.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a repository named ubuntu in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteRepository
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.16.190 Python/3.6.1 Darwin/16.7.0 botocore/1.12.180
X-Amz-Date: 20190715T205933Z
Authorization: AUTHPARAMS
Content-Length: 33

{
  "repositoryName": "sample-repo"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 252
Connection: keep-alive

{
  "repository":{
    "createdAt":1.563223656E9,
    "registryId":"012345678910",
    "repositoryArn":"arn:aws:ecr:us-west-2:012345678910:repository/sample-repo",
    "repositoryName":"sample-repo",
    "repositoryUri":"012345678910.dkr.ecr.us-west-2.amazonaws.com/sample-repo"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRepositoryCreationTemplate

Deletes a repository creation template.

Request Syntax

```
{  
  "prefix": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

prefix

The repository namespace prefix associated with the repository creation template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:?:[._-][a-z0-9]+)*/?|ROOT)$`

Required: Yes

Response Syntax

```
{  
  "registryId": "string",  
  "repositoryCreationTemplate": {  
    "appliedFor": [ "string" ],  
    "createdAt": number,  
    "customRoleArn": "string",  
    "description": "string",  
    "encryptionConfiguration": {  
      "encryptionType": "string",  
      "kmsKey": "string"  
    }  
  }  
}
```

```
    },
    "imageTagMutability": "string",
    "imageTagMutabilityExclusionFilters": [
      {
        "filter": "string",
        "filterType": "string"
      }
    ],
    "lifecyclePolicy": "string",
    "prefix": "string",
    "repositoryPolicy": "string",
    "resourceTags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryCreationTemplate

The details of the repository creation template that was deleted.

Type: [RepositoryCreationTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TemplateNotFoundException

The specified repository creation template can't be found. Verify the registry ID and prefix and try again.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a repository creation template in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 88
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeRepositoryCreationTemplates
X-Amz-Date: 20231216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "prefix": "eng"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Sat, 16 Dec 2023 19:54:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 666
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54

{
  "registryId": "012345678901",
  "repositoryCreationTemplate": {
    "prefix": "eng",
    "encryptionConfiguration": {
      "encryptionType": "AES256"
    },
    "imageTagMutability": "MUTABLE"
  },
  "createdAt": "2023-12-03T16:27:57.933000-08:00",
  "updatedAt": "2023-12-03T16:27:57.933000-08:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRepositoryPolicy

Deletes the repository policy associated with the specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

registryId

The AWS account ID associated with the registry that contains the repository policy to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository that is associated with the repository policy to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
```

```
"policyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText

The JSON repository policy that was deleted from the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryPolicyNotFoundException

The specified repository and registry combination does not have an associated repository policy.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to

AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes the repository policy from the ubuntu repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteRepositoryPolicy
X-Amz-Date: 20151215T003722Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Tue, 15 Dec 2015 00:37:22 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: 01817918-a2c4-11e5-a19f-014c7a9aad99

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\n\" : \"AllowPull\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : \"*\",\n    \"Action\" : [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSigningConfiguration

Deletes the registry's signing configuration. Images pushed after deletion of the signing configuration will no longer be automatically signed.

For more information, see [Managed signing](#) in the *Amazon Elastic Container Registry User Guide*.

Note

Deleting the signing configuration does not affect existing image signatures.

Response Syntax

```
{
  "registryId": "string",
  "signingConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "signingProfileArn": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registryId

The AWS account ID associated with the registry.

Type: String

Pattern: [0-9]{12}

[signingConfiguration](#)

The registry's deleted signing configuration.

Type: [SigningConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

SigningConfigurationNotFoundException

The specified signing configuration was not found. This occurs when attempting to retrieve or delete a signing configuration that does not exist.

message

The error message associated with the exception.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterPullTimeUpdateExclusion

Removes a principal from the pull time update exclusion list for a registry. Once removed, Amazon ECR will resume updating the pull time if the specified principal pulls an image.

Request Syntax

```
{  
  "principalArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[principalArn](#)

The ARN of the IAM principal to remove from the pull time update exclusion list.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+):iam:[0-9]{12}:(role|user)/[\w+=,.\@-]+(/[ \w+=,.\@-]+)*$`

Required: Yes

Response Syntax

```
{  
  "principalArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

principalArn

The ARN of the IAM principal that was removed from the pull time update exclusion list.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+):iam:[0-9]{12}:(role|user)/[\w+=,.\@-]+(/[w+=,.\@-]+)*$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ExclusionNotFoundException

The specified pull time update exclusion was not found.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

To remove a principal from the pull time exclusion list

This example removes an IAM role from the pull time update exclusion list.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeregisterPullTimeUpdateExclusion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220830Z
Authorization: AUTHPARAMS
```

Content-Length: 73

```
{  
  "principalArn": "arn:aws:iam::012345678910:role/ECRAccess"  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f  
Content-Type: application/x-amz-json-1.1  
Content-Length: 73  
Connection: keep-alive
```

```
{  
  "principalArn": "arn:aws:iam::012345678910:role/ECRAccess"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImageReplicationStatus

Returns the replication status for a specified image.

Request Syntax

```
{  
  "imageId": {  
    "imageDigest": "string",  
    "imageTag": "string"  
  },  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

Required: Yes

registryId

The AWS account ID associated with the registry. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository that the image is in.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "replicationStatuses": [
    {
      "failureCode": "string",
      "region": "string",
      "registryId": "string",
      "status": "string"
    }
  ],
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

replicationStatuses

The replication status details for the images in the specified repository.

Type: Array of [ImageReplicationStatus](#) objects

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImages

Returns metadata about the images in a repository.

Note

Starting with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size. Therefore, Docker might return a larger image than the image shown in the AWS Management Console.

Important

The new version of Amazon ECR *Basic Scanning* doesn't use the [ImageDetail:imageScanFindingsSummary](#) and [ImageDetail:imageScanStatus](#) attributes from the API response to return scan results. Use the [DescribeImageScanFindings](#) API instead. For more information about AWS native basic scanning, see [Scan images for software vulnerabilities in Amazon ECR](#).

Request Syntax

```
{
  "filter": {
    "imageStatus": "string",
    "tagStatus": "string"
  },
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[filter](#)

The filter key and value with which to filter your DescribeImages results.

Type: [DescribeImagesFilter](#) object

Required: No

[imageIds](#)

The list of image IDs for the requested repository.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

[maxResults](#)

The maximum number of repository results returned by DescribeImages in paginated output. When this parameter is used, DescribeImages only returns maxResults results in a single page along with a nextToken response element. The remaining results of the initial request can be seen by sending another DescribeImages request with the returned nextToken value. This value can be between 1 and 1000. If this parameter is not used, then DescribeImages returns up to 100 results and a nextToken value, if applicable. This option cannot be used when you specify images with imageIds.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

The nextToken value returned from a previous paginated DescribeImages request where maxResults was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the nextToken value. This value

is `null` when there are no more results to return. This option cannot be used when you specify images with `imageIds`.

Type: String

Required: No

[registryId](#)

The AWS account ID associated with the registry that contains the repository in which to describe images. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

[repositoryName](#)

The repository that contains the images to describe.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageDetails": [
    {
      "artifactMediaType": "string",
      "imageDigest": "string",
      "imageManifestMediaType": "string",
      "imagePushedAt": number,
      "imageScanFindingsSummary": {
        "findingSeverityCounts": {
          "string" : number
        },
        "imageScanCompletedAt": number,
```

```
    "vulnerabilitySourceUpdatedAt": number
  },
  "imageScanStatus": {
    "description": "string",
    "status": "string"
  },
  "imageSizeInBytes": number,
  "imageStatus": "string",
  "imageTags": [ "string " ],
  "lastActivatedAt": number,
  "lastArchivedAt": number,
  "lastRecordedPullTime": number,
  "registryId": "string",
  "repositoryName": "string",
  "subjectManifestDigest": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageDetails

A list of [ImageDetail](#) objects that contain data about the image.

Type: Array of [ImageDetail](#) objects

nextToken

The nextToken value to include in a future DescribeImages request. When the results of a DescribeImages request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when

you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes the images in a repository named `hello-repository` in the default account. Note that the image with the digest `sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ecEXAMPLE` is tagged as `latest` and `tagtest`.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeImages
X-Amz-Date: 20220301T194641Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1

Authorization: AUTHPARAMS

{
  "repositoryName": "hello-repository"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:31:33 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 1107
Connection: keep-alive
x-amzn-RequestId: 404826b1-c3c6-11e6-a9e5-e3c203a2f07f

{
  "imageDetails": [
    {
```

```

        "registryId": "012345678910",
        "repositoryName": "hello-repository",
        "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ecEXAMPLE",
        "imageTags": [
            "tagtest"
        ],
        "imageSizeInBytes": 78447648,
        "imagePushedAt": "2021-12-03T20:36:09+00:00",
        "imageScanStatus": {
            "status": "COMPLETE",
            "description": "The scan was completed successfully."
        },
        "imageScanFindingsSummary": {
            "imageScanCompletedAt": "2021-12-03T20:36:14+00:00",
            "vulnerabilitySourceUpdatedAt": "2021-11-24T16:11:37+00:00",
            "findingSeverityCounts": {
                "HIGH": 4,
                "MEDIUM": 76,
                "INFORMATIONAL": 9,
                "LOW": 50
            }
        },
        "imageManifestMediaType": "application/
vnd.docker.distribution.manifest.v2+json",
        "artifactMediaType": "application/vnd.docker.container.image.v1+json",
        "lastRecordedPullTime": "2022-02-23T05:06:01.514000+00:00"
    },
    {
        "registryId": "012345678910",
        "repositoryName": "hello-repository",
        "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ecEXAMPLE",
        "imageTags": [
            "latest"
        ],
        "imageSizeInBytes": 78447648,
        "imagePushedAt": "2020-01-23T17:56:13+00:00",
        "imageScanStatus": {
            "status": "COMPLETE",
            "description": "The scan was completed successfully."
        },
        "imageScanFindingsSummary": {
            "imageScanCompletedAt": "2020-01-24T04:11:45+00:00",

```

```
        "vulnerabilitySourceUpdatedAt": "2020-01-23T20:25:17+00:00",
        "findingSeverityCounts": {
            "MEDIUM": 14,
            "INFORMATIONAL": 11,
            "LOW": 27
        },
        "imageManifestMediaType": "application/
vnd.docker.distribution.manifest.v2+json",
        "lastRecordedPullTime": "2022-02-24T07:35:16.530000+00:00"
    }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImageScanFindings

Returns the scan findings for the specified image.

Request Syntax

```
{  
  "imageId": {  
    "imageDigest": "string",  
    "imageTag": "string"  
  },  
  "maxResults": number,  
  "nextToken": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

Required: Yes

maxResults

The maximum number of image scan results returned by DescribeImageScanFindings in paginated output. When this parameter is used, DescribeImageScanFindings only returns maxResults results in a single page along with a nextToken response element. The remaining results of the initial request can be seen by sending another DescribeImageScanFindings request with the returned nextToken value. This value can be between 1 and 1000. If this parameter is not used, then DescribeImageScanFindings returns up to 100 results and a nextToken value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The nextToken value returned from a previous paginated DescribeImageScanFindings request where maxResults was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the nextToken value. This value is null when there are no more results to return.

Type: String

Required: No

registryId

The AWS account ID associated with the registry that contains the repository in which to describe the image scan findings for. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The repository for the image for which to describe the scan findings.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
```

```

},
"imageScanFindings": {
  "enhancedFindings": [
    {
      "awsAccountId": "string",
      "description": "string",
      "exploitAvailable": "string",
      "findingArn": "string",
      "firstObservedAt": number,
      "fixAvailable": "string",
      "lastObservedAt": number,
      "packageVulnerabilityDetails": {
        "cvss": [
          {
            "baseScore": number,
            "scoringVector": "string",
            "source": "string",
            "version": "string"
          }
        ],
        "referenceUrls": [ "string" ],
        "relatedVulnerabilities": [ "string" ],
        "source": "string",
        "sourceUrl": "string",
        "vendorCreatedAt": number,
        "vendorSeverity": "string",
        "vendorUpdatedAt": number,
        "vulnerabilityId": "string",
        "vulnerablePackages": [
          {
            "arch": "string",
            "epoch": number,
            "filePath": "string",
            "fixedInVersion": "string",
            "name": "string",
            "packageManager": "string",
            "release": "string",
            "sourceLayerHash": "string",
            "version": "string"
          }
        ]
      }
    },
    {
      "remediation": {
        "recommendation": {

```

```

        "text": "string",
        "url": "string"
    },
    "resources": [
        {
            "details": {
                "awsEcrContainerImage": {
                    "architecture": "string",
                    "author": "string",
                    "imageHash": "string",
                    "imageTags": [ "string" ],
                    "inUseCount": number,
                    "lastInUseAt": number,
                    "platform": "string",
                    "pushedAt": number,
                    "registry": "string",
                    "repositoryName": "string"
                }
            },
            "id": "string",
            "tags": {
                "string" : "string"
            },
            "type": "string"
        }
    ],
    "score": number,
    "scoreDetails": {
        "cvss": {
            "adjustments": [
                {
                    "metric": "string",
                    "reason": "string"
                }
            ],
            "score": number,
            "scoreSource": "string",
            "scoringVector": "string",
            "version": "string"
        }
    },
    "severity": "string",
    "status": "string",

```

```

        "title": "string",
        "type": "string",
        "updatedAt": number
    }
],
"findings": [
    {
        "attributes": [
            {
                "key": "string",
                "value": "string"
            }
        ],
        "description": "string",
        "name": "string",
        "severity": "string",
        "uri": "string"
    }
],
"findingSeverityCounts": {
    "string" : number
},
"imageScanCompletedAt": number,
"vulnerabilitySourceUpdatedAt": number
},
"imageScanStatus": {
    "description": "string",
    "status": "string"
},
"nextToken": "string",
"registryId": "string",
"repositoryName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

[imageScanFindings](#)

The information contained in the image scan findings.

Type: [ImageScanFindings](#) object

[imageScanStatus](#)

The current state of the scan.

Type: [ImageScanStatus](#) object

[nextToken](#)

The nextToken value to include in a future DescribeImageScanFindings request. When the results of a DescribeImageScanFindings request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[repositoryName](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ScanNotFoundException

The specified image scan could not be found. Ensure that image scanning is enabled on the repository and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example for basic image scanning

This example returns the image scan findings for an image using the image digest in a repository named `sample-repo` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 141
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeImageScanFindings
X-Amz-Date: 20200124T034807Z
User-Agent: aws-cli/1.16.310 Python/3.6.1 Darwin/18.7.0 botocore/1.13.46
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "sample-repo",
  "imageId": {
    "imageDigest":
      "sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
  }
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 24 Jan 2020 03:48:07 GMT
```

Content-Type: application/x-amz-json-1.1

Content-Length: 33967

Connection: keep-alive

x-amzn-RequestId: 3081a92b-2066-41f8-8a47-0580288ada9e

```
{
  "imageScanFindings": {
    "findings": [
      {
        "name": "CVE-2019-5188",
        "description": "A code execution vulnerability exists in the directory
rehashing functionality of E2fsprogs e2fsck 1.45.4. A specially crafted ext4 directory
can cause an out-of-bounds write on the stack, resulting in code execution. An
attacker can corrupt a partition to trigger this vulnerability.",
        "uri": "http://people.ubuntu.com/~ubuntu-security/cve/CVE-2019-5188",
        "severity": "MEDIUM",
        "attributes": [
          {
            "key": "package_version",
            "value": "1.44.1-1ubuntu1.1"
          },
          {
            "key": "package_name",
            "value": "e2fsprogs"
          },
          {
            "key": "CVSS2_VECTOR",
            "value": "AV:L/AC:L/Au:N/C:P/I:P/A:P"
          },
          {
            "key": "CVSS2_SCORE",
            "value": "4.6"
          }
        ]
      }
    ]
  },
  "imageScanCompletedAt": 1579839105.0,
  "vulnerabilitySourceUpdatedAt": 1579811117.0,
  "findingSeverityCounts": {
    "MEDIUM": 1
  }
},
"registryId": "012345678910",
"repositoryName": "sample-repo",
```

```
"imageId": {
  "imageDigest":
"sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
},
"imageScanStatus": {
  "status": "COMPLETE",
  "description": "The scan was completed successfully."
}
}
```

Example for enhanced image scanning

This example illustrates one usage of `DescribeImageScanFindings`.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 141
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeImageScanFindings
X-Amz-Date: 20250610T201255Z
User-Agent: aws-cli/1.16.310 Python/3.6.1 Darwin/18.7.0 botocore/1.13.46
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "registryId": "123456789012",
  "repositoryName": "sample-repo",
  "imageId": {
    "imageDigest":
"sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
  }
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Mon, 10 Jun 2025 20:12:55 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 33967
```

```

Connection: keep-alive
x-amzn-RequestId: 3081a92b-2066-41f8-8a47-0580288ada9e
{
  "imageScanFindings": {
    "enhancedFindings": [
      {
        "awsAccountId": "123456789012",
        "description": "xmlXIncludeAddNode in xinclude.c in libxml2 before
2.11.0 has a use-after-free.",
        "findingArn": "arn:aws:inspector2:us-
west-2:123456789012:finding/123456789012123456789012",
        "firstObservedAt": "2025-05-27T17:54:07.765000+00:00",
        "lastObservedAt": "2025-06-09T07:08:40.144000+00:00",
        "packageVulnerabilityDetails": {
          "cvss": [
            {
              "baseScore": 8.1,
              "scoringVector": "CVSS:3.1/AV:L/AC:H/PR:N/UI:N/S:C/C:H/I:H/
A:H",
              "source": "NVD",
              "version": "3.1"
            }
          ],
          "referenceUrls": [
            "https://bugs.debian.org/cgi-bin/bugreport.cgi?bug=1094238",
            "https://security-tracker.debian.org/tracker/CVE-2022-49043"
          ],
          "relatedVulnerabilities": [],
          "source": "DEBIAN_CVE",
          "sourceUrl": "https://security-tracker.debian.org/tracker/
CVE-2022-49043",
          "vendorSeverity": "not yet assigned",
          "vulnerabilityId": "CVE-2022-49043",
          "vulnerablePackages": [
            {
              "arch": "AMD64",
              "epoch": 0,
              "name": "libxml2",
              "packageManager": "OS",
              "release": "1.3~deb12u1",
              "sourceLayerHash":
"sha256:deb7d8874f38d4ec281d990aac2c7badbfcd5b97d602a388056e3f918a3f8cc7",
              "version": "2.9.14+dfsg",
              "fixedInVersion": "NotAvailable"
            }
          ]
        }
      }
    ]
  }
}

```

```

        }
      ]
    },
    "remediation": {
      "recommendation": {
        "text": "None Provided"
      }
    },
    "resources": [
      {
        "details": {
          "awsEcrContainerImage": {
            "architecture": "amd64",
            "imageHash":
"sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6",
            "imageTags": [
              "latest"
            ],
            "platform": "DEBIAN_12",
            "pushedAt": "2025-05-27T17:53:50.554000+00:00",
            "lastInUseAt": "2025-06-09T04:43:20.427000+00:00",
            "inUseCount": 1,
            "registry": "123456789012",
            "repositoryName": "sample-repo"
          }
        },
        "id": "arn:aws:ecr:us-west-2:123456789012:repository/sample-
repo/sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6",
        "tags": {},
        "type": "AWS_ECR_CONTAINER_IMAGE"
      }
    ],
    "score": 8.1,
    "scoreDetails": {
      "cvss": {
        "adjustments": [],
        "score": 8.1,
        "scoreSource": "NVD",
        "scoringVector": "CVSS:3.1/AV:L/AC:H/PR:N/UI:N/S:C/C:H/I:H/
A:H",
        "version": "3.1"
      }
    },
    "severity": "HIGH",

```

```
        "status": "ACTIVE",
        "title": "CVE-2022-49043 - libxml2",
        "type": "PACKAGE_VULNERABILITY",
        "updatedAt": "2025-06-09T07:08:40.144000+00:00",
        "fixAvailable": "NO",
        "exploitAvailable": "NO"
    },
],
"imageScanCompletedAt": "2025-06-09T07:08:40.144000+00:00",
"vulnerabilitySourceUpdatedAt": "2025-06-09T07:08:40.144000+00:00",
"findingSeverityCounts": {
    "HIGH": 1,
}
},
"registryId": "123456789012",
"repositoryName": "sample-repo",
"imageId": {
    "imageDigest":
"sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
},
"imageScanStatus": {
    "status": "ACTIVE",
    "description": "Continuous scan is selected for image."
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImageSigningStatus

Returns the signing status for a specified image. If the image matched signing rules that reference different signing profiles, a status is returned for each profile.

For more information, see [Managed signing](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageId

An object containing identifying information for an image.

Type: [ImageIdentifier](#) object

Required: Yes

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository that contains the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "registryId": "string",
  "repositoryName": "string",
  "signingStatuses": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "signingProfileArn": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageId

An object with identifying information for the image.

Type: [ImageIdentifier](#) object

registryId

The AWS account ID associated with the registry.

Type: String

Pattern: [0-9]{12}

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

signingStatuses

A list of signing statuses for the specified image. Each status corresponds to a signing profile.

Type: Array of [ImageSigningStatus](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DescribePullThroughCacheRules

Returns the pull through cache rules for a registry.

Request Syntax

```
{
  "ecrRepositoryPrefixes": [ "string" ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ecrRepositoryPrefixes](#)

The Amazon ECR repository prefixes associated with the pull through cache rules to return. If no repository prefix value is specified, all pull through cache rules are returned.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

Required: No

[maxResults](#)

The maximum number of pull through cache rules returned by `DescribePullThroughCacheRulesRequest` in paginated output. When this parameter is used, `DescribePullThroughCacheRulesRequest` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial

request can be seen by sending another `DescribePullThroughCacheRulesRequest` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter is not used, then `DescribePullThroughCacheRulesRequest` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The `nextToken` value returned from a previous paginated `DescribePullThroughCacheRulesRequest` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is null when there are no more results to return.

Type: String

Required: No

registryId

The AWS account ID associated with the registry to return the pull through cache rules for. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "pullThroughCacheRules": [
    {
      "createdAt": number,
      "credentialArn": "string",
```

```
    "customRoleArn": "string",
    "ecrRepositoryPrefix": "string",
    "registryId": "string",
    "updatedAt": number,
    "upstreamRegistry": "string",
    "upstreamRegistryUrl": "string",
    "upstreamRepositoryPrefix": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future DescribePullThroughCacheRulesRequest request. When the results of a DescribePullThroughCacheRulesRequest request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

pullThroughCacheRules

The details of the pull through cache rules.

Type: Array of [PullThroughCacheRule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

PullThroughCacheRuleNotFoundException

The pull through cache rule was not found. Specify a valid pull through cache rule and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRegistry

Describes the settings for a registry. The replication configuration for a repository can be created or updated with the [PutReplicationConfiguration](#) API action.

Response Syntax

```
{
  "registryId": "string",
  "replicationConfiguration": {
    "rules": [
      {
        "destinations": [
          {
            "region": "string",
            "registryId": "string"
          }
        ],
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ]
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[replicationConfiguration](#)

The replication configuration for the registry.

Type: [ReplicationConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.
message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.
message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRepositories

Describes image repositories in a registry.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "registryId": "string",  
  "repositoryNames": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of repository results returned by `DescribeRepositories` in paginated output. When this parameter is used, `DescribeRepositories` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `DescribeRepositories` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter is not used, then `DescribeRepositories` returns up to 100 results and a `nextToken` value, if applicable. This option cannot be used when you specify repositories with `repositoryNames`.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The `nextToken` value returned from a previous paginated `DescribeRepositories` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value

is `null` when there are no more results to return. This option cannot be used when you specify repositories with `repositoryNames`.

 Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

[registryId](#)

The AWS account ID associated with the registry that contains the repositories to be described. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

[repositoryNames](#)

A list of repositories to describe. If this parameter is omitted, then all repositories in a registry are described.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

Response Syntax

```
{
  "nextToken": "string",
```

```
"repositories": [  
  {  
    "createdAt": number,  
    "encryptionConfiguration": {  
      "encryptionType": "string",  
      "kmsKey": "string"  
    },  
    "imageScanningConfiguration": {  
      "scanOnPush": boolean  
    },  
    "imageTagMutability": "string",  
    "imageTagMutabilityExclusionFilters": [  
      {  
        "filter": "string",  
        "filterType": "string"  
      }  
    ],  
    "registryId": "string",  
    "repositoryArn": "string",  
    "repositoryName": "string",  
    "repositoryUri": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future DescribeRepositories request. When the results of a DescribeRepositories request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

repositories

A list of repository objects corresponding to valid repositories.

Type: Array of [Repository](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when

you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes the repositories in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeRepositories
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.16.190 Python/3.6.1 Darwin/16.7.0 botocore/1.12.180
X-Amz-Date: 20190715T205400Z
Authorization: AUTHPARAMS
Content-Length: 2

{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 1061
Connection: keep-alive

{
  "repositories": [
    {
      "createdAt": 1.563223656E9,
      "imageTagMutability": "MUTABLE",
      "registryId": "012345678910",
      "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/sample-repo",
      "repositoryName": "sample-repo",
      "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/sample-repo"
    },
    {
      "createdAt": 1.554824595E9,
      "imageTagMutability": "IMMUTABLE",
      "registryId": "012345678910",
```

```
    "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/tagging-test",  
    "repositoryName": "tagging-test",  
    "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/tagging-test"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRepositoryCreationTemplates

Returns details about the repository creation templates in a registry. The `prefixes` request parameter can be used to return the details for a specific repository creation template.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "prefixes": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of repository results returned by `DescribeRepositoryCreationTemplatesRequest` in paginated output. When this parameter is used, `DescribeRepositoryCreationTemplatesRequest` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `DescribeRepositoryCreationTemplatesRequest` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter is not used, then `DescribeRepositoryCreationTemplatesRequest` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The `nextToken` value returned from a previous paginated `DescribeRepositoryCreationTemplates` request where `maxResults` was used and

the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

 Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

prefixes

The repository namespace prefixes associated with the repository creation templates to describe. If this value is not specified, all repository creation templates are returned.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^((?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*/?|ROOT)$`

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "registryId": "string",
  "repositoryCreationTemplates": [
    {
      "appliedFor": [ "string" ],
      "createdAt": number,
      "customRoleArn": "string",
      "description": "string",
      "encryptionConfiguration": {
        "encryptionType": "string",
```

```
    "kmsKey": "string",
  },
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "lifecyclePolicy": "string",
  "prefix": "string",
  "repositoryPolicy": "string",
  "resourceTags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "updatedAt": number
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future DescribeRepositoryCreationTemplates request. When the results of a DescribeRepositoryCreationTemplates request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[repositoryCreationTemplates](#)

The details of the repository creation templates.

Type: Array of [RepositoryCreationTemplate](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a repository creation template in the default registry for an account.

Sample Request

```
PPOST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length:240
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeRepositoryCreationTemplates
X-Amz-Date: 20231216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "prefixes":
  [
    "eng"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Sat, 16 Dec 2023 19:54:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 1590
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54
{
  "registryId": "012345678901",
  "repositoryCreationTemplates": [{
    "prefix": "eng/test",
```

```
    "appliedFor": ["PULL_THROUGH_CACHE", "REPLICATION", "CREATE_ON_PUSH"],
    "encryptionConfiguration": {
      "encryptionType": "AES256"
    },
    "imageTagMutability": "MUTABLE",
    "createdAt": "2023-12-16T17:29:02-07:00",
    "updatedAt": "2023-12-16T19:55:02-07:00"
  }, {
    "prefix": "eng/replication-test",
    "appliedFor": ["REPLICATION"],
    "encryptionConfiguration": {
      "encryptionType": "AES256"
    },
    "imageTagMutability": "IMMUTABLE",
    "createdAt": "2023-12-14T17:29:02-07:00",
    "updatedAt": "2023-12-14T19:55:02-07:00"
  }]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountSetting

Retrieves the account setting value for the specified setting name.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the account setting, such as BASIC_SCAN_TYPE_VERSION or REGISTRY_POLICY_SCOPE.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "name": "string",  
  "value": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

name

Retrieves the name of the account setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

value

The setting value for the setting name. The following are valid values for the basic scan type being used: AWS_NATIVE or CLAIR. The following are valid values for the registry policy scope being used: V1 or V2.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example calls the BASIC_SCAN_TYPE_VERSION being used in the registry. The value returned will either be AWS_NATIVE or CLAIR.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetAccountSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T223937Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "aws ecr get-account-setting --name BASIC_SCAN_TYPE_VERSION,"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
```

```
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "name": "BASIC_SCAN_TYPE_VERSION",
  "value": "AWS_NATIVE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAuthorizationToken

Retrieves an authorization token. An authorization token represents your IAM authentication credentials and can be used to access any Amazon ECR registry that your IAM principal has access to. The authorization token is valid for 12 hours.

The `authorizationToken` returned is a base64 encoded string that can be decoded and used in a `docker login` command to authenticate to a registry. The AWS CLI offers an `get-login-password` command that simplifies the login process. For more information, see [Registry authentication](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{  
  "registryIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[registryIds](#)

This parameter has been deprecated.

A list of AWS account IDs that are associated with the registries for which to get `AuthorizationData` objects. If you do not specify a registry, the default registry is assumed.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `[0-9]{12}`

Required: No

Response Syntax

```
{
```

```
"authorizationData": [  
  {  
    "authorizationToken": "string",  
    "expiresAt": number,  
    "proxyEndpoint": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[authorizationData](#)

A list of authorization token data objects that correspond to the `registryIds` values in the request.

Note

The size of the authorization token returned by Amazon ECR is not fixed. We recommend that you don't make assumptions about the maximum size.

Type: Array of [AuthorizationData](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example gets an authorization token for your default registry.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetAuthorizationToken
X-Amz-Date: 20220516T185613Z
User-Agent: aws-cli/1.9.9 Python/2.7.10 Darwin/14.5.0 botocore/1.3.9
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Sun, 17 May 2022 06:56:13 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 1590
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "authorizationData": [
    {
      "authorizationToken": "QVdT0kNpQzErSHF1ZXZPcUR...",
      "expiresAt": "2022-05-17T06:56:13.652000+00:00",
      "proxyEndpoint": "https://012345678910.dkr.ecr.us-east-1.amazonaws.com"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDownloadUrlForLayer

Retrieves the pre-signed Amazon S3 download URL corresponding to an image layer. You can only get URLs for image layers that are referenced in an image.

When an image is pulled, the `GetDownloadUrlForLayer` API is called once per image layer that is not already cached.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerDigest": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

layerDigest

The digest of the image layer to download.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: Yes

registryId

The AWS account ID associated with the registry that contains the image layer to download. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository that is associated with the image layer to download.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "downloadUrl": "string",
  "layerDigest": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

downloadUrl

The pre-signed Amazon S3 download URL for the requested layer.

Type: String

layerDigest

The digest of the image layer to download.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LayerInaccessibleException

The specified layer is not available because it is not associated with an image. Unassociated image layers may be cleaned up at any time.

message

The error message associated with the exception.

HTTP Status Code: 400

LayersNotFoundException

The specified layers could not be found, or the specified layer is not valid for this repository.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UnableToGetUpstreamLayerException

There was an issue getting the upstream layer matching the pull through cache rule.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetLifecyclePolicy

Retrieves the lifecycle policy for the specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
```

```
"lastEvaluatedAt": number,  
"lifecyclePolicyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastEvaluatedAt

The time stamp of the last time that the lifecycle policy was run.

Type: Timestamp

lifecyclePolicyText

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example retrieves the lifecycle policy for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T210647Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 21:06:48 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 372
Connection: keep-alive
```

```
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lastEvaluatedAt":1.504295007E9,
  "lifecyclePolicyText":{"rules":[{"rulePriority":1,"description":"Expire
images older than 14 days","selection":{"tagStatus":"untagged","countType":
"sinceImagePushed","countUnit":"days","countNumber":14},"action":{"type":
"expire"}}]}},
  "registryId":"012345678910",
  "repositoryName":"project-a/amazon-ecs-sample"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetLifecyclePolicyPreview

Retrieves the results of the lifecycle policy preview request for the specified repository.

Request Syntax

```
{
  "filter": {
    "tagStatus": "string"
  },
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

filter

An optional parameter that filters results based on image tag status and all tags, if tagged.

Type: [LifecyclePolicyPreviewFilter](#) object

Required: No

imageIds

The list of imageIDs to be included.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

maxResults

The maximum number of repository results returned by `GetLifecyclePolicyPreviewRequest` in paginated output. When this parameter is used, `GetLifecyclePolicyPreviewRequest` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `GetLifecyclePolicyPreviewRequest` request with the returned `nextToken` value. This value can be between 1 and 100. If this parameter is not used, then `GetLifecyclePolicyPreviewRequest` returns up to 100 results and a `nextToken` value, if applicable. This option cannot be used when you specify images with `imageIds`.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The `nextToken` value returned from a previous paginated `GetLifecyclePolicyPreviewRequest` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return. This option cannot be used when you specify images with `imageIds`.

Type: String

Required: No

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyText": "string",
  "nextToken": "string",
  "previewResults": [
    {
      "action": {
        "targetStorageClass": "string",
        "type": "string"
      },
      "appliedRulePriority": number,
      "imageDigest": "string",
      "imagePushedAt": number,
      "imageTags": [ "string" ],
      "storageClass": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string",
  "status": "string",
  "summary": {
    "expiringImageTotalCount": number,
    "transitioningImageTotalCounts": [
      {
        "imageTotalCount": number,
        "targetStorageClass": "string"
      }
    ]
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyText

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

nextToken

The nextToken value to include in a future GetLifecyclePolicyPreview request. When the results of a GetLifecyclePolicyPreview request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

previewResults

The results of the lifecycle policy preview request.

Type: Array of [LifecyclePolicyPreviewResult](#) objects

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

status

The status of the lifecycle policy preview request.

Type: String

Valid Values: IN_PROGRESS | COMPLETE | EXPIRED | FAILED

summary

The list of images that is returned as a result of the action.

Type: [LifecyclePolicyPreviewSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LifecyclePolicyPreviewNotFoundException

There is no dry run for this repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example retrieves the result of a lifecycle policy preview for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetLifecyclePolicyPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
```

```
X-Amz-Date: 20170901T222304Z
```

```
Authorization: AUTHPARAMS
```

```
Content-Length: 48
```

```
{
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

Sample Response

```
HTTP/1.1 200 OK
```

```
Server: Server
```

```
Date: Fri, 01 Sep 2017 22:23:06 GMT
```

```
Content-Type: application/x-amz-json-1.1
```

```
Content-Length: 640
```

```
Connection: keep-alive
```

```
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
```

```
{
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}",
  "previewResults": [],
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample",
  "status": "COMPLETE",
  "summary": {"expiringImageTotalCount": 0}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRegistryPolicy

Retrieves the permissions policy for a registry.

Response Syntax

```
{
  "policyText": "string",
  "registryId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policyText](#)

The JSON text of the permissions policy for a registry.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RegistryPolicyNotFoundException

The registry doesn't have an associated registry policy.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRegistryScanningConfiguration

Retrieves the scanning configuration for a registry.

Response Syntax

```
{
  "registryId": "string",
  "scanningConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "scanFrequency": "string"
      }
    ],
    "scanType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[scanningConfiguration](#)

The scanning configuration for the registry.

Type: [RegistryScanningConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRepositoryPolicy

Retrieves the repository policy for the specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository with the policy to retrieve.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
```

```
"policyText": "string",  
"registryId": "string",  
"repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText

The JSON repository policy text associated with the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryPolicyNotFoundException

The specified repository and registry combination does not have an associated repository policy.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to

AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example gets the repository policy for the ubuntu repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetRepositoryPolicy
X-Amz-Date: 20151215T002404Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Tue, 15 Dec 2015 00:24:04 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: 25da0b72-a2c2-11e5-8543-ebda6fb1393b

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\n\" : \"AllowPull\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : \"*\",\n    \"Action\" : [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSigningConfiguration

Retrieves the registry's signing configuration, which defines rules for automatically signing images using AWS Signer.

For more information, see [Managed signing](#) in the *Amazon Elastic Container Registry User Guide*.

Response Syntax

```
{
  "registryId": "string",
  "signingConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "signingProfileArn": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[registryId](#)

The AWS account ID associated with the registry.

Type: String

Pattern: [0-9]{12}

[signingConfiguration](#)

The registry's signing configuration.

Type: [SigningConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

SigningConfigurationNotFoundException

The specified signing configuration was not found. This occurs when attempting to retrieve or delete a signing configuration that does not exist.

message

The error message associated with the exception.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

InitiateLayerUpload

Notifies Amazon ECR that you intend to upload an image layer.

When an image is pushed, the InitiateLayerUpload API is called once per image layer that has not already been uploaded. Whether or not an image layer has been uploaded is determined by the BatchCheckLayerAvailability API action.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

registryId

The AWS account ID associated with the registry to which you intend to upload layers. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository to which you intend to upload layers.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "partSize": number,
  "uploadId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

partSize

The size, in bytes, that Amazon ECR expects future layer part uploads to be.

Type: Long

Valid Range: Minimum value of 0.

uploadId

The upload ID for the layer upload. This parameter is passed to further [UploadLayerPart](#) and [CompleteLayerUpload](#) operations.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImageReferrers

Lists the artifacts associated with a specified subject image.

Note

The IAM principal invoking this operation must have the `ecr:BatchGetImage` permission.

Request Syntax

```
{
  "filter": {
    "artifactStatus": "string",
    "artifactTypes": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string",
  "subjectId": {
    "imageDigest": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

filter

The filter key and value with which to filter your `ListImageReferrers` results. If no filter is specified, only artifacts with ACTIVE status are returned.

Type: [ListImageReferrersFilter](#) object

Required: No

maxResults

The maximum number of image referrer results returned by `ListImageReferrers` in paginated output. When this parameter is used, `ListImageReferrers` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `ListImageReferrers` request with the returned `nextToken` value. This value can be between 1 and 50. If this parameter is not used, then `ListImageReferrers` returns up to 50 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

nextToken

The `nextToken` value returned from a previous paginated `ListImageReferrers` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

registryId

The AWS account ID associated with the registry that contains the repository in which to list image referrers. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository that contains the subject image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

subjectId

An object containing the image digest of the subject image for which to retrieve associated artifacts.

Type: [SubjectIdentifier](#) object

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "referrers": [
    {
      "annotations": {
        "string": "string"
      },
      "artifactStatus": "string",
      "artifactType": "string",
      "digest": "string",
      "mediaType": "string",
      "size": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future ListImageReferrers request. When the results of a ListImageReferrers request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

referrers

The list of artifacts associated with the subject image.

Type: Array of [ImageReferrer](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

To list artifacts associated with a subject image

This example lists all artifacts (such as Sigstore signatures) that reference a specific container image in the `sample-repo` repository.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.ListImageReferrers
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220033Z
Authorization: AUTHPARAMS
Content-Length: 150

{
```

```
"repositoryName": "sample-repo",
"subjectId": {
  "imageDigest":
"sha256:943e640159415616581703a53fa4ed87e96740655fd67daf2d2146a35337bce5"
}
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 470
Connection: keep-alive

{
  "referrers": [
    {
      "digest":
"sha256:270c60be5b6ed41e6e7c505ac0c4e2577748affc14147bcba76b533604dc7a07",
      "mediaType": "application/vnd.oci.image.manifest.v1+json",
      "artifactType": "application/vnd.dev.sigstore.bundle.v0.3+json",
      "size": 888,
      "annotations": {
        "dev.sigstore.bundle.predicateType": "https://sigstore.dev/cosign/sign/v1",
        "dev.sigstore.bundle.content": "dsse-envelope",
        "org.opencontainers.image.created": "2025-11-17T22:00:33Z"
      },
      "artifactStatus": "ACTIVE"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImages

Lists all the image IDs for the specified repository.

You can filter images based on whether or not they are tagged by using the `tagStatus` filter and specifying either `TAGGED`, `UNTAGGED` or `ANY`. For example, you can filter your results to return only `UNTAGGED` images and then pipe that result to a [BatchDeleteImage](#) operation to delete them. Or, you can filter your results to return only `TAGGED` images to list all of the tags in your repository.

Request Syntax

```
{
  "filter": {
    "imageStatus": "string",
    "tagStatus": "string"
  },
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[filter](#)

The filter key and value with which to filter your `ListImages` results.

Type: [ListImagesFilter](#) object

Required: No

[maxResults](#)

The maximum number of image results returned by `ListImages` in paginated output. When this parameter is used, `ListImages` only returns `maxResults` results in a single page along

with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `ListImages` request with the returned `nextToken` value. This value can be between 1 and 1000. If this parameter is not used, then `ListImages` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

`nextToken`

The `nextToken` value returned from a previous paginated `ListImages` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

`registryId`

The AWS account ID associated with the registry that contains the repository in which to list images. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

`repositoryName`

The repository with image IDs to be listed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageIds

The list of image IDs for the requested repository.

Type: Array of [ImageIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

nextToken

The nextToken value to include in a future ListImages request. When the results of a ListImages request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when

you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example lists all of the images in the amazonlinux repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 33
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.ListImages
X-Amz-Date: 20161216T200542Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AWUTHPARAMS

{
  "repositoryName": "amazonlinux"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 20:05:42 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 235
Connection: keep-alive
x-amzn-RequestId: 05bfc4ac-c3cb-11e6-99fb-b1be070cc24b

{
  "imageIds": [
    {
      "imageDigest":
        "sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
      "imageTag": "2016.09"
    },
    {
      "imageDigest":
        "sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
```

```
    "imageTag": "latest"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPullTimeUpdateExclusions

Lists the IAM principals that are excluded from having their image pull times recorded.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of pull time update exclusion results returned by ListPullTimeUpdateExclusions in paginated output. When this parameter is used, ListPullTimeUpdateExclusions only returns maxResults results in a single page along with a nextToken response element. The remaining results of the initial request can be seen by sending another ListPullTimeUpdateExclusions request with the returned nextToken value. This value can be between 1 and 1000. If this parameter is not used, then ListPullTimeUpdateExclusions returns up to 100 results and a nextToken value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The nextToken value returned from a previous paginated ListPullTimeUpdateExclusions request where maxResults was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the nextToken value. This value is null when there are no more results to return.

Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "pullTimeUpdateExclusions": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future ListPullTimeUpdateExclusions request. When the results of a ListPullTimeUpdateExclusions request exceed maxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

pullTimeUpdateExclusions

The list of IAM principal ARNs that are excluded from having their image pull times recorded.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+)*:iam:[0-9]{12}:(role|user)/[\w+=,.\@-]+(/[w+=,.\@-]+)*$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

To list all pull time update exclusions

This example lists all IAM principals that are excluded from having their image pull timestamps recorded in the registry.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.ListPullTimeUpdateExclusions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220830Z
Authorization: AUTHPARAMS
Content-Length: 2

{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 95
Connection: keep-alive

{
  "pullTimeUpdateExclusions": [
```

```
    "arn:aws:iam::012345678910:role/ECRAccess"  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List the tags for an Amazon ECR resource.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) that identifies the resource for which to list the tags. Currently, the only supported resource is an Amazon ECR repository.

Type: String

Required: Yes

Response Syntax

```
{  
  "tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[tags](#)

The tags for the resource.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example lists the tags associated with the `sample-repo` repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 81
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.ListTagsForResource
X-Amz-Date: 20161216T201255Z
User-Agent: aws-cli/1.16.310 Python/3.6.1 Darwin/18.7.0 botocore/1.13.46
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "resourceArn": "arn:aws:ecr:us-west-2:012345678910:repository/sample-repo"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 24 Jan 2020 03:48:07 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 11
Connection: keep-alive
x-amzn-RequestId: 3081a92b-2066-41f8-8a47-0580288ada9e

{
  "tags": [
    {
      "Key": "environment",
      "Value": "production"
    }
  ]
}
```

```
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutAccountSetting

Allows you to change the basic scan type version or registry policy scope.

Request Syntax

```
{  
  "name": "string",  
  "value": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the account setting, such as BASIC_SCAN_TYPE_VERSION or REGISTRY_POLICY_SCOPE.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

value

Setting value that is specified. The following are valid values for the basic scan type being used: AWS_NATIVE or CLAIR. The following are valid values for the registry policy scope being used: V1 or V2.

Type: String

Required: Yes

Response Syntax

```
{
```

```
"name": "string",  
"value": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

name

Retrieves the name of the account setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

value

Retrieves the value of the specified account setting.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example assigns the BASIC_SCAN_TYPE_VERSION to be used in the registry. The accepted values are AWS_NATIVE or CLAIR.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutAccountSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T223937Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  aws ecr put-account-setting --name BASIC_SCAN_TYPE_VERSION --value AWS_NATIVE,
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "name": "BASIC_SCAN_TYPE_VERSION",
  "value": "AWS_NATIVE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutImage

Creates or updates the image manifest and tags associated with an image.

When an image is pushed and all new image layers have been uploaded, the PutImage API is called once to create or update the image manifest and the tags associated with the image.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{
  "imageDigest": "string",
  "imageManifest": "string",
  "imageManifestMediaType": "string",
  "imageTag": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageDigest

The image digest of the image manifest corresponding to the image.

Type: String

Required: No

imageManifest

The image manifest corresponding to the image to be uploaded.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4194304.

Required: Yes

imageManifestMediaType

The media type of the image manifest. If you push an image manifest that does not contain the `mediaType` field, you must specify the `imageManifestMediaType` in the request.

Type: String

Required: No

imageTag

The tag to associate with the image. This parameter is optional.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

registryId

The AWS account ID associated with the registry that contains the repository in which to put the image. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository in which to put the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "image": {
    "imageId": {
      "imageDigest": "string",
      "imageTag": "string"
    },
    "imageManifest": "string",
    "imageManifestMediaType": "string",
    "registryId": "string",
    "repositoryName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

image

Details of the image uploaded.

Type: [Image](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageAlreadyExistsException

The specified image has already been pushed, and there were no changes to the manifest or image tag after the last push.

message

The error message associated with the exception.

HTTP Status Code: 400

ImageDigestDoesNotMatchException

The specified image digest does not match the digest that Amazon ECR calculated for the image.

HTTP Status Code: 400

ImageTagAlreadyExistsException

The specified image is tagged with a tag that already exists. The repository is configured for tag immutability.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.
message

The error message associated with the exception.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

LayersNotFoundException

The specified layers could not be found, or the specified layer is not valid for this repository.
message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ReferencedImagesNotFoundException

The manifest list is referencing an image that does not exist.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example puts an image to the amazonlinux repository with the tag 2016.09.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 653
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutImage
X-Amz-Date: 20161216T201255Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType\n\": \"application/vnd.docker.distribution.manifest.v2+json\n\", \n  \"config\": {\n    \"mediaType\": \"application/\nvnd.docker.container.image.v1+json\", \n    \"size\": 1486, \n    \"digest\":\n    \"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\"\n  }, \n  \"layers\": [\n    {\n      \"mediaType\": \"application/\nvnd.docker.image.rootfs.diff.tar.gzip\", \n      \"size\": 91768077, \n      \"digest\":\n      \"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\"\n    }\n  ]\n}\n",
  "repositoryName": "amazonlinux",
  "imageTag": "2016.09"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 20:12:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 786
Connection: keep-alive
x-amzn-RequestId: 084038f1-c3cc-11e6-8d10-9da51cf53fd3

{
  "image": {
```

```

    "imageId": {
      "imageDigest":
        "sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
      "imageTag": "2016.09"
    },
    "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType\n\": \"application/vnd.docker.distribution.manifest.v2+json\n\", \n  \"config\": {\n    \"mediaType\": \"application/\nvnd.docker.container.image.v1+json\", \n    \"size\": 1486, \n    \"digest\":\n      \"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\"\n  }, \n  \"layers\": [\n    {\n      \"mediaType\": \"application/\nvnd.docker.image.rootfs.diff.tar.gzip\", \n      \"size\": 91768077, \n      \"digest\":\n        \"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\"\n    }\n  ]\n}\n",
    "registryId": "012345678910",
    "repositoryName": "amazonlinux"
  }
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutImageScanningConfiguration

Important

The PutImageScanningConfiguration API is being deprecated, in favor of specifying the image scanning configuration at the registry level. For more information, see [PutRegistryScanningConfiguration](#).

Updates the image scanning configuration for the specified repository.

Request Syntax

```
{
  "imageScanningConfiguration": {
    "scanOnPush": boolean
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageScanningConfiguration

The image scanning configuration for the repository. This setting determines whether images are scanned for known vulnerabilities after being pushed to the repository.

Type: [ImageScanningConfiguration](#) object

Required: Yes

registryId

The AWS account ID associated with the registry that contains the repository in which to update the image scanning configuration setting. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName](#)

The name of the repository in which to update the image scanning configuration setting.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "imageScanningConfiguration": {
    "scanOnPush": boolean
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageScanningConfiguration](#)

The image scanning configuration setting for the repository.

Type: [ImageScanningConfiguration](#) object

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutImageTagMutability

Updates the image tag mutability settings for the specified repository. For more information, see [Image tag mutability](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[imageTagMutability](#)

The tag mutability setting for the repository. If `MUTABLE` is specified, image tags can be overwritten. If `IMMUTABLE` is specified, all image tags within the repository will be immutable which will prevent them from being overwritten.

Type: String

Valid Values: `MUTABLE` | `IMMUTABLE` | `IMMUTABLE_WITH_EXCLUSION` | `MUTABLE_WITH_EXCLUSION`

Required: Yes

[imageTagMutabilityExclusionFilters](#)

A list of filters that specify which image tags should be excluded from the image tag mutability setting being applied.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[registryId](#)

The AWS account ID associated with the registry that contains the repository in which to update the image tag mutability settings. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

[repositoryName](#)

The name of the repository in which to update the image tag mutability settings.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageTagMutability](#)

The image tag mutability setting for the repository.

Type: String

Valid Values: MUTABLE | IMMUTABLE | IMMUTABLE_WITH_EXCLUSION |
MUTABLE_WITH_EXCLUSION

[imageTagMutabilityExclusionFilters](#)

The list of filters that specify which image tags are excluded from the repository's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[repositoryName](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example updates the image tag mutability setting for the `sample-repo` repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 73
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutImageTagMutability
X-Amz-Date: 20161216T201255Z
User-Agent: aws-cli/1.16.310 Python/3.6.1 Darwin/18.7.0 botocore/1.13.46
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "sample-repo",
  "imageTagMutability": "IMMUTABLE"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 24 Jan 2020 03:48:07 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 98
Connection: keep-alive
x-amzn-RequestId: 3081a92b-2066-41f8-8a47-0580288ada9e

{
  "registryId": "012345678910",
  "repositoryName": "sample-repo",
  "imageTagMutability": "IMMUTABLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutLifecyclePolicy

Creates or updates the lifecycle policy for the specified repository. For more information, see [Lifecycle policy template](#).

Request Syntax

```
{  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[lifecyclePolicyText](#)

The JSON repository policy text to apply to the repository.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

Required: Yes

[registryId](#)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName](#)

The name of the repository to receive the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyText": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicyText](#)

The JSON repository policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

[repositoryName](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a lifecycle policy to expire images older than 14 days for a repository called project-a/amazon-ecs-sample in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T194217Z
Authorization: AUTHPARAMS
Content-Length: 535

{
  "repositoryName": "project-a/amazon-ecs-sample",
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\n\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n      }\n      \"countType\": \"sinceImagePushed\",\n      \"countUnit\": \"days\",\n      \"countNumber\": 14\n    },\n    {\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}"
```

Sample Response

```
HTTP/1.1 200 OK
```

```
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lifecyclePolicyText": "{\\"rules\\": [{\\"rulePriority\\": 1, \\"description\\": \\"Expire images older than 14 days\\", \\"selection\\": {\\"tagStatus\\": \\"untagged\\", \\"countType\\": \\"sinceImagePushed\\", \\"countUnit\\": \\"days\\", \\"countNumber\\": 14}, \\"action\\": {\\"type\\": \\"expire\\"}}]}",
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutRegistryPolicy

Creates or updates the permissions policy for your registry.

A registry policy is used to specify permissions for another AWS account and is used when configuring cross-account replication. For more information, see [Registry permissions](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{  
  "policyText": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[policyText](#)

The JSON policy text to apply to your registry. The policy text follows the same format as IAM policy text. For more information, see [Registry permissions](#) in the *Amazon Elastic Container Registry User Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: Yes

Response Syntax

```
{  
  "policyText": "string",  
  "registryId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText

The JSON policy text for your registry.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutRegistryScanningConfiguration

Creates or updates the scanning configuration for your private registry.

Request Syntax

```
{
  "rules": [
    {
      "repositoryFilters": [
        {
          "filter": "string",
          "filterType": "string"
        }
      ],
      "scanFrequency": "string"
    }
  ],
  "scanType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

rules

The scanning rules to use for the registry. A scanning rule is used to determine which repository filters are used and at what frequency scanning will occur.

Type: Array of [RegistryScanningRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Required: No

scanType

The scanning type to set for the registry.

When a registry scanning configuration is not defined, by default the BASIC scan type is used.

When basic scanning is used, you may specify filters to determine which individual repositories,

or all repositories, are scanned when new images are pushed to those repositories. Alternatively, you can do manual scans of images with basic scanning.

When the ENHANCED scan type is set, Amazon Inspector provides automated vulnerability scanning. You may choose between continuous scanning or scan on push and you may specify filters to determine which individual repositories, or all repositories, are scanned.

Type: String

Valid Values: BASIC | ENHANCED

Required: No

Response Syntax

```
{
  "registryScanningConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "scanFrequency": "string"
      }
    ],
    "scanType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registryScanningConfiguration

The scanning configuration for your registry.

Type: [RegistryScanningConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BlockedByOrganizationPolicyException

The operation did not succeed because the account is managed by a organization policy.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutReplicationConfiguration

Creates or updates the replication configuration for a registry. The existing replication configuration for a repository can be retrieved with the [DescribeRegistry](#) API action. The first time the PutReplicationConfiguration API is called, a service-linked IAM role is created in your account for the replication process. For more information, see [Using service-linked roles for Amazon ECR](#) in the *Amazon Elastic Container Registry User Guide*. For more information on the custom role for replication, see [Creating an IAM role for replication](#).

Note

When configuring cross-account replication, the destination account must grant the source account permission to replicate. This permission is controlled using a registry permissions policy. For more information, see [PutRegistryPolicy](#).

Request Syntax

```
{
  "replicationConfiguration": {
    "rules": [
      {
        "destinations": [
          {
            "region": "string",
            "registryId": "string"
          }
        ],
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ]
      }
    ]
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[replicationConfiguration](#)

An object representing the replication configuration for a registry.

Type: [ReplicationConfiguration](#) object

Required: Yes

Response Syntax

```
{
  "replicationConfiguration": {
    "rules": [
      {
        "destinations": [
          {
            "region": "string",
            "registryId": "string"
          }
        ],
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ]
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[replicationConfiguration](#)

The contents of the replication configuration for the registry.

Type: [ReplicationConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutSigningConfiguration

Creates or updates the registry's signing configuration, which defines rules for automatically signing images with AWS Signer.

For more information, see [Managed signing](#) in the *Amazon Elastic Container Registry User Guide*.

Note

To successfully generate a signature, the IAM principal pushing images must have permission to sign payloads with the AWS Signer signing profile referenced in the signing configuration.

Request Syntax

```
{
  "signingConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "signingProfileArn": "string"
      }
    ]
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[signingConfiguration](#)

The signing configuration to assign to the registry.

Type: [SigningConfiguration](#) object

Required: Yes

Response Syntax

```
{
  "signingConfiguration": {
    "rules": [
      {
        "repositoryFilters": [
          {
            "filter": "string",
            "filterType": "string"
          }
        ],
        "signingProfileArn": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[signingConfiguration](#)

The registry's updated signing configuration.

Type: [SigningConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterPullTimeUpdateExclusion

Adds an IAM principal to the pull time update exclusion list for a registry. Amazon ECR will not record the pull time if an excluded principal pulls an image.

Request Syntax

```
{  
  "principalArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

principalArn

The ARN of the IAM principal to exclude from having image pull times recorded.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+)*:iam:[0-9]{12}:(role|user)/[\w+=,.\@-]+(/[ \w+=,.\@-]+)*$`

Required: Yes

Response Syntax

```
{  
  "createdAt": number,  
  "principalArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time, expressed in standard JavaScript date format, when the exclusion was created.

Type: Timestamp

principalArn

The ARN of the IAM principal that was added to the pull time update exclusion list.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+):iam:[0-9]{12}:(role|user)/[\w+=,.\@-]+(/[ \w+=,.\@-]+)*$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ExclusionAlreadyExistsException

The specified pull time update exclusion already exists for the registry.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

To exclude an IAM role from pull time tracking

This example adds an IAM role to the pull time update exclusion list so that Amazon ECR will not record image pull timestamps for this principal.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.RegisterPullTimeUpdateExclusion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220812Z
Authorization: AUTHPARAMS
Content-Length: 73

{
  "principalArn": "arn:aws:iam::012345678910:role/ECRAccess"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 118
Connection: keep-alive

{
  "principalArn": "arn:aws:iam::012345678910:role/ECRAccess",
  "createdAt": "2025-11-17T22:08:12.659000+00:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

SetRepositoryPolicy

Applies a repository policy to the specified repository to control access permissions. For more information, see [Amazon ECR Repository policies](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{  
  "force": boolean,  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[force](#)

If the policy you are attempting to set on a repository policy would prevent you from setting another policy in the future, you must force the [SetRepositoryPolicy](#) operation. This is intended to prevent accidental repository lock outs.

Type: Boolean

Required: No

[policyText](#)

The JSON repository policy text to apply to the repository. For more information, see [Amazon ECR repository policies](#) in the *Amazon Elastic Container Registry User Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: Yes

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository to receive the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "policyText": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText

The JSON repository policy text applied to the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example sets a repository policy on the ubuntu repository that allows all AWS accounts to pull from it.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 223
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.SetRepositoryPolicy
X-Amz-Date: 20151214T235302Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AWUTHPARAMS

{
  "policyText": "{\n  \"Version\": \"2012-10-17\",\n  \"Statement\": [\n    {\n      \"Sid\": \"AllowPull\",\n      \"Effect\": \"Allow\",\n      \"Action\": [\n        \"ecr:BatchGetImage\",\n        \"ecr:GetDownloadUrlForLayer\"\n      ],\n      \"Principal\": \"*\n    }\n  ]\n}\n",
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Mon, 14 Dec 2015 23:53:02 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: cfc3ead9-a2bd-11e5-91c7-7126cb670c2b

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\n\" : \"AllowPull\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : \"*\",\n    \"Action\" : [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartImageScan

Starts a basic image vulnerability scan.

A basic image scan can only be started once per 24 hours on an individual image. This limit includes if an image was scanned on initial push. You can start up to 100,000 basic scans per 24 hours. This limit includes both scans on initial push and scans initiated by the StartImageScan API. For more information, see [Basic scanning](#) in the *Amazon Elastic Container Registry User Guide*.

Request Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[imageId](#)

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

Required: Yes

[registryId](#)

The AWS account ID associated with the registry that contains the repository in which to start an image scan request. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository that contains the images to scan.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "imageScanStatus": {
    "description": "string",
    "status": "string"
  },
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: ImageIdentifier object

imageScanStatus

The current state of the scan.

Type: [ImageScanStatus](#) object

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageArchivedException

The specified image is archived and cannot be scanned.

HTTP Status Code: 400

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UnsupportedImageTypeException

The image is of a type that cannot be scanned.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example starts an image scan for and specified by the image digest in the sample-repo repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 141
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.StartImageScan
X-Amz-Date: 20161216T201255Z
User-Agent: aws-cli/1.16.310 Python/3.6.1 Darwin/18.7.0 botocore/1.13.46
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "sample-repo",
  "imageId": {
    "imageDigest":
      "sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
  }
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
```

```
Date: Fri, 24 Jan 2020 03:48:07 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 208
Connection: keep-alive
x-amzn-RequestId: 3081a92b-2066-41f8-8a47-0580288ada9e

{
  "registryId": "012345678910",
  "repositoryName": "sample-repo",
  "imageId": {
    "imageDigest":
"sha256:74b2c688c700ec95a93e478cdb959737c148df3fbf5ea706abe0318726e885e6"
  },
  "imageScanStatus": {
    "status": "IN_PROGRESS"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartLifecyclePolicyPreview

Starts a preview of a lifecycle policy for the specified repository. This allows you to see the results before associating the lifecycle policy with the repository.

Request Syntax

```
{  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

lifecyclePolicyText

The policy to be evaluated against. If you do not specify a policy, the current policy for the repository is used.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

Required: No

registryId

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository to be evaluated.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyText": "string",
  "registryId": "string",
  "repositoryName": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicyText](#)

The JSON repository policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 30720.

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

[repositoryName](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

status

The status of the lifecycle policy preview request.

Type: String

Valid Values: IN_PROGRESS | COMPLETE | EXPIRED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

LifecyclePolicyPreviewInProgressException

The previous lifecycle policy preview request has not completed. Wait and try again.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a lifecycle policy preview to expire images older than 14 days for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.StartLifecyclePolicyPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T221604Z
```

Authorization: AUTHPARAMS

Content-Length: 535

```
{
  "repositoryName": "project-a/amazon-ecs-sample",
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}"
```

Sample Response

HTTP/1.1 200 OK

Server: Server

Date: Fri, 01 Sep 2017 22:16:05 GMT

Content-Type: application/x-amz-json-1.1

Content-Length: 583

Connection: keep-alive

x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

```
{
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}",
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample",
  "status": "IN_PROGRESS"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds specified tags to a resource with the specified ARN. Existing tags on a resource are not changed if they are not specified in the request parameters.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the the resource to which to add tags. Currently, the only supported resource is an Amazon ECR repository.

Type: String

Required: Yes

tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

InvalidTagParameterException

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes specified tags from a resource.

Request Syntax

```
{  
  "resourceArn": "string",  
  "tagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource from which to remove tags. Currently, the only supported resource is an Amazon ECR repository.

Type: String

Required: Yes

tagKeys

The keys of the tags to be removed.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

InvalidTagParameterException

An invalid parameter has been specified. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateImageStorageClass

Transitions an image between storage classes. You can transition images from Amazon ECR standard storage class to Amazon ECR archival storage class for long-term storage, or restore archived images back to Amazon ECR standard.

Request Syntax

```
{  
  "imageId": {  
    "imageDigest": "string",  
    "imageTag": "string"  
  },  
  "registryId": "string",  
  "repositoryName": "string",  
  "targetStorageClass": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

Required: Yes

registryId

The AWS account ID associated with the registry that contains the image to transition. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository that contains the image to transition.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

targetStorageClass

The target storage class for the image.

Type: String

Valid Values: STANDARD | ARCHIVE

Required: Yes

Response Syntax

```
{
  "imageId": {
    "imageDigest": "string",
    "imageTag": "string"
  },
  "imageStatus": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageId

An object with identifying information for an image in an Amazon ECR repository.

Type: [ImageIdentifier](#) object

[imageStatus](#)

The current status of the image after the call to `UpdateImageStorageClass` is complete. Valid values are ACTIVE, ARCHIVED, and ACTIVATING.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING

[registryId](#)

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

[repositoryName](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

ImageStorageClassUpdateNotSupportedException

The requested image storage class update is not supported.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to

AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

To transition an image to Amazon ECR archive

This example transitions an image with a specific digest in the hello-repository repository to Amazon ECR archive storage for long-term archival.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.UpdateImageStorageClass
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220800Z
Authorization: AUTHPARAMS
Content-Length: 225

{
  "registryId": "724772093679",
  "repositoryName": "hello-repository",
  "imageId": {
    "imageDigest":
      "sha256:0b1a4e0c81c434fa7928e5c4a2651a521ebabc4ff200c65f7e25b99373efca3b"
  },
  "targetStorageClass": "ARCHIVE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 215
Connection: keep-alive

{
  "registryId": "724772093679",
  "repositoryName": "hello-repository",
```

```
"imageId": {
  "imageDigest":
"sha256:0b1a4e0c81c434fa7928e5c4a2651a521ebabc4ff200c65f7e25b99373efca3b"
},
"imageStatus": "ARCHIVED"
}
```

To restore an archived image to Amazon ECR standard

This example restores an archived image with a specific digest back to Amazon ECR standard storage.

Sample Request

```
POST / HTTP/1.1
Host: api.ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.UpdateImageStorageClass
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0 Python/3.8.0 Darwin/20.0.0 botocore/2.0.0
X-Amz-Date: 20251117T220900Z
Authorization: AUTHPARAMS
Content-Length: 226

{
  "registryId": "724772093679",
  "repositoryName": "hello-repository",
  "imageId": {
    "imageDigest":
"sha256:0b1a4e0c81c434fa7928e5c4a2651a521ebabc4ff200c65f7e25b99373efca3b"
  },
  "targetStorageClass": "STANDARD"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 217
Connection: keep-alive
```

```
{
  "registryId": "724772093679",
  "repositoryName": "hello-repository",
  "imageId": {
    "imageDigest":
      "sha256:0b1a4e0c81c434fa7928e5c4a2651a521ebabc4ff200c65f7e25b99373efca3b"
  },
  "imageStatus": "ACTIVATING"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePullThroughCacheRule

Updates an existing pull through cache rule.

Request Syntax

```
{  
  "credentialArn": "string",  
  "customRoleArn": "string",  
  "ecrRepositoryPrefix": "string",  
  "registryId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

credentialArn

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret that identifies the credentials to authenticate to the upstream registry.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\[a-zA-Z0-9\_+=.@-]+\`

Required: No

customRoleArn

Amazon Resource Name (ARN) of the IAM role to be assumed by Amazon ECR to authenticate to the ECR upstream registry. This role must be in the same account as the registry that you are configuring.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

ecrRepositoryPrefix

The repository name prefix to use when caching images from the source registry.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:?:[._-][a-z0-9]+)*/?|ROOT)$`

Required: Yes

registryId

The AWS account ID associated with the registry associated with the pull through cache rule. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

Response Syntax

```
{
  "credentialArn": "string",
  "customRoleArn": "string",
  "ecrRepositoryPrefix": "string",
  "registryId": "string",
  "updatedAt": number,
  "upstreamRepositoryPrefix": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

credentialArn

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\[a-zA-Z0-9\/_+=.@-]+\`

customRoleArn

The ARN of the IAM role associated with the pull through cache rule.

Type: String

Length Constraints: Maximum length of 2048.

ecrRepositoryPrefix

The Amazon ECR repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

updatedAt

The date and time, in JavaScript date format, when the pull through cache rule was updated.

Type: Timestamp

upstreamRepositoryPrefix

The upstream repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.
message

The error message associated with the exception.

HTTP Status Code: 400

PullThroughCacheRuleNotFoundException

The pull through cache rule was not found. Specify a valid pull through cache rule and try again.

HTTP Status Code: 400

SecretNotFoundException

The ARN of the secret specified in the pull through cache rule was not found. Update the pull through cache rule with a valid secret ARN and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UnableToAccessSecretException

The secret is unable to be accessed. Verify the resource permissions for the secret and try again.

HTTP Status Code: 400

UnableToDecryptSecretValueException

The secret is accessible but is unable to be decrypted. Verify the resource permissions and try again.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRepositoryCreationTemplate

Updates an existing repository creation template.

Request Syntax

```
{
  "appliedFor": [ "string" ],
  "customRoleArn": "string",
  "description": "string",
  "encryptionConfiguration": {
    "encryptionType": "string",
    "kmsKey": "string"
  },
  "imageTagMutability": "string",
  "imageTagMutabilityExclusionFilters": [
    {
      "filter": "string",
      "filterType": "string"
    }
  ],
  "lifecyclePolicy": "string",
  "prefix": "string",
  "repositoryPolicy": "string",
  "resourceTags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appliedFor

Updates the list of enumerable strings representing the Amazon ECR repository creation scenarios that this template will apply towards. The supported scenarios are PULL_THROUGH_CACHE, REPLICATION, and CREATE_ON_PUSH

Type: Array of strings

Valid Values: REPLICATION | PULL_THROUGH_CACHE | CREATE_ON_PUSH

Required: No

customRoleArn

The ARN of the role to be assumed by Amazon ECR. This role must be in the same account as the registry that you are configuring. Amazon ECR will assume your supplied role when the customRoleArn is specified. When this field isn't specified, Amazon ECR will use the service-linked role for the repository creation template.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

description

A description for the repository creation template.

Type: String

Length Constraints: Maximum length of 256.

Required: No

encryptionConfiguration

The encryption configuration to associate with the repository creation template.

Type: [EncryptionConfigurationForRepositoryCreationTemplate](#) object

Required: No

imageTagMutability

Updates the tag mutability setting for the repository. If this parameter is omitted, the default setting of MUTABLE will be used which will allow image tags to be overwritten. If IMMUTABLE is

specified, all image tags within the repository will be immutable which will prevent them from being overwritten.

Type: String

Valid Values: MUTABLE | IMMUTABLE | IMMUTABLE_WITH_EXCLUSION |
MUTABLE_WITH_EXCLUSION

Required: No

imageTagMutabilityExclusionFilters

A list of filters that specify which image tags should be excluded from the repository creation template's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

lifecyclePolicy

Updates the lifecycle policy associated with the specified repository creation template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 30720.

Required: No

prefix

The repository namespace prefix that matches an existing repository creation template in the registry. All repositories created using this namespace prefix will have the settings defined in this template applied. For example, a prefix of prod would apply to all repositories beginning with prod/. This includes a repository named prod/team1 as well as a repository named prod/repository1.

To apply a template to all repositories in your registry that don't have an associated creation template, you can use ROOT as the prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?)|ROOT)$`

Required: Yes

[repositoryPolicy](#)

Updates the repository policy created using the template. A repository policy is a permissions policy associated with a repository to control access permissions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: No

[resourceTags](#)

The metadata to apply to the repository to help you categorize and organize. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "registryId": "string",
  "repositoryCreationTemplate": {
    "appliedFor": [ "string" ],
    "createdAt": number,
    "customRoleArn": "string",
    "description": "string",
    "encryptionConfiguration": {
      "encryptionType": "string",
      "kmsKey": "string"
    }
  },
}
```

```
"imageTagMutability": "string",
"imageTagMutabilityExclusionFilters": [
  {
    "filter": "string",
    "filterType": "string"
  }
],
"lifecyclePolicy": "string",
"prefix": "string",
"repositoryPolicy": "string",
"resourceTags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registryId

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryCreationTemplate

The details of the repository creation template associated with the request.

Type: [RepositoryCreationTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

TemplateNotFoundException

The specified repository creation template can't be found. Verify the registry ID and prefix and try again.

HTTP Status Code: 400

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example updates a repository creation template in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length:240
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.UpdateRepositoryCreationTemplate
X-Amz-Date: 20231216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "prefix": "eng/test",
  "resourceTags":
    [
      {"Key": "environment",
        "Value": "test"}
    ],
  "appliedFor":
    ["REPLICATION"]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Sat, 16 Dec 2023 19:54:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 950
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54

{
  "registryId": "012345678901",
  "repositoryCreationTemplate":
    {
      "appliedFor":
```

```

    ["REPLICATION"],
    "description": "Repos for testing images",
    "encryptionConfiguration":
    {
        "encryptionType": "AES256"
    },
    "imageTagMutability": "MUTABLE",
    "lifecyclePolicy": "{\r\n    \"rules\": [\r\n        {\r\n            \"rulePriority\r\n\": 1,\r\n            \"description\": \"Expire images older than 14 days\", \r\n            \"selection\": {\r\n                \"tagStatus\": \"untagged\", \r\n                \"countType\": \"sinceImagePushed\", \r\n                \"countUnit\": \"days\", \r\n                \"countNumber\": 14, \r\n                \"action\": {\r\n                    \"type\": \"expire\" \r\n                } \r\n            } \r\n        ] \r\n    }",
    "prefix": "eng/test",
    "repositoryPolicy": "{\n  \"Version\" : \"2012-10-17\", \n  \"Statement\" : [ {\n    \"Sid\" : \"LambdaECRPullPolicy\", \n    \"Effect\" : \"Allow\", \n    \"Principal\" : {\n      \"Service\" : \"lambda.amazonaws.com\" \n    }, \n    \"Action\" :\n    \"ecr:BatchGetImage\" \n  } ] \n}",
    "resourceTags":
    [
        {"Key": "environment",
         "Value": "test"}
    ],
    "createdAt": "2023-12-16T17:29:02-07:00",
    "updatedAt": "2023-12-16T19:55:02-07:00"
  }
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UploadLayerPart

Uploads an image layer part to Amazon ECR.

When an image is pushed, each new image layer is uploaded in parts. The maximum size of each image layer part can be 20971520 bytes (or about 20MB). The UploadLayerPart API is called once per each new image layer part.

Note

This operation is used by the Amazon ECR proxy and is not generally used by customers for pulling and pushing images. In most cases, you should use the docker CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerPartBlob": blob,
  "partFirstByte": number,
  "partLastByte": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

layerPartBlob

The base64-encoded layer part payload.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 20971520.

Required: Yes

[partFirstByte](#)

The position of the first byte of the layer part within the overall image layer.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

[partLastByte](#)

The position of the last byte of the layer part within the overall image layer.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

[registryId](#)

The AWS account ID associated with the registry to which you are uploading layer parts. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName](#)

The name of the repository to which you are uploading layer parts.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

[uploadId](#)

The upload ID from a previous [InitiateLayerUpload](#) operation to associate with the layer part upload.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Required: Yes

Response Syntax

```
{
  "lastByteReceived": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastByteReceived

The integer value of the last byte received in the request.

Type: Long

Valid Range: Minimum value of 0.

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

repositoryName

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

uploadId

The upload ID associated with the request.

Type: String

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidLayerPartException

The layer part size is not valid, or the first byte specified is not consecutive to the last byte of a previous layer part upload.

lastValidByteReceived

The last valid byte received from the layer part upload that is associated with the exception.

message

The error message associated with the exception.

registryId

The registry ID associated with the exception.

repositoryName

The repository name associated with the exception.

uploadId

The upload ID associated with the exception.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

message

The error message associated with the exception.

HTTP Status Code: 400

KmsException

The operation failed due to a KMS exception.

kmsError

The error code returned by AWS KMS.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR service quotas](#) in the Amazon Elastic Container Registry User Guide.

message

The error message associated with the exception.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

message

The error message associated with the exception.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

message

The error message associated with the exception.

HTTP Status Code: 500

UploadNotFoundException

The upload could not be found, or the specified upload ID is not valid for this repository.

message

The error message associated with the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ValidatePullThroughCacheRule

Validates an existing pull through cache rule for an upstream registry that requires authentication. This will retrieve the contents of the AWS Secrets Manager secret, verify the syntax, and then validate that authentication to the upstream registry is successful.

Request Syntax

```
{  
  "ecrRepositoryPrefix": "string",  
  "registryId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ecrRepositoryPrefix

The repository name prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/|ROOT)$`

Required: Yes

registryId

The registry ID associated with the pull through cache rule. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

Response Syntax

```
{
  "credentialArn": "string",
  "customRoleArn": "string",
  "ecrRepositoryPrefix": "string",
  "failure": "string",
  "isValid": boolean,
  "registryId": "string",
  "upstreamRegistryUrl": "string",
  "upstreamRepositoryPrefix": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[credentialArn](#)

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\[a-zA-Z0-9\/_+=.@-]+\`

[customRoleArn](#)

The ARN of the IAM role associated with the pull through cache rule.

Type: String

Length Constraints: Maximum length of 2048.

[ecrRepositoryPrefix](#)

The Amazon ECR repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

failure

The reason the validation failed. For more details about possible causes and how to address them, see [Using pull through cache rules](#) in the *Amazon Elastic Container Registry User Guide*.

Type: String

isValid

Whether or not the pull through cache rule was validated. If `true`, Amazon ECR was able to reach the upstream registry and authentication was successful. If `false`, there was an issue and validation failed. The `failure` reason indicates the cause.

Type: Boolean

registryId

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{12}`

upstreamRegistryUrl

The upstream registry URL associated with the pull through cache rule.

Type: String

upstreamRepositoryPrefix

The upstream repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?|ROOT)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.
message

The error message associated with the exception.

HTTP Status Code: 400

PullThroughCacheRuleNotFoundException

The pull through cache rule was not found. Specify a valid pull through cache rule and try again.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.
message

The error message associated with the exception.

HTTP Status Code: 500

ValidationException

There was an exception validating this request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Elastic Container Registry API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Attribute](#)
- [AuthorizationData](#)
- [AwsEcrContainerImageDetails](#)
- [CvssScore](#)
- [CvssScoreAdjustment](#)
- [CvssScoreDetails](#)
- [DescribeImagesFilter](#)
- [EncryptionConfiguration](#)
- [EncryptionConfigurationForRepositoryCreationTemplate](#)
- [EnhancedImageScanFinding](#)
- [Image](#)
- [ImageDetail](#)
- [ImageFailure](#)
- [ImageIdentifier](#)
- [ImageReferrer](#)
- [ImageReplicationStatus](#)
- [ImageScanFinding](#)
- [ImageScanFindings](#)
- [ImageScanFindingsSummary](#)
- [ImageScanningConfiguration](#)

- [ImageScanStatus](#)
- [ImageSigningStatus](#)
- [ImageTagMutabilityExclusionFilter](#)
- [Layer](#)
- [LayerFailure](#)
- [LifecyclePolicyPreviewFilter](#)
- [LifecyclePolicyPreviewResult](#)
- [LifecyclePolicyPreviewSummary](#)
- [LifecyclePolicyRuleAction](#)
- [ListImageReferrersFilter](#)
- [ListImagesFilter](#)
- [PackageVulnerabilityDetails](#)
- [PullThroughCacheRule](#)
- [Recommendation](#)
- [RegistryScanningConfiguration](#)
- [RegistryScanningRule](#)
- [Remediation](#)
- [ReplicationConfiguration](#)
- [ReplicationDestination](#)
- [ReplicationRule](#)
- [Repository](#)
- [RepositoryCreationTemplate](#)
- [RepositoryFilter](#)
- [RepositoryScanningConfiguration](#)
- [RepositoryScanningConfigurationFailure](#)
- [Resource](#)
- [ResourceDetails](#)
- [ScanningRepositoryFilter](#)
- [ScoreDetails](#)
- [SigningConfiguration](#)

- [SigningRepositoryFilter](#)
- [SigningRule](#)
- [SubjectIdentifier](#)
- [Tag](#)
- [TransitioningImageTotalCount](#)
- [VulnerablePackage](#)

Attribute

This data type is used in the [ImageScanFinding](#) data type.

Contents

key

The attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to the attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthorizationData

An object representing authorization data for an Amazon ECR registry.

Contents

authorizationToken

A base64-encoded string that contains authorization data for the specified Amazon ECR registry. When the string is decoded, it is presented in the format `user:password` for private registry authentication using `docker login`.

Type: String

Pattern: `^\S+$`

Required: No

expiresAt

The Unix time in seconds and milliseconds when the authorization token expires. Authorization tokens are valid for 12 hours.

Type: Timestamp

Required: No

proxyEndpoint

The registry URL to use for this authorization token in a `docker login` command. The Amazon ECR registry URL format is `https://aws_account_id.dkr.ecr.region.amazonaws.com`. For example, `https://012345678910.dkr.ecr.us-east-1.amazonaws.com..`

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AwsEcrContainerImageDetails

The image details of the Amazon ECR container image.

Contents

architecture

The architecture of the Amazon ECR container image.

Type: String

Required: No

author

The image author of the Amazon ECR container image.

Type: String

Required: No

imageHash

The image hash of the Amazon ECR container image.

Type: String

Required: No

imageTags

The image tags attached to the Amazon ECR container image.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

inUseCount

The number of Amazon ECS or Amazon EKS clusters currently running the image.

Type: Long

Valid Range: Minimum value of 0.

Required: No

lastInUseAt

The most recent date and time a cluster was running the image.

Type: Timestamp

Required: No

platform

The platform of the Amazon ECR container image.

Type: String

Required: No

pushedAt

The date and time the Amazon ECR container image was pushed.

Type: Timestamp

Required: No

registry

The registry the Amazon ECR container image belongs to.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository the Amazon ECR container image resides in.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScore

The CVSS score for a finding.

Contents

baseScore

The base CVSS score used for the finding.

Type: Double

Required: No

scoringVector

The vector string of the CVSS score.

Type: String

Required: No

source

The source of the CVSS score.

Type: String

Required: No

version

The version of CVSS used for the score.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScoreAdjustment

Details on adjustments Amazon Inspector made to the CVSS score for a finding.

Contents

metric

The metric used to adjust the CVSS score.

Type: String

Required: No

reason

The reason the CVSS score has been adjustment.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScoreDetails

Information about the CVSS score.

Contents

adjustments

An object that contains details about adjustment Amazon Inspector made to the CVSS score.

Type: Array of [CvssScoreAdjustment](#) objects

Required: No

score

The CVSS score.

Type: Double

Required: No

scoreSource

The source for the CVSS score.

Type: String

Required: No

scoringVector

The vector for the CVSS score.

Type: String

Required: No

version

The CVSS version used in scoring.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DescribeImagesFilter

An object representing a filter on a [DescribeImages](#) operation.

Contents

imageStatus

The image status with which to filter your [DescribeImages](#) results. Valid values are ACTIVE, ARCHIVED, and ACTIVATING.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING | ANY

Required: No

tagStatus

The tag status with which to filter your [DescribeImages](#) results. You can filter results based on whether they are TAGGED or UNTAGGED.

Type: String

Valid Values: TAGGED | UNTAGGED | ANY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionConfiguration

The encryption configuration for the repository. This determines how the contents of your repository are encrypted at rest.

By default, when no encryption configuration is set or the AES256 encryption type is used, Amazon ECR uses server-side encryption with Amazon S3-managed encryption keys which encrypts your data at rest using an AES256 encryption algorithm. This does not require any action on your part.

For more control over the encryption of the contents of your repository, you can use server-side encryption with AWS Key Management Service key stored in AWS Key Management Service (AWS KMS) to encrypt your images. For more information, see [Amazon ECR encryption at rest](#) in the *Amazon Elastic Container Registry User Guide*.

Contents

encryptionType

The encryption type to use.

If you use the KMS encryption type, the contents of the repository will be encrypted using server-side encryption with AWS Key Management Service key stored in AWS KMS. When you use AWS KMS to encrypt your data, you can either use the default AWS managed AWS KMS key for Amazon ECR, or specify your own AWS KMS key, which you already created.

If you use the KMS_DSSE encryption type, the contents of the repository will be encrypted with two layers of encryption using server-side encryption with the AWS KMS Management Service key stored in AWS KMS. Similar to the KMS encryption type, you can either use the default AWS managed AWS KMS key for Amazon ECR, or specify your own AWS KMS key, which you've already created.

If you use the AES256 encryption type, Amazon ECR uses server-side encryption with Amazon S3-managed encryption keys which encrypts the images in the repository using an AES256 encryption algorithm.

For more information, see [Amazon ECR encryption at rest](#) in the *Amazon Elastic Container Registry User Guide*.

Type: String

Valid Values: AES256 | KMS | KMS_DSSE

Required: Yes

kmsKey

If you use the KMS encryption type, specify the AWS KMS key to use for encryption. The alias, key ID, or full ARN of the AWS KMS key can be specified. The key must exist in the same Region as the repository. If no key is specified, the default AWS managed AWS KMS key for Amazon ECR will be used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionConfigurationForRepositoryCreationTemplate

The encryption configuration to associate with the repository creation template.

Contents

encryptionType

The encryption type to use.

If you use the KMS encryption type, the contents of the repository will be encrypted using server-side encryption with AWS Key Management Service key stored in AWS KMS. When you use AWS KMS to encrypt your data, you can either use the default AWS managed AWS KMS key for Amazon ECR, or specify your own AWS KMS key, which you already created. For more information, see [Protecting data using server-side encryption with an AWS KMS key stored in AWS Key Management Service \(SSE-KMS\)](#) in the *Amazon Simple Storage Service Console Developer Guide*.

If you use the AES256 encryption type, Amazon ECR uses server-side encryption with Amazon S3-managed encryption keys which encrypts the images in the repository using an AES256 encryption algorithm. For more information, see [Protecting data using server-side encryption with Amazon S3-managed encryption keys \(SSE-S3\)](#) in the *Amazon Simple Storage Service Console Developer Guide*.

Type: String

Valid Values: AES256 | KMS | KMS_DSSE

Required: Yes

kmsKey

If you use the KMS encryption type, specify the AWS KMS key to use for encryption. The full ARN of the AWS KMS key must be specified. The key must exist in the same Region as the repository. If no key is specified, the default AWS managed AWS KMS key for Amazon ECR will be used.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^$|arn:aws[a-z0-9-]*:kms:[a-z0-9-]+:[0-9]{12}:key[/[a-z0-9-]]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnhancedImageScanFinding

The details of an enhanced image scan. This is returned when enhanced scanning is enabled for your private registry.

Contents

awsAccountId

The AWS account ID associated with the image.

Type: String

Pattern: [0-9]{12}

Required: No

description

The description of the finding.

Type: String

Required: No

exploitAvailable

If a finding discovered in your environment has an exploit available.

Type: String

Required: No

findingArn

The Amazon Resource Number (ARN) of the finding.

Type: String

Required: No

firstObservedAt

The date and time that the finding was first observed.

Type: Timestamp

Required: No

fixAvailable

Details on whether a fix is available through a version update. This value can be YES, NO, or PARTIAL. A PARTIAL fix means that some, but not all, of the packages identified in the finding have fixes available through updated versions.

Type: String

Required: No

lastObservedAt

The date and time that the finding was last observed.

Type: Timestamp

Required: No

packageVulnerabilityDetails

An object that contains the details of a package vulnerability finding.

Type: [PackageVulnerabilityDetails](#) object

Required: No

remediation

An object that contains the details about how to remediate a finding.

Type: [Remediation](#) object

Required: No

resources

Contains information on the resources involved in a finding.

Type: Array of [Resource](#) objects

Required: No

score

The Amazon Inspector score given to the finding.

Type: Double

Required: No

scoreDetails

An object that contains details of the Amazon Inspector score.

Type: [ScoreDetails](#) object

Required: No

severity

The severity of the finding.

Type: String

Required: No

status

The status of the finding.

Type: String

Required: No

title

The title of the finding.

Type: String

Required: No

type

The type of the finding.

Type: String

Required: No

updatedAt

The date and time the finding was last updated at.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Image

An object representing an Amazon ECR image.

Contents

imageId

An object containing the image tag and image digest associated with an image.

Type: [ImageIdentifier](#) object

Required: No

imageManifest

The image manifest associated with the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4194304.

Required: No

imageManifestMediaType

The manifest media type of the image.

Type: String

Required: No

registryId

The AWS account ID associated with the registry containing the image.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository associated with the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageDetail

An object that describes an image returned by a [DescribeImages](#) operation.

Contents

artifactMediaType

The artifact media type of the image.

Type: String

Required: No

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imageManifestMediaType

The media type of the image manifest.

Type: String

Required: No

imagePushedAt

The date and time, expressed in standard JavaScript date format, at which the current image was pushed to the repository.

Type: Timestamp

Required: No

imageScanFindingsSummary

A summary of the last completed image scan.

Type: [ImageScanFindingsSummary](#) object

Required: No

imageScanStatus

The current state of the scan.

Type: [ImageScanStatus](#) object

Required: No

imageSizeInBytes

The size, in bytes, of the image in the repository.

If the image is a manifest list, this will be the max size of all manifests in the list.

Note

Starting with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size. Therefore, Docker might return a larger image than the image shown in the AWS Management Console.

Type: Long

Required: No

imageStatus

The current status of the image.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING

Required: No

imageTags

The list of tags associated with this image.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

lastActivatedAt

The date and time, expressed in standard JavaScript date format, when the image was last restored from Amazon ECR archive to Amazon ECR standard.

Type: Timestamp

Required: No

lastArchivedAt

The date and time, expressed in standard JavaScript date format, when the image was last transitioned to Amazon ECR archive.

Type: Timestamp

Required: No

lastRecordedPullTime

The date and time, expressed in standard JavaScript date format, when Amazon ECR recorded the last image pull.

 Note

Amazon ECR refreshes the last image pull timestamp at least once every 24 hours. For example, if you pull an image once a day then the `lastRecordedPullTime` timestamp will indicate the exact time that the image was last pulled. However, if you pull an image once an hour, because Amazon ECR refreshes the `lastRecordedPullTime` timestamp at least once every 24 hours, the result may not be the exact time that the image was last pulled.

Type: Timestamp

Required: No

registryId

The AWS account ID associated with the registry to which this image belongs.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName

The name of the repository to which this image belongs.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

subjectManifestDigest

The digest of the subject manifest for images that are referrers.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageFailure

An object representing an Amazon ECR image failure.

Contents

failureCode

The code associated with the failure.

Type: String

Valid Values: `InvalidImageDigest` | `InvalidImageTag` | `ImageTagDoesNotMatchDigest` | `ImageNotFound` | `MissingDigestAndTag` | `ImageReferencedByManifestList` | `KmsError` | `UpstreamAccessDenied` | `UpstreamTooManyRequests` | `UpstreamUnavailable` | `ImageInaccessible`

Required: No

failureReason

The reason for the failure.

Type: String

Required: No

imageId

The image ID associated with the failure.

Type: [ImageIdentifier](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ImageIdentifier

An object with identifying information for an image in an Amazon ECR repository.

Contents

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imageTag

The tag used for the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageReferrer

An object representing an artifact associated with a subject image.

Contents

digest

The digest of the artifact manifest.

Type: String

Required: Yes

mediaType

The media type of the artifact manifest.

Type: String

Required: Yes

size

The size, in bytes, of the artifact.

Type: Long

Required: Yes

annotations

A map of annotations associated with the artifact.

Type: String to string map

Required: No

artifactStatus

The status of the artifact. Valid values are ACTIVE, ARCHIVED, or ACTIVATING.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING

Required: No

artifactType

A string identifying the type of artifact.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageReplicationStatus

The status of the replication process for an image.

Contents

failureCode

The failure code for a replication that has failed.

Type: String

Required: No

region

The destination Region for the image replication.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Pattern: `[0-9a-z-]{2,25}`

Required: No

registryId

The AWS account ID associated with the registry to which the image belongs.

Type: String

Pattern: `[0-9]{12}`

Required: No

status

The image replication status.

Type: String

Valid Values: `IN_PROGRESS` | `COMPLETE` | `FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFinding

Contains information about an image scan finding.

Contents

attributes

A collection of attributes of the host from which the finding is generated.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

description

The description of the finding.

Type: String

Required: No

name

The name associated with the finding, usually a CVE number.

Type: String

Required: No

severity

The finding severity.

Type: String

Valid Values: INFORMATIONAL | LOW | MEDIUM | HIGH | CRITICAL | UNDEFINED

Required: No

uri

A link containing additional details about the security vulnerability.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFindings

The details of an image scan.

Contents

enhancedFindings

Details about the enhanced scan findings from Amazon Inspector.

Type: Array of [EnhancedImageScanFinding](#) objects

Required: No

findings

The findings from the image scan.

Type: Array of [ImageScanFinding](#) objects

Required: No

findingSeverityCounts

The image vulnerability counts, sorted by severity.

Type: String to integer map

Valid Keys: INFORMATIONAL | LOW | MEDIUM | HIGH | CRITICAL | UNDEFINED

Valid Range: Minimum value of 0.

Required: No

imageScanCompletedAt

The time of the last completed image scan.

Type: Timestamp

Required: No

vulnerabilitySourceUpdatedAt

The time when the vulnerability data was last scanned.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFindingsSummary

A summary of the last completed image scan.

Contents

findingSeverityCounts

The image vulnerability counts, sorted by severity.

Type: String to integer map

Valid Keys: INFORMATIONAL | LOW | MEDIUM | HIGH | CRITICAL | UNDEFINED

Valid Range: Minimum value of 0.

Required: No

imageScanCompletedAt

The time of the last completed image scan.

Type: Timestamp

Required: No

vulnerabilitySourceUpdatedAt

The time when the vulnerability data was last scanned.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanningConfiguration

The image scanning configuration for a repository.

Contents

scanOnPush

The setting that determines whether images are scanned after being pushed to a repository. If set to `true`, images will be scanned after being pushed. If this parameter is not specified, it will default to `false` and images will not be scanned unless a scan is manually started with the [API_StartImageScan](#) API.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanStatus

The current status of an image scan.

Contents

description

The description of the image scan status.

Type: String

Required: No

status

The current state of an image scan.

Type: String

Valid Values: IN_PROGRESS | COMPLETE | FAILED | UNSUPPORTED_IMAGE | ACTIVE | PENDING | SCAN_ELIGIBILITY_EXPIRED | FINDINGS_UNAVAILABLE | LIMIT_EXCEEDED | IMAGE_ARCHIVED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSigningStatus

The signing status for an image. Each status corresponds to a signing profile.

Contents

failureCode

The failure code, which is only present if status is FAILED.

Type: String

Required: No

failureReason

A description of why signing the image failed. This field is only present if status is FAILED.

Type: String

Required: No

signingProfileArn

The ARN of the AWS Signer signing profile used to sign the image.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+)*:signer:[a-z0-9-]+:[0-9]{12}:\./signing-profiles
\/[a-zA-Z0-9_]{2,}$`

Required: No

status

The image's signing status. Possible values are:

- IN_PROGRESS - Signing is currently in progress.
- COMPLETE - The signature was successfully generated.
- FAILED - Signing failed. See failureCode and failureReason for details.

Type: String

Valid Values: IN_PROGRESS | COMPLETE | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageTagMutabilityExclusionFilter

A filter that specifies which image tags should be excluded from the repository's image tag mutability setting.

Contents

filter

The filter value used to match image tags for exclusion from mutability settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[0-9a-zA-Z._*-]{1,128}$`

Required: Yes

filterType

The type of filter to apply for excluding image tags from mutability settings.

Type: String

Valid Values: WILDCARD

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Layer

An object representing an Amazon ECR image layer.

Contents

layerAvailability

The availability status of the image layer.

Type: String

Valid Values: AVAILABLE | UNAVAILABLE | ARCHIVED

Required: No

layerDigest

The sha256 digest of the image layer.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: No

layerSize

The size, in bytes, of the image layer.

Type: Long

Required: No

mediaType

The media type of the layer, such as `application/vnd.docker.image.rootfs.diff.tar.gzip` or `application/vnd.oci.image.layer.v1.tar+gzip`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LayerFailure

An object representing an Amazon ECR image layer failure.

Contents

failureCode

The failure code associated with the failure.

Type: String

Valid Values: `InvalidLayerDigest` | `MissingLayerDigest`

Required: No

failureReason

The reason for the failure.

Type: String

Required: No

layerDigest

The layer digest associated with the failure.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyPreviewFilter

The filter for the lifecycle policy preview.

Contents

tagStatus

The tag status of the image.

Type: String

Valid Values: TAGGED | UNTAGGED | ANY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyPreviewResult

The result of the lifecycle policy preview.

Contents

action

The type of action to be taken.

Type: [LifecyclePolicyRuleAction](#) object

Required: No

appliedRulePriority

The priority of the applied rule.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imagePushedAt

The date and time, expressed in standard JavaScript date format, at which the current image was pushed to the repository.

Type: Timestamp

Required: No

imageTags

The list of tags associated with this image.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

storageClass

The storage class of the image.

Type: String

Valid Values: ARCHIVE | STANDARD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyPreviewSummary

The summary of the lifecycle policy preview request.

Contents

expiringImageTotalCount

The number of expiring images.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

transitioningImageTotalCounts

The total count of images that will be transitioned to each storage class. This field is only present if at least one image will be transitioned in the summary.

Type: Array of [TransitioningImageTotalCount](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyRuleAction

The type of action to be taken.

Contents

targetStorageClass

The target storage class for the action. This is only present when the type is TRANSITION.

Type: String

Valid Values: ARCHIVE

Required: No

type

The type of action to be taken.

Type: String

Valid Values: EXPIRE | TRANSITION

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListImageReferrersFilter

An object representing a filter on a [ListImageReferrers](#) operation.

Contents

artifactStatus

The artifact status with which to filter your [ListImageReferrers](#) results. Valid values are ACTIVE, ARCHIVED, ACTIVATING, or ANY. If not specified, only artifacts with ACTIVE status are returned.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING | ANY

Required: No

artifactTypes

The artifact types with which to filter your [ListImageReferrers](#) results.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListImagesFilter

An object representing a filter on a [ListImages](#) operation.

Contents

imageStatus

The image status with which to filter your [ListImages](#) results. Valid values are ACTIVE, ARCHIVED, and ACTIVATING.

Type: String

Valid Values: ACTIVE | ARCHIVED | ACTIVATING | ANY

Required: No

tagStatus

The tag status with which to filter your [ListImages](#) results.

Type: String

Valid Values: TAGGED | UNTAGGED | ANY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageVulnerabilityDetails

Information about a package vulnerability finding.

Contents

cvss

An object that contains details about the CVSS score of a finding.

Type: Array of [CvssScore](#) objects

Required: No

referenceUrls

One or more URLs that contain details about this vulnerability type.

Type: Array of strings

Required: No

relatedVulnerabilities

One or more vulnerabilities related to the one identified in this finding.

Type: Array of strings

Required: No

source

The source of the vulnerability information.

Type: String

Required: No

sourceUrl

A URL to the source of the vulnerability information.

Type: String

Required: No

vendorCreatedAt

The date and time that this vulnerability was first added to the vendor's database.

Type: Timestamp

Required: No

vendorSeverity

The severity the vendor has given to this vulnerability type.

Type: String

Required: No

vendorUpdatedAt

The date and time the vendor last updated this vulnerability in their database.

Type: Timestamp

Required: No

vulnerabilityId

The ID given to this vulnerability.

Type: String

Required: No

vulnerablePackages

The packages impacted by this vulnerability.

Type: Array of [VulnerablePackage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PullThroughCacheRule

The details of a pull through cache rule.

Contents

createdAt

The date and time the pull through cache was created.

Type: Timestamp

Required: No

credentialArn

The ARN of the Secrets Manager secret associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 612.

Pattern: `^arn:aws(-\w+)*:secretsmanager:[a-zA-Z0-9-:]+:secret:ecr\-\pullthroughcache\[a-zA-Z0-9\_\+=.\@-]+\$`

Required: No

customRoleArn

The ARN of the IAM role associated with the pull through cache rule.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

ecrRepositoryPrefix

The Amazon ECR repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*/?)|ROOT)$`

Required: No

registryId

The AWS account ID associated with the registry the pull through cache rule is associated with.

Type: String

Pattern: `[0-9]{12}`

Required: No

updatedAt

The date and time, in JavaScript date format, when the pull through cache rule was last updated.

Type: Timestamp

Required: No

upstreamRegistry

The name of the upstream source registry associated with the pull through cache rule.

Type: String

Valid Values: `ecr` | `ecr-public` | `quay` | `k8s` | `docker-hub` | `github-container-registry` | `azure-container-registry` | `gitlab-container-registry`

Required: No

upstreamRegistryUrl

The upstream registry URL associated with the pull through cache rule.

Type: String

Required: No

upstreamRepositoryPrefix

The upstream repository prefix associated with the pull through cache rule.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 30.

Pattern: `^((?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*/?|ROOT)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Recommendation

Details about the recommended course of action to remediate the finding.

Contents

text

The recommended course of action to remediate the finding.

Type: String

Required: No

url

The URL address to the CVE remediation recommendations.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryScanningConfiguration

The scanning configuration for a private registry.

Contents

rules

The scanning rules associated with the registry.

Type: Array of [RegistryScanningRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Required: No

scanType

The type of scanning configured for the registry.

Type: String

Valid Values: BASIC | ENHANCED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryScanningRule

The details of a scanning rule for a private registry.

Contents

repositoryFilters

The repository filters associated with the scanning configuration for a private registry.

Type: Array of [ScanningRepositoryFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: Yes

scanFrequency

The frequency that scans are performed at for a private registry. When the ENHANCED scan type is specified, the supported scan frequencies are CONTINUOUS_SCAN and SCAN_ON_PUSH. When the BASIC scan type is specified, the SCAN_ON_PUSH scan frequency is supported. If scan on push is not specified, then the MANUAL scan frequency is set by default.

Type: String

Valid Values: SCAN_ON_PUSH | CONTINUOUS_SCAN | MANUAL

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Remediation

Information on how to remediate a finding.

Contents

recommendation

An object that contains information about the recommended course of action to remediate the finding.

Type: [Recommendation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicationConfiguration

The replication configuration for a registry.

Contents

rules

An array of objects representing the replication destinations and repository filters for a replication configuration.

Type: Array of [ReplicationRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicationDestination

An array of objects representing the destination for a replication rule.

Contents

region

The Region to replicate to.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Pattern: `[0-9a-z-]{2,25}`

Required: Yes

registryId

The AWS account ID of the Amazon ECR private registry to replicate to. When configuring cross-Region replication within your own registry, specify your own account ID.

Type: String

Pattern: `[0-9]{12}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicationRule

An array of objects representing the replication destinations and repository filters for a replication configuration.

Contents

destinations

An array of objects representing the destination for a replication rule.

Type: Array of [ReplicationDestination](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: Yes

repositoryFilters

An array of objects representing the filters for a replication rule. Specifying a repository filter for a replication rule provides a method for controlling which repositories in a private registry are replicated.

Type: Array of [RepositoryFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Repository

An object representing a repository.

Contents

createdAt

The date and time, in JavaScript date format, when the repository was created.

Type: Timestamp

Required: No

encryptionConfiguration

The encryption configuration for the repository. This determines how the contents of your repository are encrypted at rest.

Type: [EncryptionConfiguration](#) object

Required: No

imageScanningConfiguration

The image scanning configuration for a repository.

Type: [ImageScanningConfiguration](#) object

Required: No

imageTagMutability

The tag mutability setting for the repository.

Type: String

Valid Values: MUTABLE | IMMUTABLE | IMMUTABLE_WITH_EXCLUSION |
MUTABLE_WITH_EXCLUSION

Required: No

imageTagMutabilityExclusionFilters

A list of filters that specify which image tags are excluded from the repository's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

registryId

The AWS account ID associated with the registry that contains the repository.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryArn

The Amazon Resource Name (ARN) that identifies the repository. The ARN contains the `arn:aws:ecr` namespace, followed by the region of the repository, AWS account ID of the repository owner, repository namespace, and repository name. For example, `arn:aws:ecr:region:012345678910:repository-namespace/repository-name`.

Type: String

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

repositoryUri

The URI for the repository. You can use this URI for container image push and pull operations.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryCreationTemplate

The details of the repository creation template associated with the request.

Contents

appliedFor

A list of enumerable Strings representing the repository creation scenarios that this template will apply towards. The supported scenarios are `PULL_THROUGH_CACHE`, `REPLICATION`, and `CREATE_ON_PUSH`

Type: Array of strings

Valid Values: `REPLICATION` | `PULL_THROUGH_CACHE` | `CREATE_ON_PUSH`

Required: No

createdAt

The date and time, in JavaScript date format, when the repository creation template was created.

Type: Timestamp

Required: No

customRoleArn

The ARN of the role to be assumed by Amazon ECR. Amazon ECR will assume your supplied role when the `customRoleArn` is specified. When this field isn't specified, Amazon ECR will use the service-linked role for the repository creation template.

Type: String

Length Constraints: Maximum length of 2048.

Required: No

description

The description associated with the repository creation template.

Type: String

Length Constraints: Maximum length of 256.

Required: No

encryptionConfiguration

The encryption configuration associated with the repository creation template.

Type: [EncryptionConfigurationForRepositoryCreationTemplate](#) object

Required: No

imageTagMutability

The tag mutability setting for the repository. If this parameter is omitted, the default setting of `MUTABLE` will be used which will allow image tags to be overwritten. If `IMMUTABLE` is specified, all image tags within the repository will be immutable which will prevent them from being overwritten.

Type: String

Valid Values: `MUTABLE` | `IMMUTABLE` | `IMMUTABLE_WITH_EXCLUSION` | `MUTABLE_WITH_EXCLUSION`

Required: No

imageTagMutabilityExclusionFilters

A list of filters that specify which image tags are excluded from the repository creation template's image tag mutability setting.

Type: Array of [ImageTagMutabilityExclusionFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

lifecyclePolicy

The lifecycle policy to use for repositories created using the template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 30720.

Required: No

prefix

The repository namespace prefix associated with the repository creation template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^((?:[a-z0-9]+(?:?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:?:[._-][a-z0-9]+)*/?)|ROOT)$`

Required: No

repositoryPolicy

The repository policy to apply to repositories created using the template. A repository policy is a permissions policy associated with a repository to control access permissions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: No

resourceTags

The metadata to apply to the repository to help you categorize and organize. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Required: No

updatedAt

The date and time, in JavaScript date format, when the repository creation template was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryFilter

The filter settings used with image replication. Specifying a repository filter to a replication rule provides a method for controlling which repositories in a private registry are replicated. If no filters are added, the contents of all repositories are replicated.

Contents

filter

The repository filter details. When the `PREFIX_MATCH` filter type is specified, this value is required and should be the repository name prefix to configure replication for.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `^(?:[a-z0-9]+(?:?:[._-][a-z0-9]*)*/)*[a-z0-9]*(?:?:[._-][a-z0-9]*)*$`

Required: Yes

filterType

The repository filter type. The only supported value is `PREFIX_MATCH`, which is a repository name prefix specified with the `filter` parameter.

Type: String

Valid Values: `PREFIX_MATCH`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryScanningConfiguration

The details of the scanning configuration for a repository.

Contents

appliedScanFilters

The scan filters applied to the repository.

Type: Array of [ScanningRepositoryFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

repositoryArn

The ARN of the repository.

Type: String

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[:[._-][a-z0-9]+)*`

Required: No

scanFrequency

The scan frequency for the repository.

Type: String

Valid Values: `SCAN_ON_PUSH` | `CONTINUOUS_SCAN` | `MANUAL`

Required: No

scanOnPush

Whether or not scan on push is configured for the repository.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryScanningConfigurationFailure

The details about any failures associated with the scanning configuration of a repository.

Contents

failureCode

The failure code.

Type: String

Valid Values: REPOSITORY_NOT_FOUND

Required: No

failureReason

The reason for the failure.

Type: String

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Resource

Details about the resource involved in a finding.

Contents

details

An object that contains details about the resource involved in a finding.

Type: [ResourceDetails](#) object

Required: No

id

The ID of the resource.

Type: String

Required: No

tags

The tags attached to the resource.

Type: String to string map

Required: No

type

The type of resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDetails

Contains details about the resource involved in the finding.

Contents

awsEcrContainerImage

An object that contains details about the Amazon ECR container image involved in the finding.

Type: [AwsEcrContainerImageDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScanningRepositoryFilter

The details of a scanning repository filter. For more information on how to use filters, see [Using filters](#) in the *Amazon Elastic Container Registry User Guide*.

Contents

filter

The filter to use when scanning.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-z0-9*](?:[._\-/a-z0-9*]?[a-z0-9*]+)*$`

Required: Yes

filterType

The type associated with the filter.

Type: String

Valid Values: WILDCARD

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScoreDetails

Information about the Amazon Inspector score given to a finding.

Contents

cvss

An object that contains details about the CVSS score given to a finding.

Type: [CvssScoreDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SigningConfiguration

The signing configuration for a registry, which specifies rules for automatically signing images when pushed.

Contents

rules

A list of signing rules. Each rule defines a signing profile and optional repository filters that determine which images are automatically signed. Maximum of 10 rules.

Type: Array of [SigningRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SigningRepositoryFilter

A repository filter used to determine which repositories have their images automatically signed on push. Each filter consists of a filter type and filter value.

Contents

filter

The filter value used to match repository names. When using WILDCARD_MATCH, the `*` character matches any sequence of characters.

Examples:

- `myapp/*` - Matches all repositories starting with `myapp/`
- `*/production` - Matches all repositories ending with `/production`
- `*prod*` - Matches all repositories containing `prod`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(?:[a-z0-9*]+(?:?:[._-][a-z0-9*]+)*/)*[a-z0-9*]+(?:?:[._-][a-z0-9*]+)*$`

Required: Yes

filterType

The type of filter to apply. Currently, only WILDCARD_MATCH is supported, which uses wildcard patterns to match repository names.

Type: String

Valid Values: WILDCARD_MATCH

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SigningRule

A signing rule that specifies a signing profile and optional repository filters. When an image is pushed to a matching repository, a signing job is created using the specified profile.

Contents

signingProfileArn

The ARN of the AWS Signer signing profile to use for signing images that match this rule. For more information about signing profiles, see [Signing profiles](#) in the *AWS Signer Developer Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^arn:aws(-[a-z]+)*:signer:[a-z0-9-]+:[0-9]{12}:\./signing-profiles\.[a-zA-Z0-9_]{2,}$`

Required: Yes

repositoryFilters

A list of repository filters that determine which repositories have their images signed on push. If no filters are specified, all images pushed to the registry are signed using the rule's signing profile. Maximum of 100 filters per rule.

Type: Array of [SigningRepositoryFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

SubjectIdentifier

An object that identifies an image subject.

Contents

imageDigest

The digest of the image.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

The metadata to apply to a resource to help you categorize and organize them. Each tag consists of a key and a value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Contents

Key

One part of a key-value pair that make up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Required: Yes

Value

A value acts as a descriptor within a tag category (key).

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitioningImageTotalCount

The total count of images transitioning to a storage class.

Contents

imageTotalCount

The total number of images transitioning to the storage class.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

targetStorageClass

The target storage class.

Type: String

Valid Values: ARCHIVE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VulnerablePackage

Information on the vulnerable package identified by a finding.

Contents

arch

The architecture of the vulnerable package.

Type: String

Required: No

epoch

The epoch of the vulnerable package.

Type: Integer

Required: No

filePath

The file path of the vulnerable package.

Type: String

Required: No

fixedInVersion

The version of the package that contains the vulnerability fix.

Type: String

Required: No

name

The name of the vulnerable package.

Type: String

Required: No

packageManager

The package manager of the vulnerable package.

Type: String

Required: No

release

The release of the vulnerable package.

Type: String

Required: No

sourceLayerHash

The source layer hash of the vulnerable package.

Type: String

Required: No

version

The version of the vulnerable package.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400