



Amazon SES Mail Manager API Reference

Amazon SES Mail Manager API



API Version 2023-10-17

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon SES Mail Manager API: Amazon SES Mail Manager API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

This documentation is a draft for private preview for regions in the AWS European Sovereign Cloud. Documentation content will continue to evolve. Published: January 1, 2026.

Table of Contents

Welcome	1
Actions	2
CreateAddonInstance	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	6
Errors	6
See Also	7
CreateAddonSubscription	8
Request Syntax	8
Request Parameters	8
Response Syntax	9
Response Elements	9
Errors	9
See Also	10
CreateAddressList	11
Request Syntax	11
Request Parameters	11
Response Syntax	12
Response Elements	12
Errors	12
See Also	13
CreateAddressListImportJob	15
Request Syntax	15
Request Parameters	15
Response Syntax	16
Response Elements	16
Errors	17
See Also	17
CreateArchive	19
Request Syntax	19
Request Parameters	19
Response Syntax	20

Response Elements	20
Errors	21
See Also	22
CreateIngressPoint	23
Request Syntax	23
Request Parameters	23
Response Syntax	25
Response Elements	25
Errors	26
See Also	26
CreateRelay	27
Request Syntax	27
Request Parameters	27
Response Syntax	29
Response Elements	29
Errors	29
See Also	30
CreateRuleSet	31
Request Syntax	31
Request Parameters	31
Response Syntax	32
Response Elements	33
Errors	33
See Also	33
CreateTrafficPolicy	35
Request Syntax	35
Request Parameters	35
Response Syntax	37
Response Elements	37
Errors	37
See Also	38
DeleteAddonInstance	39
Request Syntax	39
Request Parameters	39
Response Elements	39
Errors	39

See Also	40
DeleteAddonSubscription	41
Request Syntax	41
Request Parameters	41
Response Elements	41
Errors	41
See Also	42
DeleteAddressList	43
Request Syntax	43
Request Parameters	43
Response Elements	43
Errors	43
See Also	44
DeleteArchive	45
Request Syntax	45
Request Parameters	45
Response Elements	45
Errors	45
See Also	46
DeleteIngressPoint	47
Request Syntax	47
Request Parameters	47
Response Elements	47
Errors	47
See Also	48
DeleteRelay	49
Request Syntax	49
Request Parameters	49
Response Elements	49
Errors	49
See Also	50
DeleteRuleSet	51
Request Syntax	51
Request Parameters	51
Response Elements	51
Errors	51

See Also	52
DeleteTrafficPolicy	53
Request Syntax	53
Request Parameters	53
Response Elements	53
Errors	53
See Also	54
DeregisterMemberFromAddressList	55
Request Syntax	55
Request Parameters	55
Response Elements	55
Errors	56
See Also	56
GetAddonInstance	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	58
Errors	59
See Also	60
GetAddonSubscription	61
Request Syntax	61
Request Parameters	61
Response Syntax	61
Response Elements	61
Errors	62
See Also	62
GetAddressList	64
Request Syntax	64
Request Parameters	64
Response Syntax	64
Response Elements	64
Errors	65
See Also	66
GetAddressListImportJob	67
Request Syntax	67

Request Parameters	67
Response Syntax	67
Response Elements	68
Errors	70
See Also	70
GetArchive	72
Request Syntax	72
Request Parameters	72
Response Syntax	72
Response Elements	73
Errors	74
See Also	75
GetArchiveExport	76
Request Syntax	76
Request Parameters	76
Response Syntax	76
Response Elements	77
Errors	78
See Also	78
GetArchiveMessage	80
Request Syntax	80
Request Parameters	80
Response Syntax	80
Response Elements	81
Errors	81
See Also	82
GetArchiveMessageContent	83
Request Syntax	83
Request Parameters	83
Response Syntax	83
Response Elements	83
Errors	84
See Also	84
GetArchiveSearch	86
Request Syntax	86
Request Parameters	86

Response Syntax	86
Response Elements	87
Errors	88
See Also	88
GetArchiveSearchResults	90
Request Syntax	90
Request Parameters	90
Response Syntax	90
Response Elements	91
Errors	91
See Also	92
GetIngressPoint	93
Request Syntax	93
Request Parameters	93
Response Syntax	93
Response Elements	94
Errors	96
See Also	96
GetMemberOfAddressList	98
Request Syntax	98
Request Parameters	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100
GetRelay	101
Request Syntax	101
Request Parameters	101
Response Syntax	101
Response Elements	102
Errors	103
See Also	103
GetRuleSet	105
Request Syntax	105
Request Parameters	105
Response Syntax	105

Response Elements	106
Errors	107
See Also	107
GetTrafficPolicy	109
Request Syntax	109
Request Parameters	109
Response Syntax	109
Response Elements	110
Errors	111
See Also	111
ListAddonInstances	113
Request Syntax	113
Request Parameters	113
Response Syntax	113
Response Elements	114
Errors	114
See Also	115
ListAddonSubscriptions	116
Request Syntax	116
Request Parameters	116
Response Syntax	116
Response Elements	117
Errors	117
See Also	118
ListAddressListImportJobs	119
Request Syntax	119
Request Parameters	119
Response Syntax	120
Response Elements	120
Errors	121
See Also	121
ListAddressLists	123
Request Syntax	123
Request Parameters	123
Response Syntax	123
Response Elements	124

Errors	124
See Also	125
ListArchiveExports	126
Request Syntax	126
Request Parameters	126
Response Syntax	127
Response Elements	127
Errors	128
See Also	128
ListArchives	130
Request Syntax	130
Request Parameters	130
Response Syntax	131
Response Elements	131
Errors	131
See Also	132
ListArchiveSearches	133
Request Syntax	133
Request Parameters	133
Response Syntax	134
Response Elements	134
Errors	135
See Also	135
ListIngressPoints	137
Request Syntax	137
Request Parameters	137
Response Syntax	137
Response Elements	138
Errors	138
See Also	139
ListMembersOfAddressList	140
Request Syntax	140
Request Parameters	140
Response Syntax	141
Response Elements	141
Errors	142

See Also	142
ListRelays	144
Request Syntax	144
Request Parameters	144
Response Syntax	144
Response Elements	145
Errors	145
See Also	146
ListRuleSets	147
Request Syntax	147
Request Parameters	147
Response Syntax	147
Response Elements	148
Errors	148
See Also	149
ListTagsForResource	150
Request Syntax	150
Request Parameters	150
Response Syntax	150
Response Elements	151
Errors	151
See Also	151
ListTrafficPolicies	153
Request Syntax	153
Request Parameters	153
Response Syntax	153
Response Elements	154
Errors	154
See Also	155
RegisterMemberToAddressList	156
Request Syntax	156
Request Parameters	156
Response Elements	156
Errors	157
See Also	157
StartAddressListImportJob	159

Request Syntax	159
Request Parameters	159
Response Elements	159
Errors	159
See Also	160
StartArchiveExport	162
Request Syntax	162
Request Parameters	162
Response Syntax	164
Response Elements	164
Errors	164
See Also	165
StartArchiveSearch	166
Request Syntax	166
Request Parameters	166
Response Syntax	167
Response Elements	167
Errors	168
See Also	168
StopAddressListImportJob	170
Request Syntax	170
Request Parameters	170
Response Elements	170
Errors	170
See Also	171
StopArchiveExport	172
Request Syntax	172
Request Parameters	172
Response Elements	172
Errors	172
See Also	173
StopArchiveSearch	174
Request Syntax	174
Request Parameters	174
Response Elements	174
Errors	174

See Also	175
TagResource	176
Request Syntax	176
Request Parameters	176
Response Elements	177
Errors	177
See Also	177
UntagResource	179
Request Syntax	179
Request Parameters	179
Response Elements	180
Errors	180
See Also	180
UpdateArchive	182
Request Syntax	182
Request Parameters	182
Response Elements	183
Errors	183
See Also	184
UpdateIngressPoint	185
Request Syntax	185
Request Parameters	185
Response Elements	186
Errors	187
See Also	187
UpdateRelay	188
Request Syntax	188
Request Parameters	188
Response Elements	189
Errors	189
See Also	190
UpdateRuleSet	191
Request Syntax	191
Request Parameters	191
Response Elements	192
Errors	192

See Also	193
UpdateTrafficPolicy	194
Request Syntax	194
Request Parameters	194
Response Elements	195
Errors	195
See Also	196
Data Types	197
AddHeaderAction	200
Contents	200
See Also	200
AddonInstance	201
Contents	201
See Also	202
AddonSubscription	203
Contents	203
See Also	203
AddressFilter	205
Contents	205
See Also	205
AddressList	206
Contents	206
See Also	207
Analysis	208
Contents	208
See Also	208
Archive	209
Contents	209
See Also	210
ArchiveAction	211
Contents	211
See Also	211
ArchiveBooleanExpression	212
Contents	212
See Also	212
ArchiveBooleanToEvaluate	213

Contents	213
See Also	213
ArchiveFilterCondition	214
Contents	214
See Also	214
ArchiveFilters	215
Contents	215
See Also	215
ArchiveRetention	216
Contents	216
See Also	216
ArchiveStringExpression	217
Contents	217
See Also	217
ArchiveStringToEvaluate	219
Contents	219
See Also	219
DeliverToMailboxAction	220
Contents	220
See Also	221
DeliverToQBusinessAction	222
Contents	222
See Also	223
DropAction	224
Contents	224
See Also	224
Envelope	225
Contents	225
See Also	225
ExportDestinationConfiguration	226
Contents	226
See Also	226
ExportStatus	227
Contents	227
See Also	227
ExportSummary	229

Contents	229
See Also	229
ImportDataFormat	230
Contents	230
See Also	230
ImportJob	231
Contents	231
See Also	233
IngressAnalysis	234
Contents	234
See Also	234
IngressBooleanExpression	235
Contents	235
See Also	235
IngressBooleanToEvaluate	236
Contents	236
See Also	236
IngressIpToEvaluate	237
Contents	237
See Also	237
IngressIpv4Expression	238
Contents	238
See Also	238
IngressIpv6Expression	240
Contents	240
See Also	241
IngressIpv6ToEvaluate	242
Contents	242
See Also	242
IngressIsInAddressList	243
Contents	243
See Also	243
IngressPoint	244
Contents	244
See Also	245
IngressPointAuthConfiguration	246

Contents	246
See Also	246
IngressPointConfiguration	247
Contents	247
See Also	247
IngressPointPasswordConfiguration	249
Contents	249
See Also	249
IngressStringExpression	250
Contents	250
See Also	250
IngressStringToEvaluate	252
Contents	252
See Also	252
IngressTlsProtocolExpression	253
Contents	253
See Also	253
IngressTlsProtocolToEvaluate	255
Contents	255
See Also	255
MessageBody	256
Contents	256
See Also	256
Metadata	257
Contents	257
See Also	259
NetworkConfiguration	260
Contents	260
See Also	260
NoAuthentication	261
Contents	261
See Also	261
PolicyCondition	262
Contents	262
See Also	263
PolicyStatement	264

Contents	264
See Also	264
PrivateNetworkConfiguration	265
Contents	265
See Also	265
PublicNetworkConfiguration	266
Contents	266
See Also	266
Relay	267
Contents	267
See Also	267
RelayAction	269
Contents	269
See Also	269
RelayAuthentication	271
Contents	271
See Also	271
ReplaceRecipientAction	273
Contents	273
See Also	273
Row	274
Contents	274
See Also	277
Rule	278
Contents	278
See Also	279
RuleAction	280
Contents	280
See Also	282
RuleBooleanExpression	283
Contents	283
See Also	283
RuleBooleanToEvaluate	284
Contents	284
See Also	284
RuleCondition	286

Contents	286
See Also	287
RuleDmarcExpression	288
Contents	288
See Also	288
RuleIpExpression	290
Contents	290
See Also	291
RuleIpToEvaluate	292
Contents	292
See Also	292
RuleIsInAddressList	293
Contents	293
See Also	293
RuleNumberExpression	294
Contents	294
See Also	294
RuleNumberToEvaluate	296
Contents	296
See Also	296
RuleSet	297
Contents	297
See Also	297
RuleStringExpression	299
Contents	299
See Also	300
RuleStringToEvaluate	301
Contents	301
See Also	302
RuleVerdictExpression	303
Contents	303
See Also	304
RuleVerdictToEvaluate	305
Contents	305
See Also	305
S3Action	306

Contents	306
See Also	307
S3ExportDestinationConfiguration	308
Contents	308
See Also	308
SavedAddress	309
Contents	309
See Also	309
SearchStatus	310
Contents	310
See Also	310
SearchSummary	312
Contents	312
See Also	312
SendAction	313
Contents	313
See Also	313
SnsAction	314
Contents	314
See Also	315
Tag	316
Contents	316
See Also	316
TrafficPolicy	317
Contents	317
See Also	317
Common Parameters	319
Common Errors	322

Welcome

Welcome to the Amazon SES Mail Manager API Reference. This guide provides information about the Amazon SES Mail Manager API, including supported operations, data types, parameters, and schemas.

The Amazon SES Mail Manager API contains operations and data types that comprise the Mail Manager feature of [Amazon Simple Email Service \(SES\)](#).

Mail Manager is a set of Amazon SES email gateway features designed to help you strengthen your organization's email infrastructure, simplify email workflow management, and streamline email compliance control. To learn more, see the [Mail Manager chapter](#) in the *Amazon SES Developer Guide*.

The Amazon SES Mail Manager API is available in several AWS Regions and it provides an endpoint for each of these Regions. For more information, see [Amazon SES endpoints and quotas](#) in the *Amazon Web Services General Reference*. To learn more about AWS Regions, see [Managing AWS Regions](#) in the *Amazon Web Services General Reference*.

This document was last published on January 1, 2026.

Actions

The following actions are supported:

- [CreateAddonInstance](#)
- [CreateAddonSubscription](#)
- [CreateAddressList](#)
- [CreateAddressListImportJob](#)
- [CreateArchive](#)
- [CreateIngressPoint](#)
- [CreateRelay](#)
- [CreateRuleSet](#)
- [CreateTrafficPolicy](#)
- [DeleteAddonInstance](#)
- [DeleteAddonSubscription](#)
- [DeleteAddressList](#)
- [DeleteArchive](#)
- [DeleteIngressPoint](#)
- [DeleteRelay](#)
- [DeleteRuleSet](#)
- [DeleteTrafficPolicy](#)
- [DeregisterMemberFromAddressList](#)
- [GetAddonInstance](#)
- [GetAddonSubscription](#)
- [GetAddressList](#)
- [GetAddressListImportJob](#)
- [GetArchive](#)
- [GetArchiveExport](#)
- [GetArchiveMessage](#)
- [GetArchiveMessageContent](#)
- [GetArchiveSearch](#)

- [GetArchiveSearchResults](#)
- [GetIngressPoint](#)
- [GetMemberOfAddressList](#)
- [GetRelay](#)
- [GetRuleSet](#)
- [GetTrafficPolicy](#)
- [ListAddonInstances](#)
- [ListAddonSubscriptions](#)
- [ListAddressListImportJobs](#)
- [ListAddressLists](#)
- [ListArchiveExports](#)
- [ListArchives](#)
- [ListArchiveSearches](#)
- [ListIngressPoints](#)
- [ListMembersOfAddressList](#)
- [ListRelays](#)
- [ListRuleSets](#)
- [ListTagsForResource](#)
- [ListTrafficPolicies](#)
- [RegisterMemberToAddressList](#)
- [StartAddressListImportJob](#)
- [StartArchiveExport](#)
- [StartArchiveSearch](#)
- [StopAddressListImportJob](#)
- [StopArchiveExport](#)
- [StopArchiveSearch](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateArchive](#)
- [UpdateIngressPoint](#)

- [UpdateRelay](#)
- [UpdateRuleSet](#)
- [UpdateTrafficPolicy](#)

CreateAddonInstance

Creates an Add On instance for the subscription indicated in the request. The resulting Amazon Resource Name (ARN) can be used in a conditional statement for a rule set or traffic policy.

Request Syntax

```
{
  "AddonSubscriptionId": "string",
  "ClientToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddonSubscriptionId

The unique ID of a previously created subscription that an Add On instance is created for. You can only have one instance per subscription.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: as-[a-zA-Z0-9]{1,64}

Required: Yes

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1": "value1", "key2": "value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AddonInstanceId](#)

The unique ID of the Add On instance created by this API.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: ai-[a-zA-Z0-9]{1,64}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAddonSubscription

Creates a subscription for an Add On representing the acceptance of its terms of use and additional pricing. The subscription can then be used to create an instance for use in rule sets or traffic policies.

Request Syntax

```
{
  "AddonName": "string",
  "ClientToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddonName

The name of the Add On to subscribe to. You can only have one subscription for each Add On name.

Type: String

Required: Yes

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1": "value1", "key2": "value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "AddonSubscriptionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AddonSubscriptionId](#)

The unique ID of the Add On subscription created by this API.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: as-[a-zA-Z0-9]{1,64}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAddressList

Creates a new address list.

Request Syntax

```
{  
  "AddressListName": "string",  
  "ClientToken": "string",  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddressListName](#)

A user-friendly name for the address list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

[ClientToken](#)

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1": "value1", "key2": "value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{  
  "AddressListId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddressListId

The identifier of the created address list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAddressListImportJob

Creates an import job for an address list.

Request Syntax

```
{  
  "AddressListId": "string",  
  "ClientToken": "string",  
  "ImportDataFormat": {  
    "ImportDataType": "string"  
  },  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressListId

The unique identifier of the address list for importing addresses to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

ImportDataFormat

The format of the input for an import job.

Type: [ImportDataFormat](#) object

Required: Yes

Name

A user-friendly name for the import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Response Syntax

```
{
  "JobId": "string",
  "PreSignedUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The identifier of the created import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

PreSignedUrl

The pre-signed URL target for uploading the input file.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateArchive

Creates a new email archive resource for storing and retaining emails.

Request Syntax

```
{
  "ArchiveName": "string",
  "ClientToken": "string",
  "KmsKeyArn": "string",
  "Retention": { ... },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveName

A unique name for the new archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]

Required: Yes

ClientToken

A unique token Amazon SES uses to recognize retries of this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[KmsKeyArn](#)

The Amazon Resource Name (ARN) of the KMS key for encrypting emails in the archive.

Type: String

Pattern: `arn:aws(|-cn|-us-gov|-eusc):kms:[a-z0-9-]{1,20}:[0-9]{12}:(key|alias)/.+`

Required: No

[Retention](#)

The period for retaining emails in the archive before automatic deletion.

Type: [ArchiveRetention](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[Tags](#)

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "ArchiveId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ArchiveId

The unique identifier for the newly created archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateIngressPoint

Provision a new ingress endpoint resource.

Request Syntax

```
{
  "ClientToken": "string",
  "IngressPointConfiguration": { ... },
  "IngressPointName": "string",
  "NetworkConfiguration": { ... },
  "RuleSetId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TrafficPolicyId": "string",
  "Type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

IngressPointConfiguration

If you choose an Authenticated ingress endpoint, you must configure either an SMTP password or a secret ARN.

Type: [IngressPointConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[IngressPointName](#)

A user friendly name for an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: Yes

[NetworkConfiguration](#)

Specifies the network configuration for the ingress point. This allows you to create an IPv4-only, Dual-Stack, or PrivateLink type of ingress point. If not specified, the default network type is IPv4-only.

Type: [NetworkConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[RuleSetId](#)

The identifier of an existing rule set that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

[Tags](#)

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

TrafficPolicyId

The identifier of an existing traffic policy that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Type

The type of the ingress endpoint to create.

Type: String

Valid Values: OPEN | AUTH

Required: Yes

Response Syntax

```
{
  "IngressPointId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

IngressPointId

The unique identifier for a previously created ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRelay

Creates a relay resource which can be used in rules to relay incoming emails to defined relay destinations.

Request Syntax

```
{
  "Authentication": { ... },
  "ClientToken": "string",
  "RelayName": "string",
  "ServerName": "string",
  "ServerPort": number,
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[Authentication](#)

Authentication for the relay destination server—specify the secretARN where the SMTP credentials are stored.

Type: [RelayAuthentication](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[ClientToken](#)

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

RelayName

The unique name of the relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9- _]+

Required: Yes

ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-\ .]+

Required: Yes

ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{  
  "RelayId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[RelayId](#)

A unique identifier of the created relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRuleSet

Provision a new rule set.

Request Syntax

```
{
  "ClientToken": "string",
  "Rules": [
    {
      "Actions": [
        { ... }
      ],
      "Conditions": [
        { ... }
      ],
      "Name": "string",
      "Unless": [
        { ... }
      ]
    }
  ],
  "RuleSetName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Rules

Conditional rules that are evaluated for determining actions on email.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: Yes

RuleSetName

A user-friendly name for the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "RuleSetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

RuleSetId

The identifier of the created rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTrafficPolicy

Provision a new traffic policy resource.

Request Syntax

```
{
  "ClientToken": "string",
  "DefaultAction": "string",
  "MaxMessageSizeBytes": number,
  "PolicyStatements": [
    {
      "Action": "string",
      "Conditions": [
        { ... }
      ]
    }
  ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TrafficPolicyName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: Yes

MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

PolicyStatements

Conditional statements for filtering email traffic.

Type: Array of [PolicyStatement](#) objects

Required: Yes

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: Yes

Response Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[TrafficPolicyId](#)

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAddonInstance

Deletes an Add On instance.

Request Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddonInstanceId](#)

The Add On instance ID to delete.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: ai-[a-zA-Z0-9]{1,64}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAddonSubscription

Deletes an Add On subscription.

Request Syntax

```
{  
  "AddonSubscriptionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddonSubscriptionId](#)

The Add On subscription ID to delete.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: as-[a-zA-Z0-9]{1,64}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAddressList

Deletes an address list.

Request Syntax

```
{  
  "AddressListId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddressListId](#)

The identifier of an existing address list resource to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteArchive

Initiates deletion of an email archive. This changes the archive state to pending deletion. In this state, no new emails can be added, and existing archived emails become inaccessible (search, export, download). The archive and all of its contents will be permanently deleted 30 days after entering the pending deletion state, regardless of the configured retention period.

Request Syntax

```
{  
  "ArchiveId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteIngressPoint

Delete an ingress endpoint resource.

Request Syntax

```
{  
  "IngressPointId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

IngressPointId

The identifier of the ingress endpoint resource that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRelay

Deletes an existing relay resource.

Request Syntax

```
{  
  "RelayId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRuleSet

Delete a rule set.

Request Syntax

```
{  
  "RuleSetId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

RuleSetId

The identifier of an existing rule set resource to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTrafficPolicy

Delete a traffic policy resource.

Request Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[TrafficPolicyId](#)

The identifier of the traffic policy that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterMemberFromAddressList

Removes a member from an address list.

Request Syntax

```
{  
  "Address": "string",  
  "AddressListId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Address

The address to be removed from the address list.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

Required: Yes

AddressListId

The unique identifier of the address list to remove the address from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAddonInstance

Gets detailed information about an Add On instance.

Request Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddonInstanceId](#)

The Add On instance ID to retrieve information for.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: ai-[a-zA-Z0-9]{1,64}

Required: Yes

Response Syntax

```
{  
  "AddonInstanceArn": "string",  
  "AddonName": "string",  
  "AddonSubscriptionId": "string",  
  "CreatedTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddonInstanceArn

The Amazon Resource Name (ARN) of the Add On instance.

Type: String

AddonName

The name of the Add On provider associated to the subscription of the instance.

Type: String

AddonSubscriptionId

The subscription ID associated to the instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: as-[a-zA-Z0-9]{1,64}

CreatedTimestamp

The timestamp of when the Add On instance was created.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAddonSubscription

Gets detailed information about an Add On subscription.

Request Syntax

```
{  
  "AddonSubscriptionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AddonSubscriptionId](#)

The Add On subscription ID to retrieve information for.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: as-[a-zA-Z0-9]{1,64}

Required: Yes

Response Syntax

```
{  
  "AddonName": "string",  
  "AddonSubscriptionArn": "string",  
  "CreatedTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddonName

The name of the Add On for the subscription.

Type: String

AddonSubscriptionArn

Amazon Resource Name (ARN) for the subscription.

Type: String

CreatedTimestamp

The timestamp of when the Add On subscription was created.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAddressList

Fetch attributes of an address list.

Request Syntax

```
{  
  "AddressListId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressListId

The identifier of an existing address list resource to be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Syntax

```
{  
  "AddressListArn": "string",  
  "AddressListId": "string",  
  "AddressListName": "string",  
  "CreatedTimestamp": number,  
  "LastUpdatedTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddressListArn

The Amazon Resource Name (ARN) of the address list resource.

Type: String

AddressListId

The identifier of the address list resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

AddressListName

A user-friendly name for the address list resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_ . -]+

CreatedTimestamp

The date of when then address list was created.

Type: Timestamp

LastUpdatedTimestamp

The date of when the address list was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAddressListImportJob

Fetch attributes of an import job.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The identifier of the import job that needs to be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Syntax

```
{  
  "AddressListId": "string",  
  "CompletedTimestamp": number,  
  "CreatedTimestamp": number,  
  "Error": "string",  
  "FailedItemsCount": number,  
  "ImportDataFormat": {  
    "ImportDataType": "string"  
  },  
  "ImportedItemsCount": number,  
  "JobId": "string",
```

```
"Name": "string",  
"PreSignedUrl": "string",  
"StartTimestamp": number,  
"Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddressListId

The unique identifier of the address list the import job was created for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

CompletedTimestamp

The timestamp of when the import job was completed.

Type: Timestamp

CreatedTimestamp

The timestamp of when the import job was created.

Type: Timestamp

Error

The reason for failure of an import job.

Type: String

FailedItemsCount

The number of input addresses that failed to be imported into the address list.

Type: Integer

ImportDataFormat

The format of the input for an import job.

Type: [ImportDataFormat](#) object

ImportedItemsCount

The number of input addresses successfully imported into the address list.

Type: Integer

JobId

The identifier of the import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Name

A user-friendly name for the import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

PreSignedUrl

The pre-signed URL target for uploading the input file.

Type: String

StartTimestamp

The timestamp of when the import job was started.

Type: Timestamp

Status

The status of the import job.

Type: String

Valid Values: CREATED | PROCESSING | COMPLETED | FAILED | STOPPED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchive

Retrieves the full details and current state of a specified email archive.

Request Syntax

```
{  
  "ArchiveId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

Response Syntax

```
{  
  "ArchiveArn": "string",  
  "ArchiveId": "string",  
  "ArchiveName": "string",  
  "ArchiveState": "string",  
  "CreatedTimestamp": number,  
  "KmsKeyArn": "string",  
  "LastUpdatedTimestamp": number,  
  "Retention": { ... }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ArchiveArn

The Amazon Resource Name (ARN) of the archive.

Type: String

ArchiveId

The unique identifier of the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

ArchiveName

The unique name assigned to the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]`

ArchiveState

The current state of the archive:

- **ACTIVE** – The archive is ready and available for use.
- **PENDING_DELETION** – The archive has been marked for deletion and will be permanently deleted in 30 days. No further modifications can be made in this state.

Type: String

Valid Values: **ACTIVE** | **PENDING_DELETION**

CreatedTimestamp

The timestamp of when the archive was created.

Type: Timestamp

KmsKeyArn

The Amazon Resource Name (ARN) of the KMS key used to encrypt the archive.

Type: String

Pattern: `arn:aws(|-cn|-us-gov|-eusc):kms:[a-z0-9-]{1,20}:[0-9]{12}:(key|alias)/.+`

LastUpdatedTimestamp

The timestamp of when the archive was modified.

Type: Timestamp

Retention

The retention period for emails in this archive.

Type: [ArchiveRetention](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveExport

Retrieves the details and current status of a specific email archive export job.

Request Syntax

```
{  
  "ExportId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ExportId

The identifier of the export job to get details for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "ArchiveId": "string",  
  "ExportDestinationConfiguration": { ... },  
  "Filters": {  
    "Include": [  
      { ... }  
    ],  
    "Unless": [  
      { ... }  
    ]  
  },  
  "FromTimestamp": number,
```



```
"MaxResults": number,
"Status": {
  "CompletionTimestamp": number,
  "ErrorMessage": "string",
  "State": "string",
  "SubmissionTimestamp": number
},
"ToTimestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ArchiveId

The identifier of the archive the email export was performed from.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a-[\w]{1,64}

ExportDestinationConfiguration

Where the exported emails are being delivered.

Type: [ExportDestinationConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Filters

The criteria used to filter emails included in the export.

Type: [ArchiveFilters](#) object

FromTimestamp

The start of the timestamp range the exported emails cover.

Type: Timestamp

MaxResults

The maximum number of email items included in the export.

Type: Integer

Status

The current status of the export job.

Type: [ExportStatus](#) object

ToTimestamp

The end of the date range the exported emails cover.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveMessage

Returns a pre-signed URL that provides temporary download access to the specific email message stored in the archive.

Request Syntax

```
{  
  "ArchivedMessageId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchivedMessageId

The unique identifier of the archived email message.

Type: String

Required: Yes

Response Syntax

```
{  
  "Envelope": {  
    "From": "string",  
    "Helo": "string",  
    "To": [ "string" ]  
  },  
  "MessageDownloadLink": "string",  
  "Metadata": {  
    "ConfigurationSet": "string",  
    "IngressPointId": "string",  
    "RuleSetId": "string",  
    "SenderHostname": "string",  
    "SenderIpAddress": "string",  
  }  
}
```

```
"SendingMethod": "string",
"SendingPool": "string",
"SourceArn": "string",
"SourceIdentity": "string",
"Timestamp": number,
"TlsCipherSuite": "string",
"TlsProtocol": "string",
"TrafficPolicyId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Envelope](#)

The SMTP envelope information of the email.

Type: [Envelope](#) object

[MessageDownloadLink](#)

A pre-signed URL to temporarily download the full message content.

Type: String

[Metadata](#)

The metadata about the email.

Type: [Metadata](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveMessageContent

Returns the textual content of a specific email message stored in the archive. Attachments are not included.

Request Syntax

```
{  
  "ArchivedMessageId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchivedMessageId

The unique identifier of the archived email message.

Type: String

Required: Yes

Response Syntax

```
{  
  "Body": {  
    "Html": "string",  
    "MessageMalformed": boolean,  
    "Text": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Body

The textual body content of the email message.

Type: [MessageBody](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveSearch

Retrieves the details and current status of a specific email archive search job.

Request Syntax

```
{  
  "SearchId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SearchId

The identifier of the search job to get details for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "ArchiveId": "string",  
  "Filters": {  
    "Include": [  
      { ... }  
    ],  
    "Unless": [  
      { ... }  
    ]  
  },  
  "FromTimestamp": number,  
  "MaxResults": number,  
}
```

```
"Status": {  
  "CompletionTimestamp": number,  
  "ErrorMessage": "string",  
  "State": "string",  
  "SubmissionTimestamp": number  
},  
"ToTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ArchiveId

The identifier of the archive the email search was performed in.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a- [\w]{1,64}

Filters

The criteria used to filter emails included in the search.

Type: [ArchiveFilters](#) object

FromTimestamp

The start timestamp of the range the searched emails cover.

Type: Timestamp

MaxResults

The maximum number of search results to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Status

The current status of the search job.

Type: [SearchStatus](#) object

ToTimestamp

The end timestamp of the range the searched emails cover.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveSearchResults

Returns the results of a completed email archive search job.

Request Syntax

```
{  
  "SearchId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SearchId

The identifier of the completed search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "Rows": [  
    {  
      "ArchivedMessageId": "string",  
      "Cc": "string",  
      "Date": "string",  
      "Envelope": {  
        "From": "string",  
        "Helo": "string",  
        "To": [ "string" ]  
      },  
      "From": "string",
```

```
"HasAttachments": boolean,
"IngressPointId": "string",
"InReplyTo": "string",
"MessageId": "string",
"ReceivedHeaders": [ "string" ],
"ReceivedTimestamp": number,
"SenderHostname": "string",
"SenderIdAddress": "string",
"SourceArn": "string",
"Subject": "string",
"To": "string",
"XMailer": "string",
"XOriginalMailer": "string",
"XPriority": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Rows

The list of email result objects matching the search criteria.

Type: Array of [Row](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetIngressPoint

Fetch ingress endpoint resource attributes.

Request Syntax

```
{  
  "IngressPointId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

IngressPointId

The identifier of an ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Syntax

```
{  
  "AResult": "string",  
  "CreatedTimestamp": number,  
  "IngressPointArn": "string",  
  "IngressPointAuthConfiguration": {  
    "IngressPointPasswordConfiguration": {  
      "PreviousSmtppasswordExpiryTimestamp": number,  
      "PreviousSmtppasswordVersion": "string",  
      "SmtppasswordVersion": "string"  
    },  
    "SecretArn": "string"  
  },  
  "IngressPointId": "string",
```

```
"IngressPointName": "string",  
"LastUpdatedTimestamp": number,  
"NetworkConfiguration": { ... },  
"RuleSetId": "string",  
"Status": "string",  
"TrafficPolicyId": "string",  
"Type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ARecord](#)

The DNS A Record that identifies your ingress endpoint. Configure your DNS Mail Exchange (MX) record with this value to route emails to Mail Manager.

Type: String

[CreatedTimestamp](#)

The timestamp of when the ingress endpoint was created.

Type: Timestamp

[IngressPointArn](#)

The Amazon Resource Name (ARN) of the ingress endpoint resource.

Type: String

[IngressPointAuthConfiguration](#)

The authentication configuration of the ingress endpoint resource.

Type: [IngressPointAuthConfiguration](#) object

[IngressPointId](#)

The identifier of an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

IngressPointName

A user friendly name for the ingress endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

LastUpdatedTimestamp

The timestamp of when the ingress endpoint was last updated.

Type: Timestamp

NetworkConfiguration

The network configuration for the ingress point.

Type: [NetworkConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

RuleSetId

The identifier of a rule set resource associated with the ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Status

The status of the ingress endpoint resource.

Type: String

Valid Values: PROVISIONING | DEPROVISIONING | UPDATING | ACTIVE | CLOSED | FAILED

TrafficPolicyId

The identifier of the traffic policy resource associated with the ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Type

The type of ingress endpoint.

Type: String

Valid Values: OPEN | AUTH

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMemberOfAddressList

Fetch attributes of a member in an address list.

Request Syntax

```
{  
  "Address": "string",  
  "AddressListId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Address

The address to be retrieved from the address list.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

Required: Yes

AddressListId

The unique identifier of the address list to retrieve the address from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Syntax

```
{
```

```
"Address": "string",  
"CreatedTimestamp": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Address

The address retrieved from the address list.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

CreatedTimestamp

The timestamp of when the address was created.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRelay

Fetch the relay resource and its attributes.

Request Syntax

```
{  
  "RelayId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

RelayId

A unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Syntax

```
{  
  "Authentication": { ... },  
  "CreatedTimestamp": number,  
  "LastModifiedTimestamp": number,  
  "RelayArn": "string",  
  "RelayId": "string",  
  "RelayName": "string",  
  "ServerName": "string",  
  "ServerPort": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Authentication

The authentication attribute—contains the secret ARN where the customer relay server credentials are stored.

Type: [RelayAuthentication](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

CreatedTimestamp

The timestamp of when the relay was created.

Type: Timestamp

LastModifiedTimestamp

The timestamp of when relay was last updated.

Type: Timestamp

RelayArn

The Amazon Resource Name (ARN) of the relay.

Type: String

RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

RelayName

The unique name of the relay.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9- _]+

ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-\ .]+

ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRuleSet

Fetch attributes of a rule set.

Request Syntax

```
{  
  "RuleSetId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

RuleSetId

The identifier of an existing rule set to be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Syntax

```
{  
  "CreatedDate": number,  
  "LastModificationDate": number,  
  "Rules": [  
    {  
      "Actions": [  
        { ... }  
      ],  
      "Conditions": [  
        { ... }  
      ],  
      "Name": "string",  
      "Unless": [  

```

```
        { ... }
      ]
    }
  ],
  "RuleSetArn": "string",
  "RuleSetId": "string",
  "RuleSetName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedDate

The date of when the rule set was created.

Type: Timestamp

LastModificationDate

The date of when the rule set was last modified.

Type: Timestamp

Rules

The rules contained in the rule set.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

RuleSetArn

The Amazon Resource Name (ARN) of the rule set resource.

Type: String

RuleSetId

The identifier of the rule set resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

RuleSetName

A user-friendly name for the rule set resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrafficPolicy

Fetch attributes of a traffic policy resource.

Request Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[TrafficPolicyId](#)

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Syntax

```
{  
  "CreatedTimestamp": number,  
  "DefaultAction": "string",  
  "LastUpdatedTimestamp": number,  
  "MaxMessageSizeBytes": number,  
  "PolicyStatements": [  
    {  
      "Action": "string",  
      "Conditions": [  
        { ... }  
      ]  
    }  
  ],  
}
```

```
"TrafficPolicyArn": "string",  
"TrafficPolicyId": "string",  
"TrafficPolicyName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedTimestamp

The timestamp of when the traffic policy was created.

Type: Timestamp

DefaultAction

The default action of the traffic policy.

Type: String

Valid Values: ALLOW | DENY

LastUpdatedTimestamp

The timestamp of when the traffic policy was last updated.

Type: Timestamp

MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

PolicyStatements

The list of conditions which are in the traffic policy resource.

Type: Array of [PolicyStatement](#) objects

TrafficPolicyArn

The Amazon Resource Name (ARN) of the traffic policy resource.

Type: String

TrafficPolicyId

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAddonInstances

Lists all Add On instances in your account.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```

```
"AddonInstances": [  
  {  
    "AddonInstanceArn": "string",  
    "AddonInstanceId": "string",  
    "AddonName": "string",  
    "AddonSubscriptionId": "string",  
    "CreatedTimestamp": number  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddonInstances

The list of ingress endpoints.

Type: Array of [AddonInstance](#) objects

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAddonSubscriptions

Lists all Add On subscriptions in your account.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```



```
"AddonSubscriptions": [  
  {  
    "AddonName": "string",  
    "AddonSubscriptionArn": "string",  
    "AddonSubscriptionId": "string",  
    "CreatedTimestamp": number  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddonSubscriptions

The list of ingress endpoints.

Type: Array of [AddonSubscription](#) objects

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAddressListImportJobs

Lists jobs for an address list.

Request Syntax

```
{  
  "AddressListId": "string",  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressListId

The unique identifier of the address list for listing import jobs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of import jobs that are returned per call. You can use NextToken to retrieve the next page of jobs.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
  "ImportJobs": [
    {
      "AddressListId": "string",
      "CompletedTimestamp": number,
      "CreatedTimestamp": number,
      "Error": "string",
      "FailedItemsCount": number,
      "ImportDataFormat": {
        "ImportDataType": "string"
      },
      "ImportedItemsCount": number,
      "JobId": "string",
      "Name": "string",
      "PreSignedUrl": "string",
      "StartTimestamp": number,
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImportJobs

The list of import jobs.

Type: Array of [ImportJob](#) objects

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAddressLists

Lists address lists for this account.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of address list resources that are returned per call. You can use NextToken to retrieve the next page of address lists.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```

```
"AddressLists": [  
  {  
    "AddressListArn": "string",  
    "AddressListId": "string",  
    "AddressListName": "string",  
    "CreatedTimestamp": number,  
    "LastUpdatedTimestamp": number  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AddressLists](#)

The list of address lists.

Type: Array of [AddressList](#) objects

[NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListArchiveExports

Returns a list of email archive export jobs.

Request Syntax

```
{  
  "ArchiveId": "string",  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ArchiveId](#)

The identifier of the archive.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a - `[\w]{1,64}`

Required: Yes

[NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of archive export jobs that are returned per call. You can use `NextToken` to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
  "Exports": [
    {
      "ExportId": "string",
      "Status": {
        "CompletionTimestamp": number,
        "ErrorMessage": "string",
        "State": "string",
        "SubmissionTimestamp": number
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Exports

The list of export job identifiers and statuses.

Type: Array of [ExportSummary](#) objects

NextToken

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListArchives

Returns a list of all email archives in your account.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of archives that are returned per call. You can use NextToken to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
  "Archives": [
    {
      "ArchiveId": "string",
      "ArchiveName": "string",
      "ArchiveState": "string",
      "LastUpdatedTimestamp": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Archives](#)

The list of archive details.

Type: Array of [Archive](#) objects

[NextToken](#)

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListArchiveSearches

Returns a list of email archive search jobs.

Request Syntax

```
{  
  "ArchiveId": "string",  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a - [\w]{1,64}

Required: Yes

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of archive search jobs that are returned per call. You can use `NextToken` to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Searches": [
    {
      "SearchId": "string",
      "Status": {
        "CompletionTimestamp": number,
        "ErrorMessage": "string",
        "State": "string",
        "SubmissionTimestamp": number
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

[Searches](#)

The list of search job identifiers and statuses.

Type: Array of [SearchSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListIngressPoints

List all ingress endpoint resources.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```

```
"IngressPoints": [  
  {  
    "ARecord": "string",  
    "IngressPointId": "string",  
    "IngressPointName": "string",  
    "Status": "string",  
    "Type": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[IngressPoints](#)

The list of ingress endpoints.

Type: Array of [IngressPoint](#) objects

[NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMembersOfAddressList

Lists members of an address list.

Request Syntax

```
{  
  "AddressListId": "string",  
  "Filter": {  
    "AddressPrefix": "string"  
  },  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddressListId

The unique identifier of the address list to list the addresses from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Filter

Filter to be used to limit the results.

Type: [AddressFilter](#) object

Required: No

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

[PageSize](#)

The maximum number of address list members that are returned per call. You can use `NextToken` to retrieve the next page of members.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

Response Syntax

```
{
  "Addresses": [
    {
      "Address": "string",
      "CreatedTimestamp": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Addresses](#)

The list of addresses.

Type: Array of [SavedAddress](#) objects

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRelays

Lists all the existing relay resources.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The number of relays to be returned in one request.

Type: Integer

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"Relays": [
  {
    "LastModifiedTimestamp": number,
    "RelayId": "string",
    "RelayName": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

[Relays](#)

The list of returned relays.

Type: Array of [Relay](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRuleSets

List rule sets for this account.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of rule set resources that are returned per call. You can use NextToken to obtain further rule sets.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"RuleSets": [
  {
    "LastModificationDate": number,
    "RuleSetId": "string",
    "RuleSetName": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

RuleSets

The list of rule sets.

Type: Array of [RuleSet](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Retrieves the list of tags (keys and values) assigned to the resource.

Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource to retrieve tags from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `arn:aws(|-cn|-us-gov|-eusc):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+`

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTrafficPolicies

List traffic policy resources.

Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

PageSize

The maximum number of traffic policy resources that are returned per call. You can use NextToken to obtain further traffic policies.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"TrafficPolicies": [
  {
    "DefaultAction": "string",
    "TrafficPolicyId": "string",
    "TrafficPolicyName": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

[TrafficPolicies](#)

The list of traffic policies.

Type: Array of [TrafficPolicy](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterMemberToAddressList

Adds a member to an address list.

Request Syntax

```
{  
  "Address": "string",  
  "AddressListId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Address

The address to be added to the address list.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

Required: Yes

AddressListId

The unique identifier of the address list where the address should be added.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAddressListImportJob

Starts an import job for an address list.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The identifier of the import job that needs to be started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartArchiveExport

Initiates an export of emails from the specified archive.

Request Syntax

```
{
  "ArchiveId": "string",
  "ExportDestinationConfiguration": { ... },
  "Filters": {
    "Include": [
      { ... }
    ],
    "Unless": [
      { ... }
    ]
  },
  "FromTimestamp": number,
  "IncludeMetadata": boolean,
  "MaxResults": number,
  "ToTimestamp": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive to export emails from.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a-[\w]{1,64}

Required: Yes

ExportDestinationConfiguration

Details on where to deliver the exported email data.

Type: [ExportDestinationConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[Filters](#)

Criteria to filter which emails are included in the export.

Type: [ArchiveFilters](#) object

Required: No

[FromTimestamp](#)

The start of the timestamp range to include emails from.

Type: Timestamp

Required: Yes

[IncludeMetadata](#)

Whether to include message metadata as JSON files in the export.

Type: Boolean

Required: No

[MaxResults](#)

The maximum number of email items to include in the export.

Type: Integer

Required: No

[ToTimestamp](#)

The end of the timestamp range to include emails from.

Type: Timestamp

Required: Yes

Response Syntax

```
{  
  "ExportId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ExportId](#)

The unique identifier for the initiated export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartArchiveSearch

Initiates a search across emails in the specified archive.

Request Syntax

```
{  
  "ArchiveId": "string",  
  "Filters": {  
    "Include": [  
      { ... }  
    ],  
    "Unless": [  
      { ... }  
    ]  
  },  
  "FromTimestamp": number,  
  "MaxResults": number,  
  "ToTimestamp": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive to search emails in.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: a - [\w]{1,64}

Required: Yes

Filters

Criteria to filter which emails are included in the search results.

Type: [ArchiveFilters](#) object

Required: No

FromTimestamp

The start timestamp of the range to search emails from.

Type: Timestamp

Required: Yes

MaxResults

The maximum number of search results to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: Yes

ToTimestamp

The end timestamp of the range to search emails from.

Type: Timestamp

Required: Yes

Response Syntax

```
{  
  "SearchId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SearchId

The unique identifier for the initiated search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAddressListImportJob

Stops an ongoing import job for an address list.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

JobId

The identifier of the import job that needs to be stopped.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopArchiveExport

Stops an in-progress export of emails from an archive.

Request Syntax

```
{  
  "ExportId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ExportId

The identifier of the export job to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopArchiveSearch

Stops an in-progress archive search job.

Request Syntax

```
{  
  "SearchId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SearchId

The identifier of the search job to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds one or more tags (keys and values) to a specified resource.

Request Syntax

```
{  
  "ResourceArn": "string",  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource that you want to tag.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `arn:aws(|-cn|-us-gov|-eusc):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+`

Required: Yes

Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Remove one or more tags (keys and values) from a specified resource.

Request Syntax

```
{  
  "ResourceArn": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource that you want to untag.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `arn:aws(|-cn|-us-gov|-eusc):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+`

Required: Yes

[TagKeys](#)

The keys of the key-value pairs for the tag or tags you want to remove from the specified resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9/_\+=\.\:@\-\-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateArchive

Updates the attributes of an existing email archive.

Request Syntax

```
{  
  "ArchiveId": "string",  
  "ArchiveName": "string",  
  "Retention": { ... }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ArchiveId

The identifier of the archive to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

ArchiveName

A new, unique name for the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]`

Required: No

Retention

A new retention period for emails in the archive.

Type: [ArchiveRetention](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateIngressPoint

Update attributes of a provisioned ingress endpoint resource.

Request Syntax

```
{  
  "IngressPointConfiguration": { ... },  
  "IngressPointId": "string",  
  "IngressPointName": "string",  
  "RuleSetId": "string",  
  "StatusToUpdate": "string",  
  "TrafficPolicyId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[IngressPointConfiguration](#)

If you choose an Authenticated ingress endpoint, you must configure either an SMTP password or a secret ARN.

Type: [IngressPointConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[IngressPointId](#)

The identifier for the ingress endpoint you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

IngressPointName

A user friendly name for the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: No

RuleSetId

The identifier of an existing rule set that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

StatusToUpdate

The update status of an ingress endpoint.

Type: String

Valid Values: ACTIVE | CLOSED

Required: No

TrafficPolicyId

The identifier of an existing traffic policy that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRelay

Updates the attributes of an existing relay resource.

Request Syntax

```
{  
  "Authentication": { ... },  
  "RelayId": "string",  
  "RelayName": "string",  
  "ServerName": "string",  
  "ServerPort": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[Authentication](#)

Authentication for the relay destination server—specify the secretARN where the SMTP credentials are stored.

Type: [RelayAuthentication](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[RelayId](#)

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: Yes

RelayName

The name of the relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9- _]+

Required: No

ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-\ .]+

Required: No

ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRuleSet

Update attributes of an already provisioned rule set.

Request Syntax

```
{
  "Rules": [
    {
      "Actions": [
        { ... }
      ],
      "Conditions": [
        { ... }
      ],
      "Name": "string",
      "Unless": [
        { ... }
      ]
    }
  ],
  "RuleSetId": "string",
  "RuleSetName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Rules

A new set of rules to replace the current rules of the rule set—these rules will override all the rules of the rule set.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: No

RuleSetId

The identifier of a rule set you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

RuleSetName

A user-friendly name for the rule set resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.-]+

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTrafficPolicy

Update attributes of an already provisioned traffic policy resource.

Request Syntax

```
{  
  "DefaultAction": "string",  
  "MaxMessageSizeBytes": number,  
  "PolicyStatements": [  
    {  
      "Action": "string",  
      "Conditions": [  
        { ... }  
      ]  
    }  
  ],  
  "TrafficPolicyId": "string",  
  "TrafficPolicyName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: No

MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

PolicyStatements

The list of conditions to be updated for filtering email traffic.

Type: Array of [PolicyStatement](#) objects

Required: No

TrafficPolicyId

The identifier of the traffic policy that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The MailManager API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AddHeaderAction](#)
- [AddonInstance](#)
- [AddonSubscription](#)
- [AddressFilter](#)
- [AddressList](#)
- [Analysis](#)
- [Archive](#)
- [ArchiveAction](#)
- [ArchiveBooleanExpression](#)
- [ArchiveBooleanToEvaluate](#)
- [ArchiveFilterCondition](#)
- [ArchiveFilters](#)
- [ArchiveRetention](#)
- [ArchiveStringExpression](#)
- [ArchiveStringToEvaluate](#)
- [DeliverToMailboxAction](#)
- [DeliverToQBusinessAction](#)
- [DropAction](#)
- [Envelope](#)
- [ExportDestinationConfiguration](#)

- [ExportStatus](#)
- [ExportSummary](#)
- [ImportDataFormat](#)
- [ImportJob](#)
- [IngressAnalysis](#)
- [IngressBooleanExpression](#)
- [IngressBooleanToEvaluate](#)
- [IngressIpToEvaluate](#)
- [IngressIpv4Expression](#)
- [IngressIpv6Expression](#)
- [IngressIpv6ToEvaluate](#)
- [IngressIsInAddressList](#)
- [IngressPoint](#)
- [IngressPointAuthConfiguration](#)
- [IngressPointConfiguration](#)
- [IngressPointPasswordConfiguration](#)
- [IngressStringExpression](#)
- [IngressStringToEvaluate](#)
- [IngressTlsProtocolExpression](#)
- [IngressTlsProtocolToEvaluate](#)
- [MessageBody](#)
- [Metadata](#)
- [NetworkConfiguration](#)
- [NoAuthentication](#)
- [PolicyCondition](#)
- [PolicyStatement](#)
- [PrivateNetworkConfiguration](#)
- [PublicNetworkConfiguration](#)
- [Relay](#)
- [RelayAction](#)

- [RelayAuthentication](#)
- [ReplaceRecipientAction](#)
- [Row](#)
- [Rule](#)
- [RuleAction](#)
- [RuleBooleanExpression](#)
- [RuleBooleanToEvaluate](#)
- [RuleCondition](#)
- [RuleDmarcExpression](#)
- [RuleIpExpression](#)
- [RuleIpToEvaluate](#)
- [RuleIsInAddressList](#)
- [RuleNumberExpression](#)
- [RuleNumberToEvaluate](#)
- [RuleSet](#)
- [RuleStringExpression](#)
- [RuleStringToEvaluate](#)
- [RuleVerdictExpression](#)
- [RuleVerdictToEvaluate](#)
- [S3Action](#)
- [S3ExportDestinationConfiguration](#)
- [SavedAddress](#)
- [SearchStatus](#)
- [SearchSummary](#)
- [SendAction](#)
- [SnsAction](#)
- [Tag](#)
- [TrafficPolicy](#)

AddHeaderAction

The action to add a header to a message. When executed, this action will add the given header to the message.

Contents

HeaderName

The name of the header to add to an email. The header must be prefixed with "X-". Headers are added regardless of whether the header name pre-existed in the email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [xX]\-[a-zA-Z0-9\-\-]+

Required: Yes

HeaderValue

The value of the header to add to the email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AddonInstance

An Add On instance represents a specific configuration of an Add On.

Contents

AddonInstanceArn

The Amazon Resource Name (ARN) of the Add On instance.

Type: String

Required: No

AddonInstanceId

The unique ID of the Add On instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `ai-[a-zA-Z0-9]{1,64}`

Required: No

AddonName

The name of the Add On for the instance.

Type: String

Required: No

AddonSubscriptionId

The subscription ID for the instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `as-[a-zA-Z0-9]{1,64}`

Required: No

CreatedTimestamp

The timestamp of when the Add On instance was created.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AddonSubscription

A subscription for an Add On representing the acceptance of its terms of use and additional pricing.

Contents

AddonName

The name of the Add On.

Type: String

Required: No

AddonSubscriptionArn

The Amazon Resource Name (ARN) of the Add On subscription.

Type: String

Required: No

AddonSubscriptionId

The unique ID of the Add On subscription.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `as-[a-zA-Z0-9]{1,64}`

Required: No

CreatedTimestamp

The timestamp of when the Add On subscription was created.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AddressFilter

Filtering options for ListMembersOfAddressList operation.

Contents

AddressPrefix

Filter to limit the results to addresses having the provided prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 320.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AddressList

An address list contains a list of emails and domains that are used in MailManager Ingress endpoints and Rules for email management.

Contents

AddressListArn

The Amazon Resource Name (ARN) of the address list.

Type: String

Required: Yes

AddressListId

The identifier of the address list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

AddressListName

The user-friendly name of the address list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

CreatedTimestamp

The timestamp of when the address list was created.

Type: Timestamp

Required: Yes

LastUpdatedTimestamp

The timestamp of when the address list was last updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Analysis

The result of an analysis can be used in conditions to trigger actions. Analyses can inspect the email content and report a certain aspect of the email.

Contents

Analyzer

The Amazon Resource Name (ARN) of an Add On.

Type: String

Pattern: `[a-zA-Z0-9: _/+=, @. #- ]+`

Required: Yes

ResultField

The returned value from an Add On.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `(addon\. )?[\sa-zA-Z0-9_ ]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Archive

An archive resource for storing and retaining emails.

Contents

ArchiveId

The unique identifier of the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

ArchiveName

The unique name assigned to the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]*[a-zA-Z0-9]`

Required: No

ArchiveState

The current state of the archive:

- **ACTIVE** – The archive is ready and available for use.
- **PENDING_DELETION** – The archive has been marked for deletion and will be permanently deleted in 30 days. No further modifications can be made in this state.

Type: String

Valid Values: **ACTIVE** | **PENDING_DELETION**

Required: No

LastUpdatedTimestamp

The timestamp of when the archive was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveAction

The action to archive the email by delivering the email to an Amazon SES archive.

Contents

TargetArchive

The identifier of the archive to send the email to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified archive has been deleted.

Type: String

Valid Values: CONTINUE | DROP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveBooleanExpression

A boolean expression to evaluate email attribute values.

Contents

Evaluate

The email attribute value to evaluate.

Type: [ArchiveBooleanToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The boolean operator to use for evaluation.

Type: String

Valid Values: IS_TRUE | IS_FALSE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveBooleanToEvaluate

The attribute to evaluate in a boolean expression.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

The name of the email attribute to evaluate.

Type: String

Valid Values: HAS_ATTACHMENTS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveFilterCondition

A filter condition used to include or exclude emails when exporting from or searching an archive.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

BooleanExpression

A boolean expression to evaluate against email attributes.

Type: [ArchiveBooleanExpression](#) object

Required: No

StringExpression

A string expression to evaluate against email attributes.

Type: [ArchiveStringExpression](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveFilters

A set of filter conditions to include and/or exclude emails.

Contents

Include

The filter conditions for emails to include.

Type: Array of [ArchiveFilterCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Unless

The filter conditions for emails to exclude.

Type: Array of [ArchiveFilterCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveRetention

The retention policy for an email archive that specifies how long emails are kept before being automatically deleted.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

RetentionPeriod

The enum value sets the period for retaining emails in an archive.

Type: String

Valid Values: THREE_MONTHS | SIX_MONTHS | NINE_MONTHS | ONE_YEAR | EIGHTEEN_MONTHS | TWO_YEARS | THIRTY_MONTHS | THREE_YEARS | FOUR_YEARS | FIVE_YEARS | SIX_YEARS | SEVEN_YEARS | EIGHT_YEARS | NINE_YEARS | TEN_YEARS | PERMANENT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveStringExpression

A string expression to evaluate an email attribute value against one or more string values.

Contents

Evaluate

The attribute of the email to evaluate.

Type: [ArchiveStringToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The operator to use when evaluating the string values.

Type: String

Valid Values: CONTAINS

Required: Yes

Values

The list of string values to evaluate the email attribute against.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveStringToEvaluate

Specifies the email attribute to evaluate in a string expression.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

The name of the email attribute to evaluate.

Type: String

Valid Values: TO | FROM | CC | SUBJECT | ENVELOPE_TO | ENVELOPE_FROM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeliverToMailboxAction

This action to delivers an email to a mailbox.

Contents

MailboxArn

The Amazon Resource Name (ARN) of a WorkMail organization to deliver the email to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of an IAM role to use to execute this action. The role must have access to the workmail:DeliverToMailbox API.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the mailbox ARN is no longer valid.

Type: String

Valid Values: CONTINUE | DROP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeliverToQBusinessAction

The action to deliver incoming emails to an Amazon Q Business application for indexing.

Contents

ApplicationId

The unique identifier of the Amazon Q Business application instance where the email content will be delivered.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-z0-9-]+`

Required: Yes

IndexId

The identifier of the knowledge base index within the Amazon Q Business application where the email content will be stored and indexed.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-z0-9-]+`

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of the IAM Role to use while delivering to Amazon Q Business. This role must have access to the `qbusiness:BatchPutDocument` API for the given application and index.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=@.#-]+`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified application has been deleted or the role lacks necessary permissions to call the `qbusiness:BatchPutDocument` API.

Type: String

Valid Values: CONTINUE | DROP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DropAction

This action causes processing to stop and the email to be dropped. If the action applies only to certain recipients, only those recipients are dropped, and processing continues for other recipients.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Envelope

The SMTP envelope information of the email.

Contents

From

The RCPT FROM given by the host from which the email was received.

Type: String

Required: No

Helo

The HELO used by the host from which the email was received.

Type: String

Required: No

To

All SMTP TO entries given by the host from which the email was received.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportDestinationConfiguration

The destination configuration for delivering exported email data.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

S3

Configuration for delivering to an Amazon S3 bucket.

Type: [S3ExportDestinationConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportStatus

The current status of an archive export job.

Contents

CompletionTimestamp

The timestamp of when the export job completed (if finished).

Type: Timestamp

Required: No

ErrorMessage

An error message if the export job failed.

Type: String

Required: No

State

The current state of the export job.

Type: String

Valid Values: QUEUED | PREPROCESSING | PROCESSING | COMPLETED | FAILED | CANCELLED

Required: No

SubmissionTimestamp

The timestamp of when the export job was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportSummary

Summary statuses of an archive export job.

Contents

ExportId

The unique identifier of the export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Status

The current status of the export job.

Type: [ExportStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportDataFormat

The import data format contains the specifications of the input file that would be passed to the address list import job.

Contents

ImportDataType

The type of file that would be passed as an input for the address list import job.

Type: String

Valid Values: CSV | JSON

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportJob

Details about an import job.

Contents

AddressListId

The unique identifier of the address list the import job was created for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

CreatedTimestamp

The timestamp of when the import job was created.

Type: Timestamp

Required: Yes

ImportDataFormat

The format of the input for the import job.

Type: [ImportDataFormat](#) object

Required: Yes

JobId

The identifier of the import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Name

A user-friendly name for the import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

PreSignedUrl

The pre-signed URL target for uploading the input file.

Type: String

Required: Yes

Status

The status of the import job.

Type: String

Valid Values: CREATED | PROCESSING | COMPLETED | FAILED | STOPPED

Required: Yes

CompletedTimestamp

The timestamp of when the import job was completed.

Type: Timestamp

Required: No

Error

The reason for failure of an import job.

Type: String

Required: No

FailedItemsCount

The number of addresses in the input that failed to get imported into address list.

Type: Integer

Required: No

ImportedItemsCount

The number of addresses in the input that were successfully imported into the address list.

Type: Integer

Required: No

StartTimestamp

The timestamp of when the import job was started.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressAnalysis

The Add On ARN and its returned value that is evaluated in a policy statement's conditional expression to either deny or block the incoming email.

Contents

Analyzer

The Amazon Resource Name (ARN) of an Add On.

Type: String

Pattern: `[a-zA-Z0-9: _/+=, @. # - ]+`

Required: Yes

ResultField

The returned value from an Add On.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `(addon\. )?[\sa-zA-Z0-9_ ]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressBooleanExpression

The structure for a boolean condition matching on the incoming mail.

Contents

Evaluate

The operand on which to perform a boolean condition operation.

Type: [IngressBooleanToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a boolean condition expression.

Type: String

Valid Values: IS_TRUE | IS_FALSE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressBooleanToEvaluate

The union type representing the allowed types of operands for a boolean condition.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Analysis

The structure type for a boolean condition stating the Add On ARN and its returned value.

Type: [IngressAnalysis](#) object

Required: No

IsInAddressList

The structure type for a boolean condition that provides the address lists to evaluate incoming traffic on.

Type: [IngressIsInAddressList](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressIpToEvaluate

The structure for an IP based condition matching on the incoming mail.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

An enum type representing the allowed attribute types for an IP condition.

Type: String

Valid Values: SENDER_IP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressIpv4Expression

The union type representing the allowed types for the left hand side of an IP condition.

Contents

Evaluate

The left hand side argument of an IP condition expression.

Type: [IngressIpToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for an IP condition expression.

Type: String

Valid Values: CIDR_MATCHES | NOT_CIDR_MATCHES

Required: Yes

Values

The right hand side argument of an IP condition expression.

Type: Array of strings

Pattern: ((25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)/([0-9]|[12][0-9]|3[0-2])

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressIpv6Expression

The union type representing the allowed types for the left hand side of an IPv6 condition.

Contents

Evaluate

The left hand side argument of an IPv6 condition expression.

Type: [IngressIpv6ToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for an IPv6 condition expression.

Type: String

Valid Values: CIDR_MATCHES | NOT_CIDR_MATCHES

Required: Yes

Values

The right hand side argument of an IPv6 condition expression.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 49.

Pattern: `(([0-9a-fA-F]{1,4}:){7}[0-9a-fA-F]{1,4}|([0-9a-fA-F]{1,4}:){1,7}:|([0-9a-fA-F]{1,4}:){1,6}:[0-9a-fA-F]{1,4}|([0-9a-fA-F]{1,4}:){1,5}(:[0-9a-fA-F]{1,4}){1,2}|([0-9a-fA-F]{1,4}:){1,4}(:[0-9a-fA-F]{1,4}){1,3}|([0-9a-fA-F]{1,4}:){1,3}(:[0-9a-fA-F]{1,4}){1,4}|([0-9a-fA-F]{1,4}:){1,2}(:[0-9a-fA-F]{1,4}){1,5}|[0-9a-fA-F]{1,4}:((:[0-9a-fA-F]{1,4}){1,6})|(:([0-9a-fA-F]{1,4}){1,7}|:))\/(12[0-8]|1[0-1][0-9]|[1-9][0-9]|[0-9])`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressIpv6ToEvaluate

The structure for an IPv6 based condition matching on the incoming mail.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

An enum type representing the allowed attribute types for an IPv6 condition.

Type: String

Valid Values: SENDER_IPV6

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressIsInAddressList

The address lists and the address list attribute value that is evaluated in a policy statement's conditional expression to either deny or block the incoming email.

Contents

AddressLists

The address lists that will be used for evaluation.

Type: Array of strings

Array Members: Fixed number of 1 item.

Required: Yes

Attribute

The email attribute that needs to be evaluated against the address list.

Type: String

Valid Values: RECIPIENT

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressPoint

The structure of an ingress endpoint resource.

Contents

IngressPointId

The identifier of the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

IngressPointName

A user friendly name for the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: Yes

Status

The status of the ingress endpoint resource.

Type: String

Valid Values: PROVISIONING | DEPROVISIONING | UPDATING | ACTIVE | CLOSED | FAILED

Required: Yes

Type

The type of ingress endpoint resource.

Type: String

Valid Values: OPEN | AUTH

Required: Yes

ARecord

The DNS A Record that identifies your ingress endpoint. Configure your DNS Mail Exchange (MX) record with this value to route emails to Mail Manager.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressPointAuthConfiguration

The authentication configuration for the ingress endpoint resource.

Contents

IngressPointPasswordConfiguration

The ingress endpoint password configuration for the ingress endpoint resource.

Type: [IngressPointPasswordConfiguration](#) object

Required: No

SecretArn

The ingress endpoint SecretsManager::Secret ARN configuration for the ingress endpoint resource.

Type: String

Pattern: `arn:(aws|aws-cn|aws-us-gov|aws-eusc):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressPointConfiguration

The configuration of the ingress endpoint resource.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

SecretArn

The SecretsManager::Secret ARN of the ingress endpoint resource.

Type: String

Pattern: `arn:(aws|aws-cn|aws-us-gov|aws-eusc):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+`

Required: No

Smtppassword

The password of the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 64.

Pattern: `[A-Za-z0-9!@#$%^&*()_+\-=\[\]\{\} | . , ? ]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressPointPasswordConfiguration

The password configuration of the ingress endpoint resource.

Contents

PreviousSmtplibPasswordExpiryTimestamp

The previous password expiry timestamp of the ingress endpoint resource.

Type: Timestamp

Required: No

PreviousSmtplibPasswordVersion

The previous password version of the ingress endpoint resource.

Type: String

Required: No

SmtplibPasswordVersion

The current password expiry timestamp of the ingress endpoint resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressStringExpression

The structure for a string based condition matching on the incoming mail.

Contents

Evaluate

The left hand side argument of a string condition expression.

Type: [IngressStringToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a string condition expression.

Type: String

Valid Values: EQUALS | NOT_EQUALS | STARTS_WITH | ENDS_WITH | CONTAINS

Required: Yes

Values

The right hand side argument of a string condition expression.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressStringToEvaluate

The union type representing the allowed types for the left hand side of a string condition.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Analysis

The structure type for a string condition stating the Add On ARN and its returned value.

Type: [IngressAnalysis](#) object

Required: No

Attribute

The enum type representing the allowed attribute types for a string condition.

Type: String

Valid Values: RECIPIENT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressTlsProtocolExpression

The structure for a TLS related condition matching on the incoming mail.

Contents

Evaluate

The left hand side argument of a TLS condition expression.

Type: [IngressTlsProtocolToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a TLS condition expression.

Type: String

Valid Values: MINIMUM_TLS_VERSION | IS

Required: Yes

Value

The right hand side argument of a TLS condition expression.

Type: String

Valid Values: TLS1_2 | TLS1_3

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

IngressTlsProtocolToEvaluate

The union type representing the allowed types for the left hand side of a TLS condition.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

The enum type representing the allowed attribute types for the TLS condition.

Type: String

Valid Values: TLS_PROTOCOL

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MessageBody

The textual body content of an email message.

Contents

Html

The HTML body content of the message.

Type: String

Required: No

MessageMalformed

A flag indicating if the email was malformed.

Type: Boolean

Required: No

Text

The plain text body content of the message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Metadata

The metadata about the email.

Contents

ConfigurationSet

The name of the configuration set used when sent through a configuration set with archiving enabled.

Type: String

Required: No

IngressPointId

The ID of the ingress endpoint through which the email was received.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RuleSetId

The ID of the rule set that processed the email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

SenderHostname

The name of the host from which the email was received.

Type: String

Required: No

SenderIpAddress

The IP address of the host from which the email was received.

Type: String

Required: No

SendingMethod

The name of the API call used when sent through a configuration set with archiving enabled.

Type: String

Required: No

SendingPool

The name of the dedicated IP pool used when sent through a configuration set with archiving enabled.

Type: String

Required: No

SourceArn

Specifies the archived email source, identified by either a Rule Set's ARN with an Archive action, or a Configuration Set's Archive ARN.

Type: String

Required: No

SourceIdentity

The identity name used to authorize the sending action when sent through a configuration set with archiving enabled.

Type: String

Required: No

Timestamp

The timestamp of when the email was received.

Type: Timestamp

Required: No

TlsCipherSuite

The TLS cipher suite used to communicate with the host from which the email was received.

Type: String

Required: No

TlsProtocol

The TLS protocol used to communicate with the host from which the email was received.

Type: String

Required: No

TrafficPolicyId

The ID of the traffic policy that was in effect when the email was received.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkConfiguration

The network type (IPv4-only, Dual-Stack, PrivateLink) of the ingress endpoint resource.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

PrivateNetworkConfiguration

Specifies the network configuration for the private ingress point.

Type: [PrivateNetworkConfiguration](#) object

Required: No

PublicNetworkConfiguration

Specifies the network configuration for the public ingress point.

Type: [PublicNetworkConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NoAuthentication

Explicitly indicate that the relay destination server does not require SMTP credential authentication.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyCondition

The email traffic filtering conditions which are contained in a traffic policy resource.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

BooleanExpression

This represents a boolean type condition matching on the incoming mail. It performs the boolean operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressBooleanExpression](#) object

Required: No

IpExpression

This represents an IP based condition matching on the incoming mail. It performs the operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressIpv4Expression](#) object

Required: No

Ipv6Expression

This represents an IPv6 based condition matching on the incoming mail. It performs the operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressIpv6Expression](#) object

Required: No

StringExpression

This represents a string based condition matching on the incoming mail. It performs the string operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressStringExpression](#) object

Required: No

TlsExpression

This represents a TLS based condition matching on the incoming mail. It performs the operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressTlsProtocolExpression](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyStatement

The structure containing traffic policy conditions and actions.

Contents

Action

The action that informs a traffic policy resource to either allow or block the email if it matches a condition in the policy statement.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

Conditions

The list of conditions to apply to incoming messages for filtering email traffic.

Type: Array of [PolicyCondition](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PrivateNetworkConfiguration

Specifies the network configuration for the private ingress point.

Contents

VpcEndpointId

The identifier of the VPC endpoint to associate with this private ingress point.

Type: String

Pattern: `vpce-[a-zA-Z0-9]{17}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PublicNetworkConfiguration

Specifies the network configuration for the public ingress point.

Contents

IpType

The IP address type for the public ingress point. Valid values are IPV4 and DUAL_STACK.

Type: String

Valid Values: IPV4 | DUAL_STACK

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Relay

The relay resource that can be used as a rule to relay receiving emails to the destination relay server.

Contents

LastModifiedTimestamp

The timestamp of when the relay was last modified.

Type: Timestamp

Required: No

RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: No

RelayName

The unique relay name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-_]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RelayAction

The action relays the email via SMTP to another specific SMTP server.

Contents

Relay

The identifier of the relay resource to be used when relaying an email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified relay has been deleted.

Type: String

Valid Values: `CONTINUE` | `DROP`

Required: No

MailFrom

This action specifies whether to preserve or replace original mail from address while relaying received emails to a destination server.

Type: String

Valid Values: `REPLACE` | `PRESERVE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RelayAuthentication

Authentication for the relay destination server—specify the `secretARN` where the SMTP credentials are stored, or specify an empty `NoAuthentication` structure if the relay destination server does not require SMTP credential authentication.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

NoAuthentication

Keep an empty structure if the relay destination server does not require SMTP credential authentication.

Type: [NoAuthentication](#) object

Required: No

SecretArn

The ARN of the secret created in secrets manager where the relay server's SMTP credentials are stored.

Type: String

Pattern: `arn:(aws|aws-cn|aws-us-gov|aws-eusc):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplaceRecipientAction

This action replaces the email envelope recipients with the given list of recipients. If the condition of this action applies only to a subset of recipients, only those recipients are replaced with the recipients specified in the action. The message contents and headers are unaffected by this action, only the envelope recipients are updated.

Contents

ReplaceWith

This action specifies the replacement recipient email addresses to insert.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 254.

Pattern: `[a-zA-Z0-9._+-]+@[a-zA-Z0-9.-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Row

A result row containing metadata for an archived email message.

Contents

ArchivedMessageId

The unique identifier of the archived message.

Type: String

Required: No

Cc

The email addresses in the CC header.

Type: String

Required: No

Date

The date the email was sent.

Type: String

Required: No

Envelope

The SMTP envelope information of the email.

Type: [Envelope](#) object

Required: No

From

The email address of the sender.

Type: String

Required: No

HasAttachments

A flag indicating if the email has attachments.

Type: Boolean

Required: No

IngressPointId

The ID of the ingress endpoint through which the email was received.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

InReplyTo

The email message ID this is a reply to.

Type: String

Required: No

MessageId

The unique message ID of the email.

Type: String

Required: No

ReceivedHeaders

The received headers from the email delivery path.

Type: Array of strings

Required: No

ReceivedTimestamp

The timestamp of when the email was received.

Type: Timestamp

Required: No

SenderHostname

The name of the host from which the email was received.

Type: String

Required: No

SenderIpAddress

- Mail archived with Mail Manager: The IP address of the client that connects to the ingress endpoint.
- Mail sent through a configuration set with the archiving option enabled: The IP address of the client that makes the SendEmail API call.

Type: String

Required: No

SourceArn

Specifies the archived email source, identified by either a Rule Set's ARN with an Archive action, or a Configuration Set's Archive ARN.

Type: String

Required: No

Subject

The subject header value of the email.

Type: String

Required: No

To

The email addresses in the To header.

Type: String

Required: No

XMailer

The user agent that sent the email.

Type: String

Required: No

XOriginalMailer

The original user agent that sent the email.

Type: String

Required: No

XPriority

The priority level of the email.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Rule

A rule contains conditions, "unless conditions" and actions. For each envelope recipient of an email, if all conditions match and none of the "unless conditions" match, then all of the actions are executed sequentially. If no conditions are provided, the rule always applies and the actions are implicitly executed. If only "unless conditions" are provided, the rule applies if the email does not match the evaluation of the "unless conditions".

Contents

Actions

The list of actions to execute when the conditions match the incoming email, and none of the "unless conditions" match.

Type: Array of [RuleAction](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Conditions

The conditions of this rule. All conditions must match the email for the actions to be executed. An empty list of conditions means that all emails match, but are still subject to any "unless conditions"

Type: Array of [RuleCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Name

The user-friendly name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

Unless

The "unless conditions" of this rule. None of the conditions can match the email for the actions to be executed. If any of these conditions do match the email, then the actions are not executed.

Type: Array of [RuleCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleAction

The action for a rule to take. Only one of the contained actions can be set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

AddHeader

This action adds a header. This can be used to add arbitrary email headers.

Type: [AddHeaderAction](#) object

Required: No

Archive

This action archives the email. This can be used to deliver an email to an archive.

Type: [ArchiveAction](#) object

Required: No

DeliverToMailbox

This action delivers an email to a WorkMail mailbox.

Type: [DeliverToMailboxAction](#) object

Required: No

DeliverToQBusiness

This action delivers an email to an Amazon Q Business application for ingestion into its knowledge base.

Type: [DeliverToQBusinessAction](#) object

Required: No

Drop

This action terminates the evaluation of rules in the rule set.

Type: [DropAction](#) object

Required: No

PublishToSns

This action publishes the email content to an Amazon SNS topic.

Type: [SnsAction](#) object

Required: No

Relay

This action relays the email to another SMTP server.

Type: [RelayAction](#) object

Required: No

ReplaceRecipient

The action replaces certain or all recipients with a different set of recipients.

Type: [ReplaceRecipientAction](#) object

Required: No

Send

This action sends the email to the internet.

Type: [SendAction](#) object

Required: No

WriteToS3

This action writes the MIME content of the email to an S3 bucket.

Type: [S3Action](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleBooleanExpression

A boolean expression to be used in a rule condition.

Contents

Evaluate

The operand on which to perform a boolean condition operation.

Type: [RuleBooleanToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a boolean condition expression.

Type: String

Valid Values: IS_TRUE | IS_FALSE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleBooleanToEvaluate

The union type representing the allowed types of operands for a boolean condition.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Analysis

The Add On ARN and its returned value to evaluate in a boolean condition expression.

Type: [Analysis](#) object

Required: No

Attribute

The boolean type representing the allowed attribute types for an email.

Type: String

Valid Values: READ_RECEIPT_REQUESTED | TLS | TLS_WRAPPED

Required: No

IsInAddressList

The structure representing the address lists and address list attribute that will be used in evaluation of boolean expression.

Type: [RuleIsInAddressList](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleCondition

The conditional expression used to evaluate an email for determining if a rule action should be taken.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

BooleanExpression

The condition applies to a boolean expression passed in this field.

Type: [RuleBooleanExpression](#) object

Required: No

DmarcExpression

The condition applies to a DMARC policy expression passed in this field.

Type: [RuleDmarcExpression](#) object

Required: No

IpExpression

The condition applies to an IP address expression passed in this field.

Type: [RuleIpExpression](#) object

Required: No

NumberExpression

The condition applies to a number expression passed in this field.

Type: [RuleNumberExpression](#) object

Required: No

StringExpression

The condition applies to a string expression passed in this field.

Type: [RuleStringExpression](#) object

Required: No

VerdictExpression

The condition applies to a verdict expression passed in this field.

Type: [RuleVerdictExpression](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleDmarcExpression

A DMARC policy expression. The condition matches if the given DMARC policy matches that of the incoming email.

Contents

Operator

The operator to apply to the DMARC policy of the incoming email.

Type: String

Valid Values: EQUALS | NOT_EQUALS

Required: Yes

Values

The values to use for the given DMARC policy operator. For the operator EQUALS, if multiple values are given, they are evaluated as an OR. That is, if any of the given values match, the condition is deemed to match. For the operator NOT_EQUALS, if multiple values are given, they are evaluated as an AND. That is, only if the email's DMARC policy is not equal to any of the given values, then the condition is deemed to match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Valid Values: NONE | QUARANTINE | REJECT

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleIpExpression

An IP address expression matching certain IP addresses within a given range of IP addresses.

Contents

Evaluate

The IP address to evaluate in this condition.

Type: [RuleIpToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The operator to evaluate the IP address.

Type: String

Valid Values: CIDR_MATCHES | NOT_CIDR_MATCHES

Required: Yes

Values

The IP CIDR blocks in format "x.y.z.w/n" (eg 10.0.0.0/8) to match with the email's IP address. For the operator CIDR_MATCHES, if multiple values are given, they are evaluated as an OR. That is, if the IP address is contained within any of the given CIDR ranges, the condition is deemed to match. For NOT_CIDR_MATCHES, if multiple CIDR ranges are given, the condition is deemed to match if the IP address is not contained in any of the given CIDR ranges.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 43.

Pattern: (([0-9]|.|:|/)*)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleIpToEvaluate

The IP address to evaluate for this condition.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

The attribute of the email to evaluate.

Type: String

Valid Values: SOURCE_IP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RulesInAddressList

The structure type for a boolean condition that provides the address lists and address list attribute to evaluate.

Contents

AddressLists

The address lists that will be used for evaluation.

Type: Array of strings

Array Members: Fixed number of 1 item.

Required: Yes

Attribute

The email attribute that needs to be evaluated against the address list.

Type: String

Valid Values: RECIPIENT | MAIL_FROM | SENDER | FROM | TO | CC

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleNumberExpression

A number expression to match numeric conditions with integers from the incoming email.

Contents

Evaluate

The number to evaluate in a numeric condition expression.

Type: [RuleNumberToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The operator for a numeric condition expression.

Type: String

Valid Values: EQUALS | NOT_EQUALS | LESS_THAN | GREATER_THAN |
LESS_THAN_OR_EQUAL | GREATER_THAN_OR_EQUAL

Required: Yes

Value

The value to evaluate in a numeric condition expression.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

RuleNumberToEvaluate

The number to evaluate in a numeric condition expression.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Attribute

An email attribute that is used as the number to evaluate.

Type: String

Valid Values: MESSAGE_SIZE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleSet

A rule set contains a list of rules that are evaluated in order. Each rule is evaluated sequentially for each email.

Contents

LastModificationDate

The last modification date of the rule set.

Type: Timestamp

Required: No

RuleSetId

The identifier of the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RuleSetName

A user-friendly name for the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleStringExpression

A string expression is evaluated against strings or substrings of the email.

Contents

Evaluate

The string to evaluate in a string condition expression.

Type: [RuleStringToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a string condition expression.

Type: String

Valid Values: EQUALS | NOT_EQUALS | STARTS_WITH | ENDS_WITH | CONTAINS

Required: Yes

Values

The string(s) to be evaluated in a string condition expression. For all operators, except for NOT_EQUALS, if multiple values are given, the values are processed as an OR. That is, if any of the values match the email's string using the given operator, the condition is deemed to match. However, for NOT_EQUALS, the condition is only deemed to match if none of the given strings match the email's string.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleStringToEvaluate

The string to evaluate in a string condition expression.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Analysis

The Add On ARN and its returned value to evaluate in a string condition expression.

Type: [Analysis](#) object

Required: No

Attribute

The email attribute to evaluate in a string condition expression.

Type: String

Valid Values: MAIL_FROM | HELO | RECIPIENT | SENDER | FROM | SUBJECT | TO | CC

Required: No

MimeHeaderAttribute

The email MIME X-Header attribute to evaluate in a string condition expression.

Type: String

Pattern: X-[a-zA-Z0-9-]{1,256}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleVerdictExpression

A verdict expression is evaluated against verdicts of the email.

Contents

Evaluate

The verdict to evaluate in a verdict condition expression.

Type: [RuleVerdictToEvaluate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Operator

The matching operator for a verdict condition expression.

Type: String

Valid Values: EQUALS | NOT_EQUALS

Required: Yes

Values

The values to match with the email's verdict using the given operator. For the EQUALS operator, if multiple values are given, the condition is deemed to match if any of the given verdicts match that of the email. For the NOT_EQUALS operator, if multiple values are given, the condition is deemed to match if none of the given verdicts match the verdict of the email.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Valid Values: PASS | FAIL | GRAY | PROCESSING_FAILED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleVerdictToEvaluate

The verdict to evaluate in a verdict condition expression.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Analysis

The Add On ARN and its returned value to evaluate in a verdict condition expression.

Type: [Analysis](#) object

Required: No

Attribute

The email verdict attribute to evaluate in a string verdict expression.

Type: String

Valid Values: SPF | DKIM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Action

Writes the MIME content of the email to an S3 bucket.

Contents

RoleArn

The Amazon Resource Name (ARN) of the IAM Role to use while writing to S3. This role must have access to the `s3:PutObject`, `kms:Encrypt`, and `kms:GenerateDataKey` APIs for the given bucket.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

S3Bucket

The bucket name of the S3 bucket to write to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `[a-zA-Z0-9.- ]+`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified the bucket has been deleted.

Type: String

Valid Values: `CONTINUE` | `DROP`

Required: No

S3Prefix

The S3 prefix to use for the write to the s3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: [a-zA-Z0-9!_.*'()/-]+

Required: No

S3SseKmsKeyId

The KMS Key ID to use to encrypt the message in S3.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: [a-zA-Z0-9-:/]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ExportDestinationConfiguration

The configuration for exporting email data to an Amazon S3 bucket.

Contents

S3Location

The S3 location to deliver the exported email data.

Type: String

Pattern: `s3://[a-zA-Z0-9.-]{3,63}(/[a-zA-Z0-9!_.*'()/-]*)*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SavedAddress

An address that is a member of an address list.

Contents

Address

The email or domain that constitutes the address.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 320.

Required: Yes

CreatedTimestamp

The timestamp of when the address was added to the address list.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchStatus

The current status of an archive search job.

Contents

CompletionTimestamp

The timestamp of when the search completed (if finished).

Type: Timestamp

Required: No

ErrorMessage

An error message if the search failed.

Type: String

Required: No

State

The current state of the search job.

Type: String

Valid Values: QUEUED | RUNNING | COMPLETED | FAILED | CANCELLED

Required: No

SubmissionTimestamp

The timestamp of when the search was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchSummary

Summary details of an archive search job.

Contents

SearchId

The unique identifier of the search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Status

The current status of the search job.

Type: [SearchStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SendAction

Sends the email to the internet using the ses:SendRawEmail API.

Contents

RoleArn

The Amazon Resource Name (ARN) of the role to use for this action. This role must have access to the ses:SendRawEmail API.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: [a-zA-Z0-9:_/+=, @. #-]+

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the caller does not have the permissions to call the sendRawEmail API.

Type: String

Valid Values: CONTINUE | DROP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SnsAction

The action to publish the email content to an Amazon SNS topic. When executed, this action will send the email as a notification to the specified SNS topic.

Contents

RoleArn

The Amazon Resource Name (ARN) of the IAM Role to use while writing to Amazon SNS. This role must have access to the `sns:Publish` API for the given topic.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `[a-zA-Z0-9:_/+=, @. #- ]+`

Required: Yes

TopicArn

The Amazon Resource Name (ARN) of the Amazon SNS Topic to which notification for the email received will be published.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov|aws-eusc):sns:[a-z0-9-]+:\d{12}:[\w\-\]{1,256}`

Required: Yes

ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, specified SNS topic has been deleted or the role lacks necessary permissions to call the `sns:Publish` API.

Type: String

Valid Values: `CONTINUE` | `DROP`

Required: No

Encoding

The encoding to use for the email within the Amazon SNS notification. The default value is UTF-8. Use BASE64 if you need to preserve all special characters, especially when the original message uses a different encoding format.

Type: String

Valid Values: UTF-8 | BASE64

Required: No

PayloadType

The expected payload type within the Amazon SNS notification. CONTENT attempts to publish the full email content with 20KB of headers content. HEADERS extracts up to 100KB of header content to include in the notification, email content will not be included to the notification. The default value is CONTENT.

Type: String

Valid Values: HEADERS | CONTENT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A key-value pair (the value is optional), that you can define and assign to AWS resources.

Contents

Key

The key of the key-value tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9/_\+=\.\:@\-\ ]+`

Required: Yes

Value

The value of the key-value tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[a-zA-Z0-9/_\+=\.\:@\-\ ]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrafficPolicy

The structure of a traffic policy resource which is a container for policy statements.

Contents

DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: Yes

TrafficPolicyId

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

TrafficPolicyName

A user-friendly name of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [A-Za-z0-9_\-]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400